

Toad[®] for Oracle 17.0 Patch 1

Release Notes

Revised 1/16/2024

Contents

- About Toad for Oracle** **4**
 - Toad for Oracle resources 4
 - About this release 4

- About Toad[®] for Oracle[®] Editions** **5**
 - Toad for Oracle Subscription 5
 - Toad for Oracle non-Subscription 6
 - Toad for Oracle on Mac 7
 - Install 8
 - Uninstall 8

- New Features and Enhancements** **9**
 - Toad for Oracle 17.0 9
 - Toad for Oracle on Mac 9
 - Oracle 23c 9
 - Editor 9
 - Connections 10
 - Connection Colors 10
 - Trace File Browser 10
 - Object Palette 10
 - Automation Designer 10
 - Data Grids 10
 - Compare Schemas 11
 - Generate Schema Script 11
 - Schema Browser 11
 - Session Browser 11
 - Import Table Data 11
 - Workspaces 11
 - Debugger 11
 - DB Health Scan (Preview) 11
 - SQL*Net Editor 12
 - TNSNames Editor 12
 - Toad for Oracle 16.3 12

| | |
|--|-----------|
| Editor | 12 |
| Schema Browser | 12 |
| Color Schemes/Dark Mode | 13 |
| Automation Designer | 13 |
| Data Grids | 13 |
| Export Dataset | 13 |
| Window Bar/Menu | 14 |
| Login Window/Connections | 14 |
| Export DDL | 14 |
| SQL Recall | 14 |
| Manage User Settings | 14 |
| Miscellaneous | 15 |
| Toad for Oracle 16.2 | 15 |
| Data Grids | 15 |
| Fonts | 15 |
| Color Schemes/Dark Mode | 15 |
| Login Window/Connections | 15 |
| Automation Designer | 16 |
| Editor | 16 |
| Execute/Compile | 16 |
| Generate Schema Script, HTML Schema Doc Generator, and Compare Schemas | 16 |
| Schema Browser | 16 |
| Describe Dialogs | 16 |
| Compare Files | 16 |
| Toad Debug Mode | 17 |
| Discontinued Features | 19 |
| Resolved issues | 20 |
| Toad for Oracle 17.0 Patch 1 | 20 |
| Toad for Oracle 17.0 | 21 |
| Toad for Oracle 16.3 | 24 |
| Toad for Oracle 16.2 | 28 |
| Known issues | 31 |
| General known issues | 31 |
| Oracle client known issues | 32 |
| Proxy server known issues | 32 |
| Data Grids known issues | 33 |
| Code Analysis known issues | 34 |
| Editor known issues | 34 |
| Session Browser known issues | 34 |
| Team Coding known issues | 35 |
| Unicode known issues | 35 |
| High DPI known issues | 36 |
| Toad for Oracle on Mac known issues | 36 |
| Third-party known issues | 37 |

| | |
|---|-----------|
| System requirements | 38 |
| Hardware requirements | 38 |
| Database requirements | 39 |
| Network | 40 |
| Additional requirements | 40 |
| Virtualization support | 40 |
| Windows Privileges | 41 |
| Product licensing | 42 |
| Legacy Toad for Oracle with offline license keys | 42 |
| Toad for Oracle Subscription with online licensing (including Editions) | 42 |
| Getting started with Toad for Oracle | 44 |
| Upgrade and installation instructions | 44 |
| User instructions | 44 |
| Additional resources | 44 |
| Globalization | 45 |
| Global Operation Statement | 45 |
| About us | 46 |
| Contacting Quest | 46 |
| Technical support resources | 46 |

About Toad for Oracle

Toad for Oracle provides an intuitive and efficient way for database professionals of all skill and experience levels to perform their jobs with an overall improvement in workflow effectiveness and productivity. With Toad for Oracle you can:

- Understand your database environment through visual representations
- Meet deadlines easily through automation and smooth workflows
- Perform essential development and administration tasks from a single tool
- Deploy high-quality applications that meet user requirements; perform predictably and reliably in production
- Validate database code to ensure the best-possible performance and adherence to best-practice standards
- Manage and share projects, templates, scripts, and more with ease

The Toad for Oracle solutions are built for you, by you. Nearly two decades of development and feedback from various communities like Toad World have made it the most powerful and functional tool available. With an installed-base of over two million, Toad for Oracle continues to be the "de facto" standard tool for database development and administration.

Toad for Oracle resources

Toad World is a unique and valuable resource available to all Toad users. Toad World provides forums, blogs, videos, product information, Beta releases (when available), and Trial downloads for Toad products. Visit Toad World at: <https://www.toadworld.com>.

Two of the most-often used features of Toad World are the Forums and the Idea Pond.

- On the Idea Pond page, you can submit your ideas to improve Toad and vote for or comment on other ideas. The Toad team takes your suggestions seriously, and you may even hear back from one of our developers on the topic. We encourage all Toad users—from new to experienced—to let us know how we can improve Toad.
- On the Forum page, you can ask a question or start a discussion and view all other forums within the Toad community.

The Toad World blog pages feature a broad range of information, including topics of interest to our industry, as well as instructions from team members on how to use the latest Toad features.

The Toad for Oracle [web-based training](#) is a perfect accompaniment to your product license. This free training walks you through major product features and explains how to perform frequent tasks. You'll also see how to utilize time-saving automation functionality. You'll receive a certificate of completion for each course once you pass the accompanying test.

About this release

Toad for Oracle 17.0 Patch 1 is a minor release, with enhanced features and functionality.

Toad for Oracle 17.0 Patch 1 includes component and requirement upgrades. These upgrades address security vulnerabilities previously identified in the third party component.

About Toad[®] for Oracle[®] Editions

Each Toad for Oracle Edition is packaged with additional Quest products to expand your experience.

Toad for Oracle Subscription

Toad for Oracle is now available with subscription licensing. The benefits of subscription include:

- All of the great, award-winning Toad features you have grown to love
- Access to our world-class support team, Knowledge Base, how-to videos and more
- Quest Auto Update keeping you on the latest version
- [Online License Management](#) making it easy to assign licenses to individuals, keep track of individual usage, manage organizations, and reassign unused or under-used licenses as needed to ensure license compliance
- Automatic Renewal ensuring that Toad for Oracle Subscription will be continuously available to users
- Invitations to training events like our Ask Toad and Toad Training Tuesdays series

The following products may be part of your Toad for Oracle Subscription Edition:

- [Toad for Oracle](#)
- Benchmark Factory for Databases
- Code Tester for Oracle
- Spotlight on Oracle
- SQL Optimizer for Oracle
- Toad Data Modeler

The following Toad for Oracle Subscription Editions are available:

| Edition | Licensed |
|--|--|
| Toad for Oracle Base Subscription Edition | Toad [®] for Oracle [®] |
| Toad for Oracle Professional Subscription Edition | Toad [®] for Oracle [®] Professional |
| Toad for Oracle Professional DB Admin Subscription Edition | Everything in Toad [®] for Oracle [®] Professional DB Admin Module Add-on Sensitive Data Protection Add-on |
| Toad for Oracle Xpert Plus Edition | Everything in Toad [®] for Oracle [®] Professional DB Admin Edition SQL Optimizer for Oracle [®] |

| Edition | Licensed |
|--|--|
| Toad for Oracle Developer Plus Edition | Everything in Toad® for Oracle® Xpert Plus Code Tester for Oracle® Benchmark Factory® for Databases - Oracle Edition with 100 virtual users |
| Toad for Oracle DBA Plus Edition | Everything in Toad® for Oracle® Developer Plus Benchmark Factory® for Databases - Oracle Edition with 500 virtual users Toad® Data Modeler Spotlight on Oracle® |
| Toad for Oracle DBA RAC Plus Edition | Everything in Toad® for Oracle® DBA Plus Spotlight on Oracle® with RAC Option |
| Toad for Oracle DBA Exadata Plus Edition | Everything in Toad® for Oracle® DBA RAC Plus – Includes Exadata Spotlight on Oracle® with RAC and Exadata Options |

NOTE: Spotlight on Oracle® includes Spotlight on Unix/Linux, Spotlight on Windows, and Spotlight on Oracle® Data Guard.

Toad for Oracle non-Subscription

Toad for Oracle non-Subscription uses offline term and perpetual licensing. This is Toad for Oracle's legacy licensing model.

The following products may be part of your Toad for Oracle non-Subscription Edition:

- [Toad for Oracle](#)
- [Benchmark Factory for Databases](#)
- [Code Tester for Oracle](#)
- [Spotlight on Oracle](#)
- [SQL Optimizer for Oracle](#)
- [Toad Data Modeler](#)

The following Toad for Oracle non-Subscription Editions are available:

| Edition | Licensed |
|--------------------------------------|---|
| Toad for Oracle Base Edition | Toad® for Oracle® |
| Toad for Oracle Professional Edition | Toad® for Oracle® Professional |
| Toad for Oracle Xpert Edition | Everything in Toad® for Oracle® Professional SQL Optimizer for Oracle® |
| Toad for Oracle Developer Edition | Everything in Toad® for Oracle® Xpert |

| Edition | Licensed |
|-------------------------------------|--|
| | Code Tester for Oracle® Benchmark Factory® for Databases - Oracle Edition |
| Toad for Oracle DBA Edition | Everything in Toad® for Oracle® Developer DB Admin Module Add-on Spotlight on Oracle® Benchmark Factory® for Databases - Oracle Edition Toad® Data Modeler |
| Toad for Oracle DBA RAC Edition | Everything in Toad® for Oracle® DBA Spotlight on Oracle® with RAC Option |
| Toad for Oracle DBA Exadata Edition | Everything in Toad® for Oracle® DBA RAC – Includes Exadata Spotlight on Oracle® with RAC and Exadata Options |

NOTE: The DB Admin Module can be added to any Toad Edition. Spotlight on Oracle® includes Spotlight on Unix/Linux, Spotlight on Windows, and Spotlight on Oracle® Data Guard.

Toad for Oracle on Mac

Toad for Oracle is now available for Mac using a new license specific for macOS. Click [here](#) to download the free trial.

It includes the great, award-winning Toad features you have grown to love with a few limitations:

- There is no installer so setting Toad to be read-only or disable internet access using command-line arguments during installation is not possible
- Scheduling tasks and **Utilities | Task Scheduler** are unavailable
- Auto Update is unavailable in the Subscription version
- The edition includes Toad for Oracle; additional Quest products are not included
- Team Coding does not support VCS integration
- Excel Instance and Microsoft Access formats for Export/Import features are unsupported
- Only executables bundled with Toad may be launched (e.g. Toad Script Runner); other external applications and **Utilities | External Tools** are unsupported
- Font choosers may appear to duplicate fonts due to truncation; Courier New, Courier New Baltic, and Courier New Greek, for example, may all show as Courier New

- Only clientless connections are supported
 - Direct connect works as usual
 - TNS and LDAP connections work as usual provided the network configuration files (e.g. tnsnames.ora, ldap.ora, and sqlnet.ora) are found on disk in either of these folders:
 - **\$TNS_ADMIN**
 - **\$ORACLE_HOME/network/admin**
 - If **TNS_ADMIN** and **ORACLE_HOME** are not defined environment variables you may place the network configuration files in a special folder created by Toad upon first launch for this purpose; only one of these folders will exist depending on your version of Toad:
 - **~/Library/Application Support/Toad for Oracle/TnsAdmin**
 - **~/Library/Application Support/Toad for Oracle Subscription/TnsAdmin**

The following Toad for Oracle on Mac Editions are available:

| Edition | Licensed |
|---|--|
| Toad for Oracle on Mac Professional DB Admin Subscription Edition | Toad® for Oracle® Professional DB Admin Module Add-on Sensitive Data Protection Add-on |
| Toad for Oracle on Mac Professional DB Admin Edition | Toad® for Oracle® Professional DB Admin Module Add-on |

Install

1. Download the Toad for Oracle on Mac zip file
2. Double-click the zip file; macOS will automatically extract it to the current folder
3. Optionally copy the app folder to the **Applications** folder; macOS will prompt you to do so upon first run if run from any other location

Uninstall

1. Quit Toad for Oracle
2. Move the app folder to **Trash**
3. Removing the app does not remove Toad for Oracle's configuration files; delete **~/Library/Application Support/Toad for Oracle** for complete removal

For more information about the products in your Toad for Oracle Edition and the minimum system requirements for running these products, see the Toad for Oracle Editions release notes at:

<https://support.quest.com/technical-documents>

New Features and Enhancements

Toad for Oracle 17.0

Toad for Oracle on Mac

Toad for Oracle Professional DB Admin edition is now available for Mac. Click [here](#) to download the free trial.

Oracle 23c

- Support for new features in Create/Alter windows, generated scripts, and elsewhere as appropriate:
 - ANNOTATIONS
 - Boolean datatypes
 - DEFAULT ON NULL FOR INSERT AND UPDATE
 - DOMAINS
 - IF [NOT] EXISTS
 - JSON-Relational Duality Views
 - PRECHECK Constraints
 - Schema-level privileges

Editor

- Data grids can be pinned allowing for multiple statements to be executed within a single tab without losing the results of the previous execution
- Option added to trim whitespace when saving files
- Improved performance when the Navigator option to "Show references" is unchecked; also applies to the Schema Browser when viewing PL/SQL objects
- Improved performance of parameter assistance for Oracle built-in functions defined within the SYS.STANDARD package, e.g. TO_CHAR()
- Added an option to the Script Output tab that synchronizes the Editor caret position with the active Script Output data grid and vice versa
- Exporting all Script Output data grids to an Excel file now produces a summary sheet

- Old, automatic backups are purged for improved performance
- Option added to enable utPLSQL integration if it is installed; unchecking this option improves performance by eliminating internal queries, but disables all Editor support for utPLSQL test suites

Connections

- SSH connections can be made natively without needing PuTTY or similar
- Clientless connections support TCPS protocol
- Common users having the SET CONTAINER privilege can easily switch between CDB and PDB instances via the Connection Bar context menu

Connection Colors

- An option has been added to fill Toad's title bar with the active connection's color when using a color scheme and connection colors

Trace File Browser

- Improved workflow when loading files from the database server
 - Option to exclude non-SQL trace files
 - Filter by file content, e.g. SQL ID, tablename, or any text that may exist in the trace file
 - Limit files to only those produced within a specified timeframe
 - Option to preview files after retrieval

Object Palette

- Option added to "Show Subobjects" that displays related objects (e.g. table constraints, grants, indexes, triggers, etc.) just like the Schema Browser's "Show LHS Subobjects" feature

Automation Designer

- Improved Action palette
- Export Dataset action can pass variables to SQL files as parameters

Data Grids

- Columns can be sorted even when the query contains an ORDER BY clause
- **Find Data** and **Filter Data** from the context menu allows searching and filtering across multiple columns
- A refresh button has been added to the Editor Data Grid to reexecute the query
- Single Record Viewer supports copying the column header and value to clipboard

Compare Schemas

- Options added to verify that tablespaces and Oracle features exists in the target database; any violations that will cause the sync script to fail are identified in the Difference Details tab

Generate Schema Script

- Added the ability to combine related objects when generating one script per object; for example, synonyms and grants with their target objects, type/package with its body, indexes with their table, etc.
- An option has been added to include schema name in object filenames
- An option has been added to include private synonyms for objects when exporting

Schema Browser

- Improved performance when selecting Procedures, Functions, and Packages
- Added the ability to pin quick filters

Session Browser

- "Kill Session" button added to the Locks tab
- "Status" column added to the Locks tab

Import Table Data

- Added the ability to create a new table from the Import Table Data wizard prior to importing

Workspaces

- New command line parameter for launching Toad and opening a specific workspace, e.g. `Toad.exe -workspace my_favorite_workspace_name`

Debugger

- A new "Check Privileges" menu item is available from the main Debug menu to check the active connection for the privileges required to debug

DB Health Scan (Preview)

DB Health Scan is a new window similar to DB Health Check with improved visualization of results. This window is a preview feature with additional improvements planned for a future release.

SQL*Net Editor

- Added support for SSL parameters

TNSNames Editor

- Added support for Retry Delay, Retry Count, and Compression parameters

Toad for Oracle 16.3

Editor

- New minimap with options to control position and scale
- Support for font ligatures
- Revamped brace highlighting options to provide additional behavior
- Search across all open Editor tabs from Find in Files/Editors
- Auto Replace options to include/exclude replacement within comments and strings
- Option to lock tab positions when multi-line tab mode is enabled
- Reload file/database object improvements to support reloading all items that have been modified
- Object name highlighting option to highlight dependencies from other schemas
- Navigator option to exclude PL/SQL parameters from sorting
- Navigator option to indicate PL/SQL parameter position
- Navigator option to show references
- Context menu is customizable
- Refactoring item to replace package constant references with their literal values
- Format Code can be canceled
- Additional user experience improvements

Schema Browser

- Object quick filter support for regular expressions
- Data tab filter dialog automatically adds quotes for IN/NOT IN conditions
- Data tab filter dialog options to save size/position
- Scheduler Jobs displays "subname" field on the Run Log tab

- Tables | Copy to another schema allows setting options as the default values used each time the window opens
- Tables | Copy to another schema options to create indexes/constraints when creating non-existent tables in the destination schema
- Create/Alter Materialized View option to specify the refresh group
- ID column added to the Arguments tab for PL/SQL
- Option to lock tab positions when multi-line tab mode is enabled

Color Schemes/Dark Mode

Additional schemes

Automation Designer

- New action to run reports configured in the Reports Manager
- New action to perform single column import
- Running apps can be canceled
- Execute Script action option to suppress the progress dialog
- Action palette buttons rearranged to be more intuitive
- Expanded copy to clipboard support to areas that previously lacked it

Data Grids

- Paste from clipboard across multiple selected cells
- Sort on multiple columns
- Context menu, Appearance submenu improvements

Export Dataset

- 7-Zip and gzip compression
- Query executed when "Display all results in grid" is unchecked can be canceled
- Flat File export option to set the end of line style
- Excel File export option to retry when the file is locked by another process
- Excel File/Instance export option to allow formulas which sets the Excel column formatting accordingly

Window Bar/Menu

- Ability to rename a window by right-clicking on its Window Bar button
- Option to show individual Editor tabs on the main Window menu

Login Window/Connections

- Create multiple logins at once applying the same properties across databases defined in tnsnames.ora
- Reconnect Lost Connections feature added to only reconnect sessions that are known to be disconnected
- Test Connections from the Login window improvements to update password if an ORA-01017 is raised and multiselect output
- Filter tabs when previously used connections are displayed using one of the "Tabbed by" views
- Toad Script Runner clientless connection support
- Retry button on the connection error dialog
- Messages configured using the SEC_USER_UNAUTHORIZED_ACCESS_BANNER and SEC_USER_AUDIT_ACTION_BANNER properties in the server's sqlnet.ora are displayed and acceptance is required to make the connection
- Custom field values can be modified when editing multiple login records

Export DDL

- Option to group object DDL into folders by their object type
- Option to exclude BEQUEATH clause from Views

SQL Recall

- Improved workflow when moving items from recently used to saved
- Options moved from the toolbar to a dedicated dialog to improve toolbar usefulness
- Additional display options and usability improvements

Manage User Settings

- Automatically backup key configuration files with options to configure what is backed up, the frequency, and a discard policy for old backups
- Ability to reset user files and selectively restore configuration files from a backup

Miscellaneous

- Team Coding automatically remaps object IDs which is necessary when controlled objects have been dropped and recreated
- Code Analysis option to limit the number of violations per rule type
- Compare Schemas produces an overall summary file in addition to each comparison's individual report when the multiple schemas option is used
- Various improvements to document recovery
- Various improvements to Master Detail Browser
- Many bugs fixes and other enhancements

Toad for Oracle 16.2

Data Grids

Improved formatting when copy/paste into applications that can accept HTML, e.g., Microsoft Teams, Microsoft Word, etc.

Fonts

Default fonts have been changed for an updated look. The default UI font is Segoe UI and the default Editor font is Consolas.

Color Schemes/Dark Mode

- Toad Script Runner now supports color schemes.
- Improvements to default Editor colors in dark schemes.

Login Window/Connections

- Clientless connections now support LDAP.
- Unchecking "Save passwords" requires confirmation.
- TNSNAMES Editor and LDAP Editor buttons have been moved to more relevant locations.
- Improved error handling and recovery when an ORA error is raised during connection initialization.

Automation Designer

- Improved performance with many apps/actions.
- Apps and folders can be cloned using copy/paste.
- Connections within the Connection Iterator action can be selectively enabled/disabled.

Editor

- Tabs for files modified externally have their captions updated to reflect the modification.
- A new word list has been added that can be used by you to set your own words to style how you see fit. See the "User List 1" list on the SQL tab (**View | Options | Editor | Font and Styling**).

Execute/Compile

- A new option has been added to check for locks prior to compiling (**View | Options | Execute/Compile**).
- Execute Snippet chooses better variable names when replacing PL/SQL references with bind variables.

Generate Schema Script, HTML Schema Doc Generator, and Compare Schemas

- Object set filters are saved as text files.
- Filter files can be specified in the respective actions for those windows in the Automation Designer.

Schema Browser

The right-click Clone/Copy user window now has a Show SQL button.

Describe Dialogs

Options added to remember the size and position (**View | Options | Schema Browser | Describe Dialogs**).

Compare Files

Shortcuts have been added for next/previous difference.

Toad Debug Mode

Toad debug mode has always been available via Toad.ini settings. Debug mode can now be enabled using controls within the Options window (**View | Options | General**). Use these options only when requested by Quest Support.

You can find the most up-to-date list of new features for this release in the *Toad for Oracle Release Notes* found at: <https://support.quest.com/toad-for-oracle/technical-documents>.

Discontinued Features

Knowledge Xpert. Knowledge Xpert is no longer available on Toad World. Beginning with release 13.1, Toad components no longer reference the online Knowledge Xpert.

Ask a Question. The **Go to Toad World** and **Ask a Question** commands on the Toad World toolbar have been replaced. To ask a question, click the **Forums** toolbar button to go directly to the forum. To go to Toad World, click the **Forums** or the **Browse Blogs** toolbar buttons. You can also use the Help menu: **Help | Toad World | Forums**. This change is found in Toad for Oracle 13.1 or later.

Integration with Toad Intelligence Central. Beginning with Toad for Oracle 13.1, Toad no longer provides integration with Toad Intelligence Central. The Toad Intelligence Central window is not available and you cannot publish scripts, files, Code Analysis results, and other resources to a Toad Intelligence Central server using Toad for Oracle. You cannot connect to Toad Intelligence Central through Toad for Oracle.

Resolved issues

The following is a list of issues addressed and enhancements implemented in this release of Toad for Oracle.

Toad for Oracle 17.0 Patch 1

The following list of resolved issues includes issues received from the Toad for Oracle forum, Toad Beta users, and exception data collected from the Toad Improvement Program.

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|---|
| TOR-7680 | | Script Manager: Access Violation occurs when running scripts in 64-bit Toad. |
| TOR-7681 | link | Toad for Oracle on Mac: Animation on the Script Execution dialog looks bad. |
| TOR-7682 | | Toad for Oracle on Mac: "Task Manager not running" error on startup. |
| TOR-7683 | | Toad for Oracle on Mac: Compiling a Team Coding controlled object in the Editor using shortcut (F9) results in endless loop. |
| TOR-7684 | link | Toad for Oracle on Mac: Cannot drag/drop files from Finder to Editor. |
| TOR-7686 | | Alter Database Link: Incorrect username for connection is shown. |
| TOR-7687 | | Editor Options: The Tab stop setting is not being saved when Toad closes. |
| TOR-7694 | link | Editor: The Navigator tree scrolls each time it refreshes. |
| TOR-7704 | link | Toad for Oracle on Mac: Find Next (F3) does not work properly if the find dialog is not showing. |
| TOR-7705 | link | Toad for Oracle on Mac: Grid lines are invisible in some windows. |
| TOR-7711 | | Schema Browser: "Invalid table name" error is raised when generating scripts for Tables, Views, and Materialized Views for users lacking the SELECT ANY DICTIONARY privilege. |
| TOR-7712 | | Import Table Data: Importing from a Fixed Field Width file raises an incorrect error regarding field size and nothing is imported. |
| TOR-7715 | | Automation Designer: Upgrading from Toad for Oracle 16.3 to 17.0 raises an error at startup for ToadActions.dat if the 16.3 datafile contains a Data Pump Import action. |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|--|
| TOR-7717 | | Debugger: "Invalid Oracle Home" error is raised when debugging if the session is made without a client and no clients are installed. |
| TOR-7718 | link | Toad for Oracle on Mac: Cannot save BLOB data from the data grid BLOB editor. |
| TOR-7737 | | Toad for Oracle on Mac: Poor font quality. |
| TOR-7753 | | Login Window: LDAP dropdown list is slow to load when in clientless mode. |
| TOR-7763 | | Toad for Oracle on Mac: CAPS lock can get out of sync. |
| TOR-7764 | | Toad for Oracle on Mac: The TNS_ADMIN location is not as apparent as it could be. |
| TOR-7838 | | TNSNAMES Editor: Adding a new service is nonfunctional. |

Toad for Oracle 17.0

The following list of resolved issues includes issues received from the Toad for Oracle forum, Toad Beta users, and exception data collected from the Toad Improvement Program.

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|--|
| TOR-2632 | | Editor: "Refactor > Remove Subqueries" generates invalid SQL when aggregate functions are present |
| TOR-6414 | link | Data Grids: Strings exceeding the width of the control do not show a trailing ellipsis |
| TOR-7086 | link | Triggers: Incorrect DDL is generated for disabled triggers containing a header comment and a WHEN clause |
| TOR-7087 | link | Login: When grouped by multiple columns, deleting records from an expanded group collapses all other expanded groups |
| TOR-7089 | link | Session Browser: Locks tab does not select the top row following a refresh |
| TOR-7101 | link | Schema Browser: Favorites folder cannot be renamed |
| TOR-7102 | link | Schema Browser: Scheduler Job script is invalid when the job has unnamed arguments |
| TOR-7103 | link | Alter Tablespace: Maximum size is changed to UNLIMITED in some cases |
| TOR-7112 | link | Generate Schema/Database Script: IN MEMORY and COMPRESSION options are ignored |
| TOR-7117 | | Session Browser: Selected row in the Open Cursors tab changes after |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|--|
| | | activating a different tab and returning to Open Cursors |
| TOR-7130 | | Insert Table Data: Some rows are not imported following a constraint violation when the "Use Array DML" option is checked |
| TOR-7133 | link | Workspaces: Unicode characters in the Editor are lost |
| TOR-7134 | link | Schema Browser: Scheduler Job run log throws an error on Oracle database 10g Release 1 |
| TOR-7135 | link | Export Dataset: Auto detection of schema doesn't work with a SELECT from a table across a database link containing a '.' in its name |
| TOR-7176 | link | Schema Browser: Sending a trigger to the Editor ignores the Editor option to exclude schema name when loading objects |
| TOR-7178 | link | Code Insight: Results not shown when invoked within SQL containing a subquery. |
| TOR-7181 | | Subscription Licensing: An Access Violation occurs after upgrading Toad in some cases |
| TOR-7185 | link | Schema Browser: Incorrect script is generated for tablespaces that are encrypted, but not compressed |
| TOR-7195 | link | Schema Browser: Rebuild Table window does not allow new columns having a name longer than 30 characters on Oracle database 12g Release 2 and newer |
| TOR-7201 | | Automation Designer: Execute Script action fails if the output file or path contains variables |
| TOR-7202 | | Team Coding: The Team Coding Browser VCS tab hangs when using Azure DevOps Services (TFVC) |
| TOR-7210 | link | Data Grids: Sorting a column no longer focuses the sort direction radio group by default |
| TOR-7211 | link | Change Password: ORA-00922 is raised when changing password if a password verify function has been configured |
| TOR-7217 | | Data Grids: The columns dropdown on the Filter tab of the Filter/Sort Data dialog is not wide enough to show long column names |
| TOR-7232 | link | Editor: The prompt to reload files modified externally is shown even after choosing "Yes to All" at the initial prompt and then deactivating and activating Toad |
| TOR-7233 | link | Team Coding: The compare dialog does not show Unicode characters |
| TOR-7237 | link | Trace File Browser: The modified date of some files is not displayed |
| TOR-7240 | link | Trace File Browser: Poor contrast when using a dark color scheme |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|---|
| TOR-7257 | | Editor: Refactor Resolve Package Constants does not work for SQL containing a single package constant reference |
| TOR-7262 | link | Code Insight: Very slow filtering of results while typing in some cases |
| TOR-7264 | link | Code Analysis: SQL Scan does not work when using proxy user authentication |
| TOR-7266 | link | Data Grids: Popup Editor throws a "Cannot modify a read-only dataset" error when formatting text |
| TOR-7274 | link | Data Grids: Using the DEL key to clear a cell throws an "Invalid value for field" error when the column has a foreign key |
| TOR-7319 | link | TNSNames Editor: Some parameters within the SECURITY section are unsupported |
| TOR-7332 | | Color Schemes: Schemes are not fully applied to SQL Recall after changing the color scheme and restarting Toad |
| TOR-7347 | | Compare Schemas: Schema name is excluded in the sync script if the "Include Schema in Migration DDL" and "Format before comparison" options are both checked |
| TOR-7349 | link | Script Execution: The SQL feedback text is formatted poorly or incorrect with some statements |
| TOR-7358 | link | Code Insight: PL/SQL objects are not shown in the list in some cases. |
| TOR-7376 | link | Explain Plan: Toad sometimes connects to the wrong RAC instance when the "Separate session" for Explain Plan option is set |
| TOR-7408 | link | Automation Designer: Export Dataset action changes the file extension of the results file in some cases |
| TOR-7409 | link | Color Schemes: The selected node in some tree views is difficult to see with some color schemes |
| TOR-7410 | link | Schema Browser: The left side navigator does not update its selected node to reflect the caret position after searching for text in the Script tab of a package |
| TOR-7423 | | Team Coding: Access Violation occurs after dropping materialized views |
| TOR-7424 | link | Schema Browser: The generated script for Materialized View is incorrect when the "Add to refresh group" option is checked in the script generation options |
| TOR-7438 | | Editor: The automatic backup feature does not clean up stale files and references which can lead to Access Violations and general performance issues in time |
| TOR-7479 | | Test Connections: An Access Violation can occur when closing the dialog immediately after testing connections |
| TOR-7480 | link | Automation Designer: FTP action does not observe variables in filenames to |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|--------------------|--|
| | | download |
| TOR-7593 | | Schema Browser: The right side/detail view when selecting a table is scaled incorrectly in some cases when using high-definition resolutions |
| TOR-7596 | | Import Table Data: Access Violation occurs when importing from CSV files having fields with more than 32k bytes of data |
| TOR-7600 | | DB Health Check: Bad results are generated for the "Foreign Keys with mix of nullable and not nullable columns" option |

Toad for Oracle 16.3

The following list of resolved issues includes issues received from the Toad for Oracle forum, Toad Beta users, and exception data collected from the Toad Improvement Program.

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|---|
| TOR-540 | link | Code Insight: Assistance is not provided when invoked after an unmatched parenthesis. |
| TOR-1300 | link | Code Insight: Join conditions are inserted incorrectly when the condition partially exists in the text. |
| TOR-6535 | link | Team Coding: Filter exclusions are not working completely. |
| TOR-6537 | | Find Dialog: Incorrect messaging when a match is not found in some cases. |
| TOR-6545 | | Team Coding: Merging a table that is out of sync causes data loss. |
| TOR-6550 | link | Editor: A file split over multiple tabs incorrectly prompts to reload the file when editing, saving, and then switching to another tab for the same file. |
| TOR-6551 | | Auto Optimize SQL: Invalid password message is seen for globally authenticated users. |
| TOR-6552 | link | Automation Designer: The Execute Script action does not support collection of DBMS OUTPUT. |
| TOR-6558 | link | Schema Browser: The Jobs, Script tab uses DBMS IJOB when the connection lacks privileges on it. |
| TOR-6573 | | Trace File Browser: Incomplete results when loading a multipart trace file. |
| TOR-6574 | | Editor: Executing a "ROLLBACK TO savepoint" also executes a generic ROLLBACK. |
| TOR-6597 | link | Toad Command Line Script Runner: Fatal Error occurs when the current working directory is not the directory containing tsr.exe. |
| TOR-6602 | link | Compare Schemas: Comparing a snapshot file to a schema results in an incorrect sync script for tables that have constraints/indexes named differently from what they are in the snapshot. |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|--|
| TOR-6607 | link | Team Coding: Stack Overflow error occurs when Subversion URL includes a trailing slash in some environments. |
| TOR-6608 | link | Workspaces: Toad closes unexpectedly when loading a workspace in some cases. |
| TOR-6609 | | Editor: Script execution takes a long time to start in some cases. |
| TOR-6619 | link | Options: Thousands separator no longer allows for space character. |
| TOR-6624 | link | Schema Browser: The "Deps (Uses)" and "Deps (Used By)" tabs have UI defects when using a dark mode color scheme. |
| TOR-6632 | | Data Grids: Pasting multiline text into a grid cell only retains the first line of the text. |
| TOR-6633 | link | Editor: Rearranging tabs causes the desktop layout to become corrupt in some cases. |
| TOR-6638 | link | Schema Browser: Space character incorrectly inserted into "class" when viewing Java Source code. |
| TOR-6640 | link | Options: New file types are not saved. |
| TOR-6645 | link | Toad Script Runner: "Execute via Script Runner" fails to establish connection when Toad's connection is a direct connection without using a client. |
| TOR-6646 | link | Editor: When using split editor mode the caret position is not retained following a format code in the secondary instance. |
| TOR-6650 | link | Automation Designer: Import Table Data action gives incorrect message that it cannot import into a read-only connection in some cases. |
| TOR-6656 | link | Data Grids: Mouse-wheel scrolling in grouped grid causes collapsed sections to expand. |
| TOR-6661 | | DBMS Output: Polling for output raises an ORA-06502 error in some cases. |
| TOR-6678 | link | Automation Designer: Drag/drop actions onto a collection action, e.g. If..Then..Else, Iterators, etc., causes the order of dropped actions to be reversed when the Automation Designer is closed and reopened. |
| TOR-6681 | link | Data Grids: Poor sizing/alignment of the summary panel. |
| TOR-6682 | link | Data Grids: Copying data via Ctrl+C and pasting into Excel includes the column headers. |
| TOR-6683 | | DBMS Output: The option to trim whitespace only works for the first 10 lines of output. |
| TOR-6686 | link | Generate Database Script: Roles are sorted alphabetically instead of by order required for creation when the "Object privileges granted to roles" option is not checked. |
| TOR-6693 | link | Compare Schemas: Comparing a snapshot file to a live schema includes public synonyms when the option to include public synonyms is not checked. |
| TOR-6697 | | Object Compare: The object type dropdown may be slow to load on large databases or over slow connections. |
| TOR-6702 | link | Toolbars: The active connection on the Change Session dropdown menu is identified by a checkbox which is difficult or impossible to see using some dark |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|---|
| | | mode schemes. |
| TOR-6710 | link | Master-Detail Browser: Long table names are truncated in detail pane. |
| TOR-6718 | | Editor/Schema Browser: Access Violation occurs when selecting from a table having ANYDATA column(s) if the data contains anything other than VARCHAR2, DATE, or NUMBER. |
| TOR-6719 | | Editor: Execute via Toad Script Runner/SQL*Plus throws an ORA-00942 when the current schema selection is not the logon schema and selecting from a table owned by the current schema. |
| TOR-6722 | | Connections: No prompt to change password when the password is expired and when connecting without an Oracle client. |
| TOR-6737 | link | Toolbars: The blue border used in the Connection/Window bar to identify buttons for the active connection is difficult to see when using a dark color scheme. |
| TOR-6738 | | Connections: "Invalid release" error is raised when connecting to some databases. |
| TOR-6743 | link | Schema Browser: PARALLEL_INSTANCES attribute is missing from the Scheduler Jobs Info and Script tabs and the Create/Alter Scheduler Job window. |
| TOR-6749 | link | Schema Browser: Wrong popup menu is shown when multiple packages are selected in some cases. |
| TOR-6750 | link | Connections: The most recently used connection is not automatically selected in the Login window when connections are grouped in some cases. |
| TOR-6755 | link | Editor: An externally modified file may result in duplicate confirmation prompts to reload the file. |
| TOR-6786 | | Schema Browser: Altering a tablespace datafile that has the size specified in MB will change to display GB after setting the max size to unlimited. |
| TOR-6824 | link | Master Detail Browser: Custom master query is lost after setting an invalid filter. |
| TOR-6827 | | Schema Browser: Materialized View, Deps (Used By) tab does not list views that query the materialized view. |
| TOR-6828 | link | Editor: Executable line indicators (blue dots) in the margin appear on lines that are inaccessible when debugging, e.g. lines within anonymous blocks. |
| TOR-6837 | link | Schema Browser: The selected object may scroll out of view after changing the filter such that more objects are displayed. |
| TOR-6849 | | Editor: Toad stops responding and crashes after moving one of the splitters in some cases. |
| TOR-6863 | link | Find Dialog: The Whole Words option is checked when the find dialog is shown after doing a Describe (F4). |
| TOR-6868 | link | Schema Browser: The selected and focused row indicators on the Tables, Triggers tab may be out of sync. |
| TOR-6870 | link | Master-Detail Browser: Long table names are truncated in detail pane. |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|--|
| TOR-6882 | link | DBMS Output: Polling for output omits blank lines in the output if they occur beyond the 10th line. |
| TOR-6901 | | Connections: Importing connections does not update/overwrite properties, e.g. passwords, of existing connections for the same user@database. |
| TOR-6903 | link | Editor: Changing the caret position within a package is slow after connection loss if the database has utPLSQL installed. |
| TOR-6910 | link | Editor: Prompting to save empty tabs that are not loaded from a file is unnecessary. |
| TOR-6917 | | Connections: LDAP connections fail with an "" is not a valid release" error if the DIRECTORY_SERVERS value in ldap.ora lacks a primary directory port. |
| TOR-6922 | link | Login: Custom columns that have been fixed and then removed from the grid cannot be added back. |
| TOR-6930 | link | Schema Browser: Materialized View Script tab lacks the USING TRUSTED CONSTRAINTS clause for views created with the BUILD DEFERRED and USING TRUSTED CONSTRAINTS clauses. |
| TOR-6933 | | Editor: CONNECT statement does not work for externally authenticated connections. |
| TOR-6938 | link | Schema Browser: Queue Script tab shows incorrect DDL for sharded queues and these queues are not properly shown in the Alter Queue window. |
| TOR-6942 | | Team Coding: Objects with double quoted names are not supported and cause errors. |
| TOR-6947 | | Object Palette: Action Console is missing from the context menu. |
| TOR-6954 | link | Code Analysis: Double clicking a rule violation should display a popup dialog with additional information, but it is blank. |
| TOR-6968 | link | Auto Optimize SQL: Unhelpful error message when sending SQL from the Editor and the connection is made without a client and no clients are installed. |
| TOR-6970 | link | HTML: Error message that Microsoft Edge cannot read and write to its data directory is seen in dialogs where HTML is displayed in some environments. |
| TOR-6974 | | Schema Browser: Expanding the Constraints or Indexes sub-objects nodes beneath a Table results in ORA-00942 when connected to an Oracle 21c database. |
| TOR-6976 | | Export Dataset: Timestamp values export as a date, i.e. fractional seconds and time zone are eliminated, and the time is omitted if it is 12:00 AM/00:00. |
| TOR-6977 | link | Schema Browser: Alter Table dialog is slow to load and eventually Toad crashes if there are many constraints. |
| TOR-6978 | link | Statspack Browser: Grid sorting does not work. |
| TOR-6979 | | Schema Browser: Selecting multiple tables and using Create Script omits NOT NULL constraints in some cases. |
| TOR-6981 | link | Statspack Browser/AWR Browser: Checked snapshots are not automatically scrolled into view. |
| TOR-6983 | | Alert Log Viewer: Some dates are missing if the loaded log file contains |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|---|
| | | multiple date formats. |
| TOR-6985 | link | AWR Browser: ORA-00907 is raised when trying to create a snapshot on Oracle Database 10gR2. |
| TOR-6988 | | Workspaces: Editor bookmarks are not saved for all tabs. |

Toad for Oracle 16.2

The following list of resolved issues includes issues received from the Toad for Oracle forum, Toad Beta users, and exception data collected from the Toad Improvement Program.

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|--|
| TOR-5226 | link | Data Grid: Copied data doesn't paste nicely into Word or Teams. |
| TOR-6028 | | Execute Script: SQL keywords are not accepted as script arguments. |
| TOR-6086 | | Schema Browser: Object type dropdown is non-functional using some themes, e.g. Golden Age, when Toad is maximized. |
| TOR-6222 | | Query Builder: Excessive spacing between columns in the model area. |
| TOR-6292 | | Generate Table Data: ORA-06550 is raised when generating data for multiple tables related via referential integrity when the "Enforce Referential Integrity" option is selected. |
| TOR-6293 | | Login Window: Duplicate entries created for the same user@database when LDAP server returns the database name in lower or mixed case. |
| TOR-6294 | | Connections: Connection colors disappear when windows are unmaximized and a popup dialog is shown. |
| TOR-6301 | | Editor: Variable prompt dialog stays on top of other apps. |
| TOR-6306 | | Compare Files: Access Violation is thrown when clicking the Save button in some cases. |
| TOR-6308 | | Export Dataset: Exporting to Excel Instance does not bring Excel to the foreground when complete. |
| TOR-6313 | | Execute Script: Memory leak when executing any script. |
| TOR-6314 | link | Options: Decimal and Thousands separator values are not loading or saving in some cases. |
| TOR-6318 | link | Schema Browser: Filter/Sort Dialog adds unnecessary parenthesis in some cases. |
| TOR-6319 | | Schema Browser: Several issues with object types when connected to a database which has Team Coding enabled, e.g. attributes/methods are unavailable, wrong font color is used, and body is unavailable in the Script tab for types with bodies. |
| TOR-6322 | | Export Dataset: The "Enclose string fields in" option does not allow an empty value when using the SQL Loader format. |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|---|
| TOR-6327 | link | Team Coding: Project Global Filter merges multiple exclusions into a single line when saved. |
| TOR-6329 | | Import Table Data: Timestamp format error when importing from file in some cases. |
| TOR-6330 | link | Schema Browser: Team Coding images are not shown for sequences. |
| TOR-6332 | link | Schema Browser: Context menu is corrupt when multiselecting types when the selection contains both object and collection types. |
| TOR-6335 | | Schema Browser: Materialized view Info and Script tabs always report NOLOGGING even when the view was created with the LOGGING clause. |
| TOR-6336 | | Export Dataset: SQL Loader format wraps NULL values for numeric columns in double quotes leading to errors when using the export with SQL Loader. |
| TOR-6337 | | Login Window: Database dropdown mnemonic key doesn't work. |
| TOR-6338 | | Toolbars/Menus: The Window menu does not include Describe windows. |
| TOR-6348 | | Schema Browser: Refreshing the left side (object list) is nonfunctional for functions, procedures, packages, and types when using the Dropdown or Tabbed browser style. |
| TOR-6359 | | Automation Designer: Performance and resource issues when a lot of apps exist. |
| TOR-6361 | link | Schema Browser: The object type incremental search feature can be a little bit clumsy making it difficult to type multiple characters. |
| TOR-6362 | link | Login Window: Deleting a previously used connection when the grid is grouped by a column may move focus to a row within a different group. |
| TOR-6364 | link | Describe: Describing (F4) a package constant declared in the spec loads the package body instead of the spec. |
| TOR-6365 | link | Unit Test Manager: Context menu opens and closes erratically when invoked while a test is running. |
| TOR-6366 | link | Describe: The Describe window always remembers the size and position, i.e. there is no option to disable this as with other windows. |
| TOR-6371 | | Compare Multiple Tables/Compare Table Data: Script output uses incorrect decimal and thousands separators in some cases. |
| TOR-6372 | | Auto Update: The QuestDBTAutoUpdate Windows service does not use double quoted executable path. |
| TOR-6373 | | Session Browser: Various errors when the session lacks the privileges required to use it. |
| TOR-6374 | link | Editor: Execute Snippet replaces PL/SQL references with bind variables and uses variable names that are not intuitive. |
| TOR-6377 | | Execute Script: Memory leak when executing any script. |
| TOR-6378 | link | Schema Browser: Revoking an object grant from a schema having a name requiring double quotes fails. |
| TOR-6407 | link | Alter Table: Clicking NOT NULL on a column after scrolling down in the grid results in the setting being applied to the wrong column. |

| Issue ID | Link to Forum Post | Resolved Issue |
|----------|----------------------|---|
| TOR-6413 | link | Schema Browser: Object quick filter selects the wrong item from history in some cases. |
| TOR-6424 | link | Automation Designer: Execute Script action gives the wrong error message when the script file has been deleted from disk. |
| TOR-6430 | link | Create/Alter Tablespace: Several issues with encryption algorithm and temporary tablespaces, e.g. algorithm dropdown is enabled when altering, algorithm is excluded from the script tab, only the AES128 algorithm is present in the Create Tablespace window. |
| TOR-6432 | link | Single Object Compare: An object in the target session having the same name as the source object should be selected by default. |
| TOR-6438 | link | Session Browser: "Engine is currently busy" error message. |
| TOR-6447 | link | Data Grids: Up Down arrow navigation does not work when editing VARCHAR2 fields. |
| TOR-6448 | | Create/Alter Scheduler Job: ORA-27453 is thrown when altering a scheduler job that has unnamed parameters. |
| TOR-6512 | link | Export Dataset: Excel Instance format changes the file/clipboard setting unnecessarily. |

You can find the most up-to-date list of resolved issues for this release in the *Toad for Oracle Release Notes* found at: <https://support.quest.com/toad-for-oracle/technical-documents>.

Known issues

The following is a list of issues, including those attributed to third-party products, known to exist in this release line at the time of the current release.

General known issues

| Known Issue | Issue ID |
|--|----------|
| Toad's help cannot be opened from an installation path that contains Unicode characters. | 72966 |
| <p>If you check "Indexes" on the Scripts tab for snapshots, then the primary key for the snapshot will be included in the script, even though the CREATE MATERIALIZED VIEW statement implicitly creates this primary key.</p> <p>Toad currently does not differentiate between indexes created explicitly on the snapshot and indexes created automatically when the snapshot is created.</p> <p><i>Workaround:</i> If you are running the generated script to recreate the snapshot, then you can simply ignore the error that occurs when the script tries to recreate the primary key index for the snapshot. If you do not normally create indexes on snapshots, then you can uncheck "Indexes" when generating the snapshot script.</p> | N/A |
| <p>If you use 11g Oracle ODP.NET client or any other client that does not have the oci.dll in the BIN directory, Toad has the following problems:</p> <ol style="list-style-type: none">1. Client shows as invalid2. Client version is not detected3. As a result of #2, columns of the following datatypes are not shown in the Schema Browser table data: CLOB, BLOB, NCLOB, XMLTYPE, TIMESTAMP, INTERVAL, BINARY_DOUBLE, and BINARY_FLOAT | N/A |
| <p>Debugger</p> <p>If there is an exception during debugging on a 10Gr2 or greater database, REFCURSOR output and DBMS output will not be available when debugging is completed. This is due to the target session not being available.</p> <p><i>Workaround:</i> To see REFCURSOR output and DBMS output, execute the procedure without the debugger.</p> | N/A |
| <p>Connections</p> <p>While Toad supports LDAP connectivity, some features of Toad depend on tnsnames.ora file to operate correctly, such as Toad Script Runner (TSR).</p> | N/A |

| Known Issue | Issue ID |
|--|----------|
| <p>Schema Browser</p> <p>Sometimes after pressing "Compile invalid objects", you may get ORA-20000, ORA-06512, or ORA-06512 errors. This could mean that you do not have the privileges to compile the object, but it also happens when the schema contains a package body that does not have an associated spec.</p> <p><i>Workaround:</i> Look in the schema that you are trying to compile to see whether there are any orphan package bodies. If it is your own schema, then do:select * from user_objects o1 where object_type = "PACKAGE BODY" and not exists (select "x" from user_objects o2 where o2.object_name = o1.object_name and o2.object_type = "PACKAGE") Then drop any orphan package bodies that are found.</p> | N/A |
| <p>Virtualization</p> <p>An access violation error may display when you close Toad in a Citrix XenApp environment.</p> | 76354 |
| <p>Import/Export</p> <p>Constraint scripts from Export DDL do not contain the "using index" or "tablespace" clause.</p> | 59228 |
| <p>Data Modeler:</p> <ul style="list-style-type: none"> • Generation of HTML reports of large diagrams may fail during generation of an image of the ER Diagram. • Comparison of large models may consume too much memory. | N/A |

Oracle client known issues

| Known Issue | Issue ID |
|--|----------|
| <p>In some cases, connecting to an 11g database using a 19c or 21c client may result in a hang when cancelling a query or when using Code Insight.</p> <p><i>Workaround:</i> Use an 18c or older client when connecting to an affected database.</p> | N/A |
| <p>All versions of Oracle client 19c leak memory when working with LOB types. This includes simple SELECT statements against a table containing LOB types.</p> | N/A |

Proxy server known issues

| Known Issue | Issue ID |
|--|----------|
| <p>Toad does not support Proxy Automatic Configuration (PAC) scripts; however, Toad does allow you to specify Quest-specific proxy settings to work around this limitation. By default Toad will use non-PAC proxy settings configured within Windows automatically.</p> | 72966 |

Apply settings system-wide:

HKEY_LOCAL_MACHINE\Software\Quest Software\Internet Settings:

- ProxyEnable (DWORD): 1 = enable proxy override at this level, 0 = don't enable proxy override at this level
- ProxyServer (string): semicolon-delimited "<protocol>=<server>:<port>" entries
 - For a shared proxy server across multiple protocols:
 - a single "<server>:<port>" entry is all that's needed (ex: "127.0.0.1:8888")
 - For individual proxy servers by protocol, specify multiple entries:
 - ex: "https=127.0.0.1:8888;http=127.0.0.1:8080;ftp=127.0.0.1:6300"

For 32-bit applications on a 64-bit machine:

- Key: HKEY_LOCAL_MACHINE\Software\WOW6432Node\Quest Software\Internet Settings:

Apply settings to your own account:

HKEY_CURRENT_USER\Software\Quest Software\Internet Settings:

- Same keys as above

Notes for use:

1. Override proxy settings will only be included if the corresponding ProxyEnable value is set to "1". Otherwise, it's ignored.
2. HKLM (system-wide) server settings will override Windows settings.
3. HKCU (local) server settings will override HKLM and Windows settings.
4. Users can also edit both the system proxy settings (existing in Toad 14.0) and now their user-specific proxy settings (from HKCU) within Toad's Proxy Settings dialog (View | Options | Online); however, system-wide settings (from HKLM) will not be editable inside of Toad since they're more for administrators in silent installs or system-wide configs.

Data Grids known issues

You may receive an "ORA-00902 invalid datatype" error when editing an object, nested table, or varray data if you have redefined the data type for that data during the current session.

N/A

Workaround: If you redefine an object type, nested table, or varray and then need to edit data in a table based on that type, end your current connection and begin a new one.

Full table data is not displaying in the live data grid (results from F9) if the data contains "zero" characters (ASCII 0). In this case, all data after the zero character will not show in the grid.

Workaround: Double click on the data cell in the data grid to view full contents of data in a popup editor.

Code Analysis known issues

| Known Issue | Issue ID |
|--|----------|
| Saving results to a database: When dealing with nested procedures, Code Analysis can only insert run data from procs one level deep. | N/A |
| Saving PL/SQL results to a database may fail or save invalid data to the database for invalid PL/SQL objects. <i>Workaround:</i> To ensure PL/SQL results are saved to the database correctly, verify the validity of all objects before running Code Analysis. | N/A |

Editor known issues

| Known Issue | Issue ID |
|--|----------|
| Toad errors when you query on a field of Oracle collection types. <i>Workaround:</i> Execute using SQL*Plus. | 64373 |
| When spooling to an unpinned output window, the window becomes unresponsive and errors are given when Toad is closed ("Canvas does not allow drawing"). <i>Workaround:</i> Keep the output window pinned. | 68523 |
| If you use a non fixed-width font, the results are misaligned in the of Script Output tab in Editor after executing a SQL script. <i>Workaround:</i> Go to Options Scripts and select a fixed-width font for script output. | 62234 |

Session Browser known issues

| Known Issue | Issue ID |
|---|----------|
| The Program name in the Session Browser may be blank or may be the full path to the executable instead of just the executable name. This depends on the Oracle client, not on Toad. | N/A |
| In RAC databases, version 10.1.0.3 (and possibly other 10.1 versions), the query used to populate the "Current Statement" in the Session Browser fails with the following error: Runtime error occurred: 12801 (ORA-12801: error signaled in parallel query server PZ99, instance <instance name> ORA-01008: not all variables bound) This problem does not occur in Non-RAC environments. <i>Workaround:</i> Clear the "Use RAC Views" checkbox, and log into the appropriate instance of the database, if necessary. | N/A |

Team Coding known issues

| Known Issue | Issue ID |
|--|---------------|
| Creating a new revision or attempting to force a check-in to Visual Studio Team Services may result in a "404: Not Found" error. The current version of Team Foundation Server used by Visual Studio Team Services compares the source being uploaded with the source already in the repository. If the source has not changed, it may incorrectly return an error rather than allowing the forced revision. This appears to be a Microsoft issue. As a result, these two commands may fail. | N/A |
| When using the Team Foundation Server internal client and Team Foundation Server 2012 or 2013 alternate Team Project Collections, workspaces created outside of Toad are not visible from within Toad. A workspace may be created from Toad by clicking the 'New' button during the Team Foundation Server log in. This is not an issue when using the Team Foundation Server external client. | 114334 |
| Team Coding is disabled for mixed-case object names. | N/A |
| With CVS, Toad may fail to retrieve the list of projects for you to select from in the CVS browser or in the Code Control Groups configuration. <i>Workaround:</i> See "Missing CVS\Entries File Error" in the online help. | N/A |
| Team Coding and Clearcase: Dynamic Views are not supported via SCC interface. Snapshot Views must be used instead. (Rational case ID v0830629, Rational Defect # CMBU00053934) | N/A |

Unicode known issues

| Known Issue | Issue ID |
|--|----------|
| The following features in Toad do not support Unicode: <ul style="list-style-type: none">• ASM Manager• Export File Browser• Hex Editor In addition, Java itself does not allow Unicode class names or file names. This is relevant to the Java Manager, Editor, and Schema Browser. | N/A |
| Editor options to highlight object names may not work for object names that contain Unicode characters. | N/A |
| Script Execution in Editor: Error offset can be incorrect when running scripts with multi-byte object names. | N/A |
| XML (Plain) format creates bad XML if Unicode string values and Unicode column names are exported through Export Dataset. | N/A |
| Import mapping for Unicode characters is incorrect if the characters are not a fixed width (such as Korean). | 63221 |

| Known Issue | Issue ID |
|---|----------|
| In Team Coding, objects with Unicode <i>contents</i> are supported, objects with Unicode <i>names</i> are not. Supported Version Control Providers do not support Unicode names. | N/A |
| The OCI option ORA_NCHAR_LITERAL_REPLACE affects the NCHAR String Literal Replacement behavior when connected to non-Unicode databases. The option can be enabled or disabled. See the "Enable ORA_NCHAR_LITERAL_REPLACE" option (View Options Oracle General). The option has adverse behavior regardless of its value. <ul style="list-style-type: none"> • Enabled - ORA-01756 error when executing SQL using the Q-quote operator where the end delimiter appears within the string literal and is followed by a single quote that is also part of the string literal. The single quote does not have to immediately follow the delimiter. • Disabled - NCHAR string literal corruption when connected to non-Unicode database. | N/A |

High DPI known issues

| Known Issue | Issue ID |
|--|----------|
| <p>Toolbars</p> <p>(Affects Windows Server 2019 only)</p> <p>Toolbar button images may disappear when you mouse over them if the "High DPI scaling override" option is set to "System (Enhanced)" in the Windows file properties dialog for Toad.exe</p> | N/A |

Toad for Oracle on Mac known issues

| Known Issue | Issue ID |
|--|----------|
| <p>The "Allow multiple copies of Toad to be loaded" option is nonfunctional.</p> <p>The option allows multiple copies of Toad to be opened on Windows, but does not work on macOS. The option has been disabled.</p> <p><i>Workaround:</i> Review macOS documentation for instructions on how to open a new instance of an app on Mac.</p> | N/A |
| <p>The "File Fast Exit" feature is nonfunctional.</p> <p>The feature allows for quickly closing Toad without prompting to save work. It has been disabled.</p> | N/A |
| <p>The Quit menu item from Apple's Toad for Oracle menu is nonfunctional if an Editor is open.</p> | N/A |
| <p>Editor is slow to open if CAPS lock is enabled.</p> <p><i>Workaround:</i> Turn off CAPS lock before opening Editor.</p> | N/A |
| <p>Bold text and other UI painting issues after installing Team Coding database objects.</p> <p><i>Workaround:</i> Restart Toad.</p> | N/A |

Third-party known issues

| Known Issue | Issue ID |
|---|----------|
| <p>Help</p> <p>(Affects the 64-bit version of Toad only)</p> <p>If IE9 is installed, clicking a link in the Help file may crash Toad 64-bit, even if IE9 is not the default browser.</p> <p><i>Workaround:</i> Users who have IE9 installed can open Help from outside of Toad.</p> | N/A |

System requirements

This section contains the hardware, software, and privileges required to run Toad for Oracle, as well as the database and virtual environments that Toad for Oracle supports.

Hardware requirements

| Requirement | Details |
|------------------|---|
| Processor | <ul style="list-style-type: none">• 1 GHz processor - Toad for Oracle 32/64 bit• Apple Silicon M1 or M2 processor - Toad for Oracle on Mac |
| Memory | <ul style="list-style-type: none">• 1 GB RAM - Toad for Oracle 32 bit• 2 GB RAM - Toad for Oracle 64 bit• 2 GB RAM - Toad for Oracle on Mac <p>NOTE: The memory required may vary based on the following:</p> <ul style="list-style-type: none">• Applications that are running on your system• Size and complexity of the database• Amount of database activity• Number of concurrent users accessing the database |
| Hard disk space | <ul style="list-style-type: none">• 600 MB - Toad for Oracle 32/64 bit• 2 GB - Toad for Oracle on Mac |
| Operating system | <ul style="list-style-type: none">• Windows 8.1• Windows 10• Windows 11• Windows Server 2012 R2 - 2 CPU required• Windows Server 2016• Windows Server 2019• Windows Server 2022• macOS 11• macOS 12• macOS 13 |

Requirement

Details

- macOS 14

Database requirements

Requirement

Details

Database client

An Oracle client is optional.

Connecting to a database without an Oracle client has the following considerations:

- Features requiring Oracle utilities will be unavailable including, but not limited to: SQL*Plus, Data Pumps, Import/Export Utilities, SQL Loader, TKProf, TNSPing, Wrap.
- Oracle Net Services configuration files are required for some connection methods, e.g. TNS requires tnsnames.ora and LDAP requires both ldap.ora and sqlnet.ora. These files may be placed in the folder specified by your TNS_ADMIN environment variable or in the same folder as Toad.exe.

The following Oracle clients are supported:

- Oracle Client or Instant Client 10.2.0.5
- Oracle Client or Instant Client 11.2.0.1/11.2.0.3
- Oracle Client or Instant Client 12c Release 1 and 2
- Oracle Client or Instant Client 18c
- Oracle Client or Instant Client 19c
- Oracle Client or Instant Client 21c

NOTE: You must use the 32-bit version of Toad with the 32-bit Oracle client, and the 64-bit version of Toad with the 64-bit Oracle client.

Database server

Oracle versions:

- 10g Release 2
- 11g Release 1 and 2
- 12c Release 1 and 2
- 18c
- 19c
- 21c
- 23c (Free - Developer Release)

IMPORTANT: It is recommended that your client version be of the same release (or later) as your database server. This is an Oracle recommendation to prevent performance issues.

| Requirement | Details |
|------------------------|---|
| Cloud database service | Oracle Database as a Service on Amazon EC2 and Oracle Cloud |

Network

- Internet Protocol Version 6 (IPv6) is being adopted by the US Federal Government and industries around the world. In its most basic format, the new protocol uses 128-bit addresses instead of 32-bit addresses, which are used by the current IPv4 to route packets over the Internet. Toad for Oracle features, such as FTP, access the Internet through third-party vendors that are IPv6 compliant, such as /nSoftware's IP*Works. For access to Web sites by way of the Toad Online window, Toad simply invokes the user-defined or default Web browser.
- Toad for Oracle Subscription editions require the user to sign in when using the product. This enables the product to verify the user's identity and to check that they are entitled to use the subscription. To complete this entitlement check internet access is required to connect to Quest Software's Licensing Servers.
- Toad for Oracle Subscription edition is bundled with Quest Auto Update, a service to periodically check for and deliver product updates. Quest Auto Update requires internet access and must be able to reach the cloud service at <https://autoupdate.toadworld.com>.

Additional requirements

| Requirement | Details |
|---------------------|--|
| Additional Software | <ul style="list-style-type: none"> • Microsoft Internet Explorer 6.0 or later (to view video from the Jump list within Toad, and to view the product documentation in HTML format). • Microsoft Office 2016 and recent earlier releases are supported for Word and Excel output. • Adobe Acrobat Reader 7.0 or later (to view the product documentation in PDF format). • Microsoft .NET Framework 4.0 to support the Toad for Oracle Editions Installer. |

Virtualization support

| Type | Details |
|------------------------------|---|
| Application virtualization | Citrix® XenApp |
| Desktop virtualization (VDI) | vWorkspace™ 7.0 has been tested. |
| Server virtualization | Oracle VM 3.1 has been tested. VMware ESX Server 3.5, 4.0, and 5.5 have been tested. |

NOTE: Toad may work in virtualization environments other than the ones listed.

Windows Privileges

In order to install and run Toad, make a connection, and do basic operations, you must have the following privileges.

| Operating System | Requirements |
|--|--|
| Windows 8.1 and 10 | <ul style="list-style-type: none">• Read access to the Oracle client folder |
| Windows Server 2012 R2, 2016, 2019, and 2022 | <ul style="list-style-type: none">• Read/write privileges on the Oracle Home directories that you use for your connections |

NOTE: Toad for Oracle Subscription edition is bundled with Quest Auto Update, a service to periodically check for and deliver product updates. Installation requires administrator privileges on all supported operating systems.

NOTE: Other functionality in Toad may require additional privileges.

Product licensing

Legacy Toad for Oracle with offline license keys

To activate a trial

1. Go to the trial download web page: <https://www.quest.com/products/toad-for-oracle/software-downloads.aspx>, accessed through the product page.
2. Select the Toad for Oracle Edition that you want to try.
3. Log in to your account or register.
4. Accept the license terms.
5. Download the trial file.

To activate a purchased commercial license

1. Go to the Quest Support website: <https://support.quest.com/>
2. Type the name of the product that you want to activate in the **Enter your product to find support** field.
3. Select **Download New Releases**.
4. Download the installer file.

NOTES:

- License keys compatible with Toad for Oracle 9.7 and earlier versions are no longer supported.
- Only the newer 48-character license keys are supported.
- If you have an older license type, the Editions installer points you to the license web page where you can update it.
- Toad supports cumulative licensing. You can add multiple licenses, including those for add-ons like Sensitive Data Protection, to Toad. Toad will use the licenses providing the highest degree of features.

Toad for Oracle Subscription with online licensing (including Editions)

Toad for Oracle Subscription requires you to sign in with your Quest.com account. Licenses are tied to your account giving you the flexibility to use Toad from multiple computers without having to move your license.

Sign in with existing Quest.com account

1. Enter your account email address and password when prompted
2. If you already have a Toad for Oracle Subscription license, no further action is needed
3. If you do not have a Toad for Oracle Subscription license, see **Activating a new license** below

Create a new Quest.com account

1. Select **Sign up for a new account**
2. Enter your account details and select **Sign Up**
3. A confirmation email is sent containing a verification code
4. Enter the code from the email and select **Verify**

NOTES:

- It may take a few minutes for the verification email to arrive
- Check your spam/junk folders for the email sent from supportadmin@quest.com if you do not receive it
- For additional assistance, please contact [Quest support](#)

Activating a new license

1. Toad for Oracle Subscription automatically provides a fully functioning, 30-day Trial license
2. To purchase a new license, click **Buy Now** from Toad's title bar
3. After completing your transaction, restart Toad and your license is automatically detected
4. To manage licenses, select **Account Settings** beneath your account shown at the top-right of Toad

NOTE: You can view your licenses from within Toad by selecting **Help | Licensing**

Getting started with Toad for Oracle

Toad for Oracle is distributed in the Toad for Oracle Editions at <https://support.quest.com/download-product-select>.

Upgrade and installation instructions

Please refer to the Toad for Oracle *Installation Guide* at <https://support.quest.com/technical-documents> for installation and upgrade instructions.

Upgrades for Toad for Oracle can install side-by-side with any previous versions you have installed. You can run the new and previous versions concurrently.

The first time you run the new version of Toad, the settings files from the previous version are automatically imported. To start with a clean set of user files, go to **Utilities | Copy User Settings**, then select **Create a clean set of user files from the base installation**.

NOTE: Toad supports importing settings only if the new version is within two releases of the previous version. If your versions are more than two releases apart, you need to install an intermediate version to successfully import the files.

User instructions

To get started with using Toad for Oracle, see the *Guide to Using Toad* at <https://support.quest.com/technical-documents>. For detailed information about any Toad window or feature, see the online help, which can be accessed from the **Help** menu.

Additional resources

Additional information is available from the Toad for Oracle Community on Toad World:
<https://www.toadworld.com/products/toad-for-oracle>

Globalization

Global Operation Statement

This section contains information about installing and operating this product in non-English configurations, such as those needed by customers outside of North America. This section does not replace the materials about supported platforms and configurations found elsewhere in the product documentation.

This release was not enabled and tested for international operation. Only U.S. English configurations of this product and U.S. English datasets are fully supported. Support for non-ASCII characters or non-English configurations may work appropriately, but these configurations have not been tested and this release should be used with caution in these environments.

This release has the following known capabilities or limitations: Toad 13.1 is a Unicode application. As such, it has support for any Oracle Unicode character set, such as UTF8 or AL32UTF8. There are some features in Toad which use or invoke Oracle Utilities or applications which are not themselves Unicode applications. Their functionality is therefore limited to the character set of the client on which Toad is running, and NLS_LANG must be carefully set to match the Windows character set

We have also observed issues with US7ASCII when used with non Latin characters.

About us

We are more than just a name

We are on a quest to make your information technology work harder for you. That is why we build community-driven software solutions that help you spend less time on IT administration and more time on business innovation. We help you modernize your data center, get you to the cloud quicker and provide the expertise, security and accessibility you need to grow your data-driven business. Combined with Quest's invitation to the global community to be a part of its innovation, and our firm commitment to ensuring customer satisfaction, we continue to deliver solutions that have a real impact on our customers today and leave a legacy we are proud of. We are challenging the status quo by transforming into a new software company. And as your partner, we work tirelessly to make sure your information technology is designed for you and by you. This is our mission, and we are in this together. Welcome to a new Quest. You are invited to Join the Innovation™.

Our brand, our vision. Together.

Our logo reflects our story: innovation, community and support. An important part of this story begins with the letter Q. It is a perfect circle, representing our commitment to technological precision and strength. The space in the Q itself symbolizes our need to add the missing piece — you — to the community, to the new Quest.

Contacting Quest

For sales or other inquiries, visit www.quest.com/contact.

Technical support resources

Technical support is available to Quest customers with a valid maintenance contract and customers who have trial versions. You can access the Quest Support Portal at <https://support.quest.com>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. The Support Portal enables you to:

- Submit and manage a Service Request
- View Knowledge Base articles
- Sign up for product notifications
- Download software and technical documentation
- View how-to-videos
- Engage in community discussions

- Chat with support engineers online
- View services to assist you with your product

© 2024 Quest Software Inc. ALL RIGHTS RESERVED.

This guide contains proprietary information protected by copyright. The software described in this guide is furnished under a software license or nondisclosure agreement. This software may be used or copied only in accordance with the terms of the applicable agreement. No part of this guide may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of Quest Software Inc.

The information in this document is provided in connection with Quest Software products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Quest Software products. EXCEPT AS SET FORTH IN THE TERMS AND CONDITIONS AS SPECIFIED IN THE LICENSE AGREEMENT FOR THIS PRODUCT, QUEST SOFTWARE ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL QUEST SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF QUEST SOFTWARE HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Quest Software makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Quest Software does not make any commitment to update the information contained in this document.

If you have any questions regarding your potential use of this material, contact:

Quest Software Inc.

Attn: LEGAL Dept

4 Polaris Way

Aliso Viejo, CA 92656

Refer to our Web site (<https://www.quest.com>) for regional and international office information.

Patents

Quest Software is proud of our advanced technology. Patents and pending patents may apply to this product. For the most current information about applicable patents for this product, please visit our website at <https://www.quest.com/legal>.

Trademarks

Quest, the Quest logo, Toad for Oracle, Toad, and Join the Innovation are trademarks and registered trademarks of Quest Software Inc. For a complete list of Quest marks, visit <https://www.quest.com/legal/trademark-information.aspx>. All other trademarks and registered trademarks are property of their respective owners.

Toad for Oracle Release Notes

Updated - 1/16/2024

Version - 17.0 Patch 1