

DR Series System

Command Line Reference Guide



Notes, cautions, and warnings



NOTE: A NOTE indicates important information that helps you make better use of your computer.



CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.



WARNING: A WARNING indicates a potential for property damage, personal injury, or death.

© 2016 Dell Inc. or its subsidiaries. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2016 - 12

Rev. A12

Contents

1 Introduction to the DR Series System Command Line Reference Guide.....	13
About the DR Series system CLI documentation.....	13
Other information you may need.....	13
Locating your system Service Tag.....	14
2 Introducing the DR Series system.....	15
Accessing the DR Series system CLI commands.....	16
DR Series system CLI commands overview.....	16
3 Managing the DR Series system.....	18
Alerts Commands.....	18
Alerts Command Usage.....	18
alerts --show [--email].....	19
alerts --show [--snmp].....	19
alerts --show [--events] [--index <[-]number>] [--count <number>] [--all].....	19
alerts --show [--alerts] [--index <[-] number>] [--count <number>] [--all].....	20
alerts --show [--summary].....	20
alerts --email [--relay_host <server name>].....	21
alerts --email [--appliance_alerts <yes no>].....	21
alerts --email [--software_updates <yes no>].....	21
alerts --email [--daily_report <yes no>].....	22
alerts --email [--daily_report_time <0–24 hr>].....	22
alerts --test_email.....	22
alerts --snmp_add --host <server name> --port <number> --community <name>.....	23
alerts --snmp_delete --host <server name>.....	23
alerts --snmp_disable --host <server name>.....	23
alerts --snmp_enable --host <server name>.....	23
alerts --snmp_trap_email [--enable] [--disable].....	24
alerts --help.....	24
Authenticate Commands.....	25
Authenticate Command Usage.....	25
authenticate --show [--users].....	25
authenticate --show [--domain <domain name>].....	26
authenticate --show [--login_group].....	26
authenticate --join --domain <domain name> [--ou <org-unit name>] --user <user name>.....	26
authenticate --leave [--user <user name>] [--force].....	27
authenticate --update --kerberos.....	27
authenticate --add [--user <user name>].....	27
authenticate --add [--login_group <DOMAIN\LOGIN GROUP>].....	28
authenticate --delete--user <user name>.....	28



authenticate --delete [--login_group <DOMAIN\LOGIN GROUP>]	28
authenticate --set --user <user name>	29
authenticate --guestmode [--enable] [--disable]	29
authenticate --guestmode [--enable]	29
authenticate --guestmode [--disable]	30
authenticate --server_signing --mode <auto mandatory disabled>	30
authenticate --help	30
Network	31
Network Command Usage	32
network --show	32
network --delete	33
network --restart	33
network --setdhcp	34
network --setstatic_ip [--bondif <bondN>] [--nwif <ethN>] --ip <IPv4/IPv6 address not already in use> --netmask <netmask> [--gateway <IPv4/IPv6 address>]	34
network --create_bond	34
network --create_eth	35
network --add_member	36
network --setdns [--suffix <dns suffix>] [--primary <IPv4/IPv6 address>] [--secondary <IPv4/IPv6 address>]	36
network --setbonding --bondif <bondN> [--mode <ALB 802.3ad>] [--mtu <supported MTU range 512 - 9000>]	36
network --update	37
network --factory_reset	38
network --host	38
network --route	38
network --nslookup --destination <ip address hostname>	39
network --traceroute --destination <ip address hostname>	39
network --ping --destination <ip address hostname> [--tries <number>] [--size <number>] [--interface <bondN ethN>]	39
network --blink	40
network --enable	41
network --disable	41
network --troubleshoot [--links] [--gateway] [--ntp] [--dns] [--active_domain] [--nis] [--clients] [--port_mapper] [--network_config] [--show_active <NFS CIFS OST RDS NDMP ISCSI FC>] [--interface <bondN ethN>]	41
network --troubleshoot --gateway --interface <bondN ethN>	43
network --troubleshoot --show_active <NFS CIFS OST NDMP ISCSI RDS>	44
network --tcpdump [--port <nfs windows replication ost rds>] [--pkt_size <128 - 32768>] [--file_size <0 - 100>] [--stop] [--host <ip address list>] [--interface <bondN ethN>]	44
network --tcpdump --pkt_size <128 - 32768>	44
network --tcpdump --file_size <0 - 100>	44
network --tcpdump --host <ip address list>	45
network --tcpdump --port <nfs windows replication ost rds>]	45



network --iperf_client --server <ip address hostname> [--port <number>] [--window_size <num bytes [KB/MB]>] [--interval <num seconds>] [--time <num seconds>].....	45
network --iperf_server [--port <number>] [--window_size <num bytes [KB/MB]>].....	46
network --help.....	46
OST.....	49
OST Command Usage.....	49
ost --show [--config] [--file_history] [--name <name>] [--active_files] [--name <name>] [--clients] [--limits].....	50
ost --update --opdup_encryption <none aes128 aes256>.....	51
ost --delete_client --name <OST Client Hostname>	51
ost --update_client --name <OST Client Hostname> --mode <auto passthrough dedupe>.....	51
ost --limit --speed <>num<>KBps MBps GBps default> --target <ip address hostname>.....	52
ost --partial_images --containerid <Container id> [--delete <Partial image path>] [-timeout <> 0>].....	52
ost --help.....	53
RDA.....	53
RDA Command Usage.....	53
rda --show [--config] [--file_history] [--name <name>] [--active_files] [--name <name>] [--clients] [--limits].....	54
rda --update --opdup_encryption <none aes128 aes256>.....	55
rda --delete_client --name <RDA Client Hostname>.....	55
rda --update_client --name <RDA Client Hostname> --mode <auto passthrough dedupe>.....	55
rda --limit --speed <>num<>KBps MBps GBps> default> --target <ip address hostname>.....	56
rda --partial_images --containerid <Container id> [--delete <Partial image path>] [-timeout <> 0>].....	56
rda --help.....	56
Stats.....	57
Stats Command Usage	58
stats --system.....	58
stats --cpu.....	59
stats --memory.....	59
stats --network.....	60
stats --datacheck.....	61
stats --nfs.....	62
stats --cifs.....	62
stats --ost.....	63
stats --rds.....	64
stats --ndmp.....	65
stats --ndmp_completed.....	65
stats --iscsi [--verbose].	65
stats --fc [-iostat] [--linkstat].	66
stats --container --name <name>.....	68
stats --storage_group --name <name>.....	68
stats --replication [--name <name>].....	68
stats --cleaner.....	69
stats --clients [--type <NFS CIFS OST RDS NDMP ISCSI FC>]	70



stats --reset [--nfs] [--cifs] [--ost] [--rds] [--datacheck].....	71
stats --reset --datacheck.....	71
stats --seed	71
stats --help.....	72
stats --datacheck.....	73
stats --datacheck Command Usage.....	73
stats --help datacheck.....	73
Storage Group commands.....	73
Storage Group Command Usage	73
storage_group --show [--name <name>] [-v].....	74
storage_group --add --name <name> [--compression_mode <fast best>].....	74
storage_group --update --name <name> [--compression_mode <fast best>].....	74
storage_group --encryption --name <name> [-set <ON OFF>] [-mode <static internal> <-interval <7 days to 70 years>].....	75
storage_group --setpassphrase --name <name>	75
storage_group --delete --name <name>	76
storage_group --help.....	76
System.....	77
System Command Usage	77
system --show [--config]	78
system --show [--hardware].....	79
system --show [--storage] [--type <boot internal external>] [-service_tag <service tag>].....	79
system --show [--storage].....	80
system --show [--license] [-v].....	81
system --show [--ntp].....	81
system --show [--version].....	81
system --show [--timezones [Region]].....	81
system --show [--upgradefile]	82
system --show [--upgradehistory].....	82
system --show [--marker].....	83
system --show [--replication_traffic].....	83
system --show [--opdup_traffic].....	83
system --show [--backup_traffic].....	83
system --show [--mgmt_traffic].....	83
system --init	84
system --init --secure_erase <1-pass/3-passes/7-passes>.....	85
system --reboot.....	88
system --shutdown.....	88
system --upgrade.....	88
system --license [-validate] [-add].....	89
system --setname --name <node_name>.....	89
system --setdate [--date <date>] [-timezone <Region/Zone>].....	90
system --setntp [-add <server name>].....	90
system --setntp [-delete <server name>].....	91



system --setntp [--enable].....	91
system --setntp [--disable].....	91
system --setntp [--adjust_time].....	91
system --setlogin.....	92
system --telnet [--enable --disable].....	92
system --datacheck --enable.....	92
system --datacheck --disable	93
system --datacheck --throttle.....	93
system --marker [--enable] [--disable].....	93
system --verify_on_read [--enable] [--disable].....	94
system --add_storage --enclosure <service tag>.....	94
system --storage [--set_usage_alert <70% - 90%>].....	95
system --storage [--blink] [-type <internal external>] [--service_tag <service tag>] [--disk <slot num> ...	95
system --storage [--unblink] [-type <internal external>] [--service_tag <service tag>] [--disk <slot num>.....	95
system --mgmt_traffic	96
system --backup_traffic	96
system --replication_traffic.....	96
system --opdup_traffic	97
system --support_agent --register.....	97
system --support_agent --unregister.....	98
system --support_agent --stats.....	98
system --support_agent --status.....	98
system --help.....	98
User.....	100
User Command Usage	100
user --show [--users] [--logins] [--verbose][--name <username>] [--roles <cifs ost rda ndmp iscsi monitor administrator email_recipient>.....	100
user --enable --user <service root>.....	101
user --disable --user <service root>.....	101
user --add --name <user name>.....	102
user --update --name <user name> [--new_name <user name>] [--add_roles <cifs ost rda ndmp iscsi monitor email_recipient>] [--remove_roles <cifs ost rda ndmp iscsi monitor email_recipient>] [--full_name <full name>] [--phone <phone number>] [--email_addr <email address>] [--description <description>].....	102
user --delete --name <user name>.....	102
user --setpassword --name <user name>.....	102
user --help.....	103
Virtual Machine.....	104
Virtual Machine Command Usage	104
virtual_machine -- show [--service_tag <service tag>].....	104
virtual_machine --show --summary.....	104
virtual_machine --update [--host <ip address hostname>] [--name <administrator name>] [--email <email address>] [--company <company name>] [--comments <comments>].....	105



virtual_machine --register [--host <ip address hostname>] [--name <administrator name>] [--email <email address>] [--company <company name>] [--comments <comments>].....	105
virtual_machine --unregister [-force].....	105
virtual_machine --delete --service_tag <service tag>.....	105

4 Maintaining the DR Series System.....

Diagnostics.....	106
Diagnostics Command Usage	106
diagnostics --start-service.....	107
diagnostics --show.....	107
diagnostics --collect.....	107
diagnostics --collect [--name <name>].....	108
diagnostics --collect [--reason <reason>].....	108
diagnostics --collect [--force].....	108
diagnostics --collect [--dset].....	109
diagnostics --collect [--logs].....	109
diagnostics --collect [--cores].....	109
diagnostics --collect [--tcpdump].....	110
diagnostics --collect [--process_dump].....	110
diagnostics --collect [--all].....	110
diagnostics --delete [--name <name>].....	110
diagnostics --delete [--all].....	111
diagnostics --copy --name <name> --host <user@host ip:><path>>.....	111
diagnostics --help.....	111
Maintenance.....	112
Maintenance Command Usage.....	112
maintenance --filesystem [--start_scan [verify_data verify_rda_metadata verify_metadata] [--storage_group <name>].....	113
maintenance --filesystem [--stop_scan].....	113
maintenance --filesystem [--scan_status].....	113
maintenance --filesystem [--scan_report [verbose]].....	114
maintenance --filesystem [--repair_status [verbose]]	114
maintenance --filesystem [--repair_history [verbose]].....	115
maintenance --filesystem [--scan_restart [verify_data verify_rda_metadata verify_metadata]].....	115
maintenance --filesystem [--repair_now].....	116
maintenance --filesystem [--reclaim_space].....	116
maintenance --filesystem [--stop_reclaim_space].....	116
maintenance --filesystem [--clear_quarantine].....	116
maintenance --filesystem --show_throughput.....	116
maintenance --configuration [--backup].....	117
maintenance --configuration [--restore]	117
maintenance --configuration [--reinit_dictionary].....	117
maintenance --configuration [--reset_web_certificate].....	118
maintenance --hardware [--reinit_nvram].....	118



maintenance --hardware [--restore_hw_db].....	118
maintenance --hardware [--motherboard_replaced].....	119
maintenance --disk [--make_standby [slot num]] [-type <internal external-<num> service tag>] --clear_foreign].....	119
maintenance --remote_access [--show].....	119
maintenance --remote_access [--enable].....	120
maintenance --remote_access [--racreset].....	120
maintenance --remote_access [--static_ip] [--ip <IPv4/IPv6 address>] [--netmask <netmask>] [--gateway <IPv4/IPv6 address>] [-device <lom1 lom2 lom3 lom4>].....	120
maintenance --remote access [--disable].....	121
maintenance --vdisk --check_consistency --type <boot internal external> [--service_tag <service tag>].	121
maintenance --help.....	121

5 Managing DR Series System Storage Operations.....123

System Storage Operation Commands.....	123
Connection.....	123
Connection Command Usage	123
connection --show [--name <name>]	123
connection --show [--name <name>] [-type <NFS CIFS OST RDS NDMP ISCSI FC>] [--verbose].....	124
connection --show [-verbose].....	125
connection --add --name <name> --type <NFS CIFS OST RDS NDMP ISCSI FC> [--clients <ip address>][--dma <ip address>][-initiator <IQN, ip address(es), hostname, or WWPN>][-rootmap <nobody root administrator>] [--options <NFS CIFS mount export options>] [--capacity <positive decimal number>].....	126
connection --update --name <name> --type <NFS CIFS OST RDS NDMP ISCSI FC> [--clients <ip address>][--dma <ip address>][-initiator <IQN, ip address(es), hostname, or WWPN>][-rootmap <nobody root administrator>] [--options <NFS CIFS mount export options>] [--capacity <positive decimal number>].....	126
connection --delete --name <name> --type <NFS CIFS OST RDS NDMP ISCSI FC> [--clients <ip address>].....	127
connection --enable --name <name> --type <NFS CIFS OST RDS>.....	127
connection --disable --name <name> --type <NFS CIFS OST RDS>.....	127
connection --help.....	128
Container.....	129
Container Command Usage	129
container --show.....	129
container --show [--name <name>] [-verbose].....	129
container --add --name <name> [-type <VTL>] [--tape_size <tape_size>][--no_of_drives <1-60>][--is_oem <yes no>][-group_name <name>].....	130
container --update --name <name> [-no_of_drives <1-60>].....	130
container --delete --name <name>.....	131
container --delete --name <name> [-delete_files].....	131



container --marker [--enable <Auto CommVault Networker TSM ARCserve HP_DataProtector Unix_Dump BridgeHead>] [--disable <Auto CommVault Networker TSM ARCserve HP_DataProtector Unix_Dump BridgeHead>] --name <name>.....	131
container --delete_files --name <name>.....	132
container --help.....	132
VTL.....	133
VTL Command Usage	133
vtl --show [--name <name>].....	133
vtl --show --verbose [--name <name>].....	134
vtl --update_carts --name <name> --add --no_of_tapes <number>.....	134
vtl --activate --name <name> [--force <yes no>].....	135
vtl --deactivate --name <name>	135
vtl --rescan --name <name> [--force <yes no>].....	135
vtl --set_rw --name <name> [-id <number>].....	135
vtl --show_replstate --name <name>	136
vtl --help.....	136
NDMP.....	137
NDMP Command Usage	137
ndmp --show	137
ndmp --update [--port <port number>].....	137
ndmp --help.....	137
iSCSI.....	138
ISCSI Command Usage	138
iscsi --show [--user].....	138
iscsi --setpassword	139
iscsi --sessions	139
iscsi --help.....	140
FC.....	140
FC Command Usage	140
fc --show [--verbose] [--target].....	140
fc --sessions [--topology] [--condensed].....	142
fc --help <command>.....	143
Replication.....	143
Replication Command Usage	144
replication --show [--name <name>] [--role <source target>] [--verbose] [--limits].....	144
replication --show.....	145
replication --show [--limits].....	145
replication --add --name <name> --role <source target> --peer <ip address hostname> [--peer_name <name>] [--peer_group_name <name>] [--replication_traffic <ip address hostname>] [--encryption <none aes128 aes256>] [--username <user name>].....	145
replication --update --name <name> --role <source target> [--peer <ip address hostname>] [--encryption <none aes128 aes256>] [--username <user name>].....	146
replication --delete --name <name> --role <source target> [--force].....	146
replication --start --name <name> --role <source target>.....	147



replication --stop --name <name> --role <source target>.....	147
replication --limit --speed <>num><KBps MBps GBps> default> --target <ip address hostname>.....	148
replication --resync --name <name> --role <source target>.....	148
replication --troubleshoot --peer <ip address hostname>.....	148
replication --help.....	149
Seed.....	150
Seed Command Usage	150
seed --create --op <import export> [--enc_type <aes128 aes256>] [--storage_group_name <name>]....	151
seed --add_container --name <container name>.....	151
seed --add_device --server <server name> --volume <volume> --username <username> --domain <domain name>.....	151
seed --cleanup.....	152
seed --create --op <import> [->enc_type <aes128 aes256>].....	152
seed --remove_device	152
seed --show.....	152
seed --start.....	153
seed --help.....	153
Schedule.....	154
Schedule Command Usage.....	154
schedule --show [--cleaner].....	154
schedule --show [--replication] [--name <name>].....	155
schedule --add --day <day of the week> [--cleaner] [--replication] [--start_time <hh:mm>] [--stop_time <hh:mm>] [--name <name>].....	155
schedule --delete --day <day of the week> [--cleaner] [--name <name>] [--replication].....	156
schedule --help.....	156
6 Data Integrity Checking.....	157
About Data Check.....	157
Priority Write Verify Scans.....	157
Continuous Data Verification Scans.....	158
Data Check CLI Commands.....	158
Data Check Options.....	158
System --Datacheck.....	159
System --Datacheck Command Usage.....	159
system --datacheck.....	159
system --datacheck --disable	159
system --datacheck --enable.....	160
system --datacheck --throttle.....	160
system --help datacheck.....	160
stats --datacheck.....	161
stats --datacheck Command Usage.....	161
stats --datacheck.....	161
7 Additional Linux Commands.....	163



grep.....	163
Description.....	163
Syntax.....	163
Result.....	163
more.....	164
Description.....	164
Syntax.....	164
Results.....	164

Introduction to the DR Series System Command Line Reference Guide

About the DR Series system CLI documentation

This topic introduces the concept of using the DR Series system command line interface (CLI) for managing your data backups, performing a variety of data storage operations, and using containers to meet your backup and replication storage needs.

 **NOTE:** The DR Series system CLI provides one method for managing the DR Series system, with the other being the DR Series system graphical user interface (GUI). In some instances, the DR Series system CLI can provide additional features and options that are not available in the DR Series system GUI and vice versa.

Other information you may need

 **WARNING:** The following table lists the documentation available for the DR Series systems. The documents listed are available at support.quest.com/DR-Series by selecting your specific DR Series system. For more information about DR Series system hardware, see the safety and regulatory information that shipped with your DR Series system. Warranty information may be included as a separate document.

Document	Description
<i>DR Series System Getting Started Guide</i>	Provides an overview of how to set up the physical DR Series system hardware and includes technical specifications.
<i>DR Series System Owner's Manual</i>	Provides information about applicable physical DR Series system features, troubleshooting the DR Series system, and installing or replacing the DR Series system components.
<i>DR2000v Deployment Guide</i>	Provides information about deploying the virtual DR Series system, DR2000v, on supported virtual platforms.
<i>DR Series System Administrator Guide</i>	Provides information about managing backup and replication operations using the DR Series system GUI.
<i>DR Series System Interoperability Guide</i>	Provides information on supported hardware and software for the DR Series systems.
<i>DR Series System Command Line Reference Guide</i>	Provides information about managing DR Series system data backup and replication operations using the DR Series system command line interface (CLI).
<i>DR Series System Release Notes</i>	Provides the latest information about new features and known issues with a specific product release.

 **NOTE:** Always check for the latest documentation updates and release notes at support.quest.com/dr-series, and read the release notes first because they contain the most recently documented information about known issues with a specific product release.



Locating your system Service Tag

Your system is identified by a unique Express Service Code and Service Tag number. The Express Service Code and Service Tag are found on the front of a physical DR Series system by pulling out the information tag. The service tag can also be found on the Support page in the GUI. This information is used to route support calls to the appropriate personnel for resolution.

Introducing the DR Series system

The DR Series system is a high-performance, disk-based backup and recovery appliance that is simple to deploy and manage and offers unsurpassed Total Cost of Ownership benefits. Features such as innovative firmware and an all-inclusive licensing model ensure optimal functionality and provide the assurance of no hidden costs for valuable future features.

 **NOTE:** Unless otherwise noted, later references to "the system" or "DR Series system" are used interchangeably to represent the DR Series system.

A purpose-built backup-to-disk appliance, the DR Series system provides advanced deduplication and compression technology to store data most efficiently. The DR Series hardware appliances are 2U, rack-based, system backup storage repositories, that include deduplication and compression technology in their operating systems. A virtual machine (VM) version is also available (that is connected via a license with a DR Series hardware appliance) to provide robust, disk-based data backup capability on Virtual Machine host servers, while taking advantage of replicating to a deduplication-enabled appliance.

Data Protection | DR Series of backup and deduplication appliances support all the major backup software applications in use today and can lower your backup storage costs to as little as \$.16/GB while reducing your total cost of ownership. The purpose built appliances achieve these results using patented Rapid technology as well as built-in, variable block-based deduplication and compression. The DR Series helps you to:

- Reduce your backup storage footprint
- Speed up recovery
- Reduce or eliminate the need for physical tapes for backup
- Optimize network bandwidth by lowering the amount of data sent to disaster recovery sites

The DR Series system includes the following features:

- Advanced data protection and disaster recover
- Two management interfaces: a command line interface (CLI) or a system graphical user interface (GUI) for the system software to manage storage containers.
- Support for a wide variety of data backup installations and environments.
- A simple installation process that provides full, intuitive remote setup and management capabilities.

The system is available in many drive capacities to fit SMB, enterprise, and remote office environments. The internal system drive capacity and available physical capacities of the DR Series system vary, depending on your system type and drives installed. For details about specific drive capacities and models available, see the *DR Series System Interoperability Guide* or the latest *DR Series System Release Notes*.

Understanding the DR Series system CLI

The DR Series system command line interface (CLI) provides the means for managing the status, data capacity, storage savings, and throughput of data containers.

 **NOTE:** An online data verification or data-checking feature called Data Check is enabled by default on the DR Series system. For more information about Data Check, see [Data Integrity Checking](#).



Accessing the DR Series system CLI commands

This guide assumes that your DR Series system has been deployed in the proper network location and is ready to be accessed using the DR Series system CLI commands.

To access the DR Series system CLI commands from the system CLI prompt, complete the following steps.

1. Launch a terminal emulation application and start the process for logging in to the DR Series system.
2. In **Host Name (or IP address)**, type the host name or IP address for the DR Series system, and click **Open**.
3. At the system prompt, enter the username for the Administrator:
 - Type **administrator**
 - Press <**Enter**>
4. At the administrator password prompt, enter the password for the Administrator (the default is **St0r@ge!**):
 - Type **St0r@ge!**
 - Press <**Enter**>

The DR Series system administrator prompt is displayed.

5. At the administrator prompt, type **help**.

The DR Series system CLI commands are displayed.

DR Series system CLI commands overview

The following command groups are available in the DR Series system CLI.

 **NOTE:** The DR Series system Administrator account only provides access to the DR Series system CLI commands listed in this section. There is no access to Linux commands other than *grep* or *more* from the DR Series system command line with the Administrator account.

For more information on each command group, run the following command:

```
<command name> --help show
```

Table 1. DR Series System CLI Commands Overview

Command Group	Description
alerts	View system events and configure email notifications, contact information, and daily reports.
authenticate	Configure Active Directory (AD) authentication.
connection	Configure NFS CIFS OST RDS NDMP iSCSI FC access to a container.
container	Configure a file system to share over NFS CIFS OST RDS NDMP iSCSI FC.
diagnostics	Gather log information for support issues.
help	Display this help message.
iscsi	Manage and view iscsi connection types for VTL containers.
ndmp	Manage and view ndmp connection types for VTL containers.
fc	Manage and view fibre channel connection types for VTL containers.
maintenance	Repair the data and state of the system.



Command Group	Description
network	Configure networking properties.
ost	Configure OST for Veritas (formerly Symantec) backup applications.
rda	Configure Rapid Data Access (RDA) for the NetVault application.
replication	Manage replication between systems.
seed	Configure and manage seeding import or export.
schedule	Manage replication and cleaner schedules in the system.
stats	View statistics for system components.
storage_group	Manage and view the storage groups on a DR Series system
system	Manage and view the system configuration.
user	Enable or disable service and root accounts on the node.
virtual machine	Manage and view DR2000v virtual machines.
vtl	Manage and view VTL container types.
grep	System tools
more	



Managing the DR Series system

This topic introduces the DR Series system CLI commands for configuring, managing, and viewing the current status of a DR Series system. For example, the DR Series system CLI **alerts** and **system** commands both contain options that provide administrators with the capability to configure, manage, and display the status of the a DR Series system.

The following list of commands provide the functionality for configuring, managing, and displaying the DR Series system status:

- **Alerts**
- **Authenticate**
- **Network**
- **OST** (OpenStorage Technology)
- **RDA** (Rapid Data Access)
- **Stats** (statistics)
- **Storage Group**
- **System**
- **User**
- **Virtual Machine**

Alerts Commands

This topic introduces the set of DR Series system CLI commands that enable you to perform the following tasks:

- Display system alerts and events.
- Create new email accounts or modify existing email accounts for recipients, which are used for email alert notifications.
- Select to receive notifications about appliance alerts and software updates.
- Test to confirm that email account recipients can receive alerts via Simple Network Management Protocol (SNMP) traps for a designated host.
- Set, enable, disable, or delete SNMP traps for a designated host.

Alerts Command Usage

This topic introduces the **alerts** command usage:

- **alerts --show [options]**
- **alerts --email [options]**
- **alerts --test_email**
- **alerts --snmp_add [options]**
- **alerts --snmp_delete --host <server name>**
- **alerts --snmp_enable --host <server name>**
- **alerts --snmp_disable --host <server name>**
- **alerts --snmp_trap_email [options]**

- alerts --help

 NOTE: If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

alerts --show [--email]

Description

Displays the list of email recipients, mail relay host, and the administrator contact information for the DR Series system.

Syntax

```
alerts --show --email
```

Result

Recipients:	john_smith@acme.com
Relay Host:	10.10.10.10
Admin Name:	John Smith
Company Name:	Acme.com
Admin Email:	john_smith@acme.com
Phone:	408-555-1212
Comments:	Day Shift Administrator

alerts --show [--snmp]

Description

Displays the current SNMP information for a DR Series system.

Syntax

```
alerts --show --snmp
```

Result

Host		Status	Port	Community
10.20.20.10	Enabled	2100	snmpPublic	
10.25.19.11	Enabled	1120	snmpPublic12	
10.12.14.20	Enabled	1550	snmpPublic11	

 NOTE: For more information about configuring a host to receive SNMP alerts, see [alerts --email \[--relay_host <server name>\]](#).

alerts --show [--events] [--index <[-]number>] [--count <number>] [--all]

Description

Displays the current list of system events.

 NOTE: The default is to display the 32 most recent events (this example is intentionally brief). The count and index options can also be used to filter the list of events (alerts --show --events --index <number> or alerts --show --events --index <number>).

Syntax

```
alerts --show --events
```

Result

Index	Severity		Event	Message
Time				
-				
399	INFO	2012-06-10 14:07:18		System
	diagnostic package collected.			
398	INFO	2012-06-10 12:21:47		Successfully
	updated Cleaner schedule.			



397 INFO 2012-06-10 12:20:03 User service
enabled.

alerts --show [--alerts] [--index <[-] number>] [--count <number>] [--all]

Description

Displays the current list of DR Series system alerts.

 **NOTE:** By default, all DR Series system alerts are displayed.

Syntax

```
alerts --show --alerts
```

Result

Index
1

Time
2012-06-19 18:19:09

Alert Message
Network Interface Controller Embedded (LOM) Port 1 disconnected. Reconnect it to a network
and/or check your network switches or routers for network connectivity issues.

Index
2

Time
2012-06-19 18:19:09

Alert Message
Network Interface Controller PCI Slot 1 Port 0 disconnected. Reconnect it to a network
and/or check your network switches or routers for network connectivity issues.

Index
3

Time
2012-06-19 18:19:09

Alert Message
Network Interface Controller PCI Slot 1 Port 1 disconnected. Reconnect it to a network
and/or check your network switches or routers for network connectivity issues.

alerts --show [--summary]

Description

Displays a summary list of DR Series system alerts.

Syntax

```
alerts --show --summary
```

Result

Total alert messages:	5
Total event messages:	42
Last event index:	42



alerts --email [--relay_host <server name>]

Description

Configures the email relay host that can receive alert email notifications for the DR Series system.

Syntax

```
alerts --email --relay_host relayhost13
```

Result

```
Alert email settings updated.  
Recipients: john_smith@acme.com;juan_ruiz@acme.com  
Relay Host: relayhost13  
Admin Name: John_Smith  
Company Name: Acme.com  
Admin Email: john_smith@acme.com  
Phone: 408-555-1212  
Comments: Day Shift Administrator
```

alerts --email [--appliance_alerts <yes | no>]

Description

Configures the “yes/no” setting for sending email notifications to the administrator of a DR Series system when there are alerts for the system appliance. Setting this option to **yes** causes the system administrator to receive email notifications when there are system appliance alerts (setting this option to **no** means that the system administrator will not receive email notifications about system appliance alerts).

Syntax

```
alerts --email --appliance_alerts yes
```

Result

```
Alert email settings updated.  
Recipients : juan_corona@acme.com  
Relay Host : acme-sys-60.western.local  
Admin Name : Juan Corona  
Company Name : Acme Inc.  
Admin Email : juan_corona@acme.com  
Phone : 438-999-6699  
Comments : Days shift1 administrator  
Appliance Alerts : Yes  
Software Updates : Yes  
Email SNMP Trap's : No  
Email Daily container stats : Yes
```

alerts --email [--software_updates <yes | no>]

Description

Configures the “yes/no” setting for sending email notifications to the administrator of a DR Series system when there are updates for the system software installed on the system appliance. Setting this option to **yes** causes the system administrator to receive email notifications when there are system software updates (setting this option to **no** means that the system administrator will not receive email notifications about system software updates).

Syntax

```
alerts --email --software_updates yes
```

Result

```
Alert email settings updated.  
Recipients : juan_corona@acme.com  
Relay Host : acme-sys-60.western.local
```



```

Admin Name : Juan Corona
Company Name : Acme Inc.
Admin Email : juan_corona@acme.com
Phone : 438-999-6699
Comments : Days shift1 administrator
Appliance Alerts : Yes
Software Updates : Yes
Email SNMP Trap's : No
Email Daily container stats : Yes

```

alerts --email [--daily_report <yes | no>]

Description

Configures the “yes/no” setting for sending daily statistics about each container to the administrator of a DR Series system. Setting this option to **yes** causes the system administrator to receive email notifications containing the statistics for the last 24 hours for each container (setting this option to **no** means that the system administrator will not receive daily email notifications about container statistics).

Syntax

```

alerts --email --daily_report <yes|no>

--yes  Enables daily container stats notification on DR.
--no   Disables daily container stats notification on DR.

```

Result

```

alerts --email --daily_report yes

Alert email settings updated.
Daily container stats notification has been enabled.
Recipients : juan_corona@acme.com
Relay Host : acme-sys-60.western.local
Admin Name : Juan Corona
Company Name : Acme Inc.
Admin Email : juan_corona@acme.com
Phone : 438-999-6699
Comments : Days shift1 administrator
Appliance Alerts : Yes
Software Updates : Yes
Email SNMP Trap's : No
Email Daily container stats : Yes

```

alerts --email [--daily_report_time <0-24 hr>]

Description

Sets the time for the daily container statistics report to be sent.

Syntax

```
alerts --email --daily_report_time <0-24 hr>
```

Result

```
alerts --email --daily_report_time
```

alerts --test_email

Description

Sends a test email alert notification to all of the configured email recipients in the DR Series system.



 **NOTE:** Verify that the configured email recipients received the test email notifications that were sent. This is an important check that proves that the designated email recipients can receive DR Series system alert notifications.

Syntax

```
alerts --test_email
```

Result

Test email sent.

alerts --snmp_add --host <server name> --port <number> --community <name>

Description

Sets SNMP traps for a host by defining its host name, port number, and listing the corresponding SNMP community.

Syntax

```
alerts --snmp_add --host 10.12.14.20 --port 1550 --community snmpPublic1
```

Result

Host "10.12.14.20" added to SNMP alert recipients.

alerts --snmp_delete --host <server name>

Description

Deletes SNMP traps for a host by identifying it by name or IP address at the DR Series system prompt.

Syntax

```
alerts --snmp_delete --host 10.10.10.12
```

Result

Host "10.10.10.12" deleted from SNMP alert recipients.

alerts --snmp_disable --host <server name>

Description

Disables SNMP traps for a host by identifying it by name or IP address at the DR Series system prompt.

Syntax

```
alerts --snmp_disable --host 10.12.14.20
```

Result

Host "10.12.14.20" disabled for SNMP alerts.

alerts --snmp_enable --host <server name>

Description

Enables SNMP traps for a host by identifying it by name or IP address at the DR Series system prompt.

Syntax

```
alerts --snmp_enable --host 10.12.14.20
```

Result

Host "10.12.14.20" enabled for SNMP alerts.



alerts --snmp_trap_email [--enable] [--disable]

Description

Enables or disables SNMP traps to be sent out as an email message.

Syntax

```
alerts --snmp_trap_email --enable
```

Result

Successfully enabled SNMP Trap email forwarding.

 **NOTE: To disable SNMP trap mail forwarding, substitute the --disable command, as in the following example:**

```
alerts --snmp_trap_email --disable  
Successfully disabled SNMP Trap email forwarding.
```

alerts --help

Description

Displays the listing of alerts and related options for using the DR Series system CLI.

Syntax

```
alerts --help
```

Result

Usage:

```
    alerts --show [--email]  
          [--snmp]  
          [--events] [--index <[-]number>] [--count <number>] [--all]  
          [--alerts] [--index <[-]number>] [--count <number>] [--all]  
          [--summary]  
  
    alerts --email  
          [--relay_host <server name>]  
          [--appliance_alerts <yes|no>]  
          [--software_updates <yes|no>]  
          [--daily_report_time <0-24 hr>]  
  
    alerts --test_email  
    alerts --snmp_add --host <server name>  
          --port <number>  
          --community <name>  
  
    alerts --snmp_delete --host <server name>  
  
    alerts --snmp_enable --host <server name>  
  
    alerts --snmp_disable --host <server name>  
  
    alerts --snmp_trap_email [--enable] [--disable]  
  
    alerts --help  
  
alerts <command> <command-arguments>  
<command> can be one of:  
--show           Displays system alerts and events.  
--email          Sets for alert notifications.  
--test_email     Sends a test email using current email settings.  
--snmp_add       Sets SNMP traps to be sent to a host.  
--snmp_delete    Stops sending SNMP traps to a host.  
--snmp_enable    Enables SNMP traps for a host.  
--snmp_disable   Disables SNMP traps for a host.
```



```
--snmp_trap_email    Enables/Disables SNMP traps to be sent out as an email.
```

For command-specific help, please type alerts --help <command>
For example:
 alerts --help show

Authenticate Commands

This topic introduces the set of DR Series system CLI commands that let you configure the DR Series system so it can authenticate with the Microsoft Windows Active Directory Services (ADS).

For information about specific **authenticate** commands, see [Authenticate Command Usage](#).

Authenticate Command Usage

This topic introduces the **authenticate** command usage:

- **authenticate --show [options]**
- **authenticate --join [options]**
- **authenticate --leave [options]**
- **authenticate --update --kerberos**
- **authenticate --add [options]**
- **authenticate --delete [options]**
- **authenticate --set --user <user name>**
- **authenticate --guestmode [options]**
- **authenticate --server_signing --mode <auto|mandatory|disabled|show>**
- **authenticate --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

authenticate --show [--users]

Description

Displays the current status of the Microsoft Active Directory Service (ADS) domain, or if it is not joined, it can display the status of any authorized local CIFS user. For more information, see the [authenticate --show \[--domain <domain name>\]](#).

 **NOTE:** If this command is entered, but the DR Series system has not joined the ADS to any domain, the following message is displayed.

This system has not joined any domain.

Syntax

```
authenticate --show
```

Result

```
Domain: ads.storage.local
```

If you have joined the ADS to a designated domain and you want to see the authorized users, enter the **authenticate --show --users** command to display the current status:

```
authenticate --show --users
administrator2
administrator
```



authenticate --show [--domain <domain name>]

Description

Displays the current status of the Active Directory Services (ADS) domain to which the DR Series system is joined.

-  **NOTE:** If you have not joined the DR Series system to an ADS domain, use the DR Series system CLI authenticate --join --domain command. For more information, see [authenticate --join --domain <domain name> \[--ou <org-unit name>\] --user <user name>](#).

Syntax

```
authenticate --show --domain acme-ad.acme.local
```

Result

Domain Name	:	acme-ad.acme.local
Domain Controller Time	:	2012-10-19 12:13:40 PDT
System Time	:	2012-10-19 12:13:40 PDT
Time Skew	:	0 secs
Domain Controller Name	:	test-ad-2008r2.acme-ad.acme.local
Domain Controller Address	:	10.20.20.4

authenticate --show [--login_group]

Description

Displays the currently enabled and authenticated login group on a Microsoft Active Directory Services domain.

Syntax

```
authenticate --show --login_group
```

Result

```
Login group: acmeADS\Domain Admins
```

authenticate --join --domain <domain name> [--ou <org-unit name>] --user <user name>

Description

Joins the DR Series system to an Active Directory Services (ADS) domain when you specify the ADS domain name and a valid user (administrator) for that domain.

-  **NOTE:** When attempting to join the ADS domain, the administrator password is required for that domain to ensure that the join operation is successful. Supported domain names are limited to 64 characters in length and can only consist of a combination of A-Z, a-z, 0-9, and two special characters: a dash (-) and a period (.).

-  **NOTE:** If you had previously joined the DR Series system to an ADS domain before running Restore Manager (RM), after it completes you must manually rejoin the desired ADS domain using the authenticate --join command.

Syntax

```
authenticate --join --domain ads.storage.local --user administrator
```

Result

```
Enter password for administrator@ads.storage.local:  
Successfully joined domain ads.storage.local  
Disabling NTP service... done.  
Updated Windows Access Server Configuration.  
Updated Kerberos configuration.  
Updated machine password.  
Updated DNS.  
Restarting Windows Access Server... done.
```



 NOTE: The --ou command is optional and allows for defining a specific organizational group in the ADS that requires its own administrative access rights (such as an executive management or finance group). In case of multiple organizational groups, use the following format: "<topLevelOU/middleLevelOU/LowerLevelOU/TargetOU>"

authenticate --leave [--user <user name>] [--force]

Description

Enables a DR Series system to leave a Microsoft Active Directory Services (ADS) domain when you provide a valid administrator password.

Syntax

```
authenticate --leave --user administrator
```

Result

```
Enter password for administrator@ads.storage.local:  
Successfully left domain ads.storage.local.  
Updated Windows Access Server configuration.  
Updated Kerberos configuration  
Restarting Windows Access Server... done.  
Enabling NTP service... done.
```

 NOTE: The --force command is optional and allows the DR Series system to leave the ADS domain when communication between the system and the ADS domain is lost and the --leave operation is pending or in progress.

authenticate --update --kerberos

Description

Updates a Microsoft Active Directory Service (ADS) Kerberos configuration (Kerberos is a computer network authentication protocol).

Syntax

```
authenticate --update --kerberos
```

Result

```
Updated kerberos configuration.
```

authenticate --add [--user <user name>]

Description

Adds a new local CIFS workgroup user for CIFS authentication (and administrative tasks) after you provide and confirm the CIFS user password.

Syntax

```
authenticate --add --user administrator2
```

Result

```
Enter password for new CIFS user administrator2:  
Re-enter password for new CIFS user administrator2:  
Added CIFS user administrator2.
```



authenticate --add [--login_group <DOMAIN\LOGIN GROUP>]

Description

Adds an authenticated login group in an Active Directory Services (ADS) domain in accordance with the following ADS login group guidelines:

- Log in as an administrator via the CLI, and use SSH, Telnet, or a local console connection as a domain\user that is part of a login group. When you log in as an administrator via the CLI, you are prompted to use the credentials of the user account by which you log in (for example: if you log in as a Domain\administrator, you need to respond using these credentials).
- Log in as an administrator via the GUI, and use a web interface connection as a domain\user that is part of a login group (when this has been enabled via the CLI).
- If no login group is specified, or the group is disabled, no access using domain accounts is permitted.
- Adding a login group can only be enabled via the CLI.
- Adding a login group is only possible when the DR Series system is already joined to a domain.
- If the login group name has a space in it, it must be contained within double-quotation marks (" ").
- When adding a login group, it must use the naming convention of Domain\group name.
- The login group must exist in the domain before you can add it (a check is performed to verify that the group exists in ADS).
- Changes made to the login group take effect on the next log in attempt (no active checking is done on group, which matches how Windows ADS works).

 **NOTE:** To delete an existing login group, see [authenticate --delete \[--login_group <DOMAIN\LOGIN GROUP>\]](#).

Syntax

```
authenticate --add --login_group "acmeads\Domain Admins"
```

Result

Successfully added login group acmeads\Domain Admins.

authenticate --delete--user <user name>

Description

Deletes an existing local CIFS workgroup user from CIFS authentication (and administrative tasks).

Syntax

```
authenticate --delete --user administrator2
```

Result

Deleted CIFS user administrator2.

authenticate --delete [--login_group <DOMAIN\LOGIN GROUP>]

Description

Deletes an existing authenticated login group in an Active Directory Services (ADS) domain. For more information about DR Series system and ADS login group guidelines, see [authenticate --add \[--login_group <DOMAIN\LOGIN GROUP>\]](#).

 **NOTE:** Ensure that the login group exists in the Active Directory Services (ADS) domain, and that the "\ and any spaces in the login group name are in quotation marks (" ").

Syntax

```
authenticate --delete --login_group "acmeads\Domain Admins"
```

Result

Deleted login group acmeads\Domain Admins.



authenticate --set --user <user name>

Description

Sets the password for an existing local CIFS workgroup user when you create and confirm the new password.

Syntax

```
authenticate --set --user administrator2
```

Result

```
Enter new password for CIFS user administrator2:  
Re-enter new password for CIFS user administrator2:  
Changed administrator2's password.
```

 **NOTE:** The DR Series system administrator that manages the DR Series system has a different set of privileges than does the CIFS user administrator. For example, only the DR Series system administrator can change the password for the CIFS user administrator.

authenticate --guestmode [--enable] [--disable]

Description

Configures all CIFS shares for guest-only access by enabling or disabling this capability. For specific examples of enabling or disabling guest-only access, see [authenticate --guestmode --enable](#) and [authenticate --guestmode --disable](#).

Syntax

```
authenticate --guestmode
```

Result

Must include either enable or disable option.
--guestmode - Configures all CIFS shares for guest only access.

Usage:

```
authenticate --guestmode [--enable]  
                  [--disable]  
  
      --enable     Enable only guest access CIFS shares.  
      --disable    Disable only guest access for CIFS shares.
```

authenticate --guestmode [--enable]

Description

Configures all CIFS shares for guest-only access.

Syntax

```
authenticate --guestmode --enable
```

Result

Restarting Windows Access Server... done.

 **NOTE:** If you attempt to enable guestmode for all CIFS shares when the DR Series system is already joined to an ADS domain by (using the DR Series system CLI authenticate --guestmode --enable command), the following error message displays: *This node is already joined to domain <domainname>. Please leave the domain before enabling the guest-only mode.*



authenticate --guestmode [--disable]

Description

Disables all CIFS shares as guest-only access.

Syntax

```
authenticate --guestmode --disable
```

Result

Restarting Windows Access Server... done.

 **NOTE:** If you attempt to enable guestmode for all CIFS shares when the DR Series system is already joined to an ADS domain (using the DR Series system CLI `authenticate --guestmode --enable` command), the following error message displays: *This node is already joined to domain <domainname>. Please leave the domain before enabling the guest-only mode.*

authenticate --server_signing --mode <auto | mandatory | disabled>

Description

Configures the server signing for Common Internet File System (CIFS) on a DR Series system. This is a security provision based on Server Message Block (SMB) signing, a form of packet authentication. After CIFS-based users are authenticated, SMB signing adds a digital signature to each packet that is transferred between client and server. These digital signatures verify that the identity of the server matches the credentials expected by the client, and vice versa. By verifying that every packet that is received comes from an authenticated source, these digital signatures ensure the integrity of the communications. The DR Series system CLI `--server_signing --mode` command contains four values:

- **auto** — Configures authentication via server signing to be automatically performed.
- **mandatory** — Configures authentication via server signing as mandatory, or the connection will be dropped.
- **disabled** — Disables authentication via server signing so that no connections are accepted.

Syntax

```
authenticate --server_signing --mode auto
```

Result

Successfully added server signing to auto.

authenticate --help

Description

Displays the list of all authenticate-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
authenticate --help
```

Result

```
Usage:  
authenticate --show [--users]  
                  [--domain <domain name>]  
                  [--login_group]  
  
authenticate --join --domain <domain name>  
                  [--ou <org-unit name>]  
                  --user <user name>  
  
authenticate --leave [--user <user name>]  
                  [--force]
```



```

authenticate --update --kerberos

authenticate --add [--user <user name>]
                  [--login_group <DOMAIN\LOGIN GROUP>]

authenticate --delete [--user <user name>]
                  [--login_group <DOMAIN\LOGIN GROUP>]

authenticate --set --user <user name>

authenticate --guestmode [--enable]
                  [--disable]

authenticate --server_signing --mode <auto|mandatory|disabled|show>

authenticate --help

authenticate <command> <command-arguments>
<command> can be one of:
--show           Displays current ADS domain, authorized local CIFS users, and
login group.
--join            Joins an ADS domain.
--leave           Leaves an ADS domain.
--update          Updates ADS configuration.
--add             Creates local workgroup user for CIFS authentication or adds
login group.
--delete          Deletes local workgroup user from CIFS authentication or
deletes login group.
--set              Sets password for a local workgroup user.
--guestmode       Configures all CIFS shares for guest only access.
--server_signing Configures server signing for CIFS.

```

For command-specific help, please type `authenticate --help <command>`
 For example:

```
      authenticate --help show
```

Network

The DR Series system CLI commands let you perform the following network-related tasks:

- Displays information about a DR Series system.
- Deletes network interfaces.
- Restarts networking.
- Configures bond interface to use DHCP.
- Assigns a static IP address to the bond interface.
- Creates bond interfaces for the system.
- Creates eth interfaces for the system.
- Adds an interface to an existing bond.
- Configures servers in the domain name system (DNS).
- Updates the bonding mode or maximum transmission unit (MTU).
- Updates bonding and individual interface information.
- Resets networking to factory configuration.
- Manages local hosts.
- Manages local routes.
- Looks up the IP address or hostname for a specific destination.
- Starts a packet trace route for a specific network host.
- Pings a destination host



- Blanks LED on the specific ethernet device.
- Starts the specific ethernet devices on restart.
- Does not start the specific ethernet devices on restart.
- Performs basic troubleshooting.
- Capture network traffic.
- Runs iperf (Network Performance) in client mode.
- Runs iperf (Network Performance) in server mode.

Network Command Usage

- **network --show [options]**
- **network --delete** (*Option only available on a Physical DR*)
- **network --restart**
- **network --setdhcp [options]**
- **network --setstatic_ip [options]**
- **network --create_bond** (*Option only available on a Physical DR*)
- **network --create_eth** (*Option only available on a Physical DR*)
- **network --add_member** (*Option only available on a Physical DR*)
- **network --setdns [options]**
- **network --setbonding [options]** (*Option only available on a Physical DR*)
- **network --update** (*Option only available on a Physical DR*)
- **network --factory_reset** (*Option only available on a Physical DR*)
- **network --host** (*Option only available on a Physical DR*)
- **network --route** (*Option only available on a Physical DR*)
- **network --nslookup [options]**
- **network --traceroute [options]**
- **network --ping [options]**
- **network --blink** (*Option only available on a Physical DR*)
- **network --enable** (*Option only available on a Physical DR*)
- **network --disable** (*Option only available on a Physical DR*)
- **network --troubleshoot [options]**
- **network --tcpdump [options]**
- **network --iperf_client [options]**
- **network --iperf_server [options]**
- **network --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you are prompted to provide the correct value or option.

 **NOTE:** Most network commands require a `network --restart` command for the changes to occur.

network --show

Description

Displays the current networking configuration for a DR Series system. (Only a Physical DR has sub-options for network --show.)

Syntax

```
network --show [--bondif <bond0,bond1,...,bondN>] [--nwif <eth0,eth1,...,ethN>]
[--hosts] [--routes] [--interface <bondN|ethN>]
```



```

--bondif      Bond interface(s) to show.
--nwif        Eth interface(s) to show.
--hosts       Show local host.
--routes      Show local routes.
--interface   Routes for a specific interface.

```

Result

```

Device                  : bond0
Enabled                : yes
Link                  : yes
Boot protocol          : dhcp
IP Addr               : 10.20.24.55
Netmask               : 255.255.252.0
Gateway               : 10.20.32.13
MAC Addr              : 78:2B:CB:47:D0:08
MTU                  : 1500
Bonding options        : "mode=balance-alb miimon=100 xmit_hash_policy=2"
Slave Interfaces       :
eth0 MAC              : 78:2B:CB:47:D0:08
eth0 Max Speed        : 1000baseT/Full
eth0 Speed             : 1000Mb/s
eth0 Duplex            : Full
eth1 MAC              : 00:50:56:93:5A:02
eth1 Max Speed        : 1000baseT/Full
eth1 Speed             : 1000Mb/s
eth1 Duplex            : Full
eth2 MAC              : 00:50:56:93:5A:03
eth2 Max Speed        : 1000baseT/Full
eth2 Speed             : 1000Mb/s
eth2 Duplex            : Full
eth3 MAC              : 00:50:56:93:5A:04
eth3 Max Speed        : 1000baseT/Full
eth3 Speed             : 1000Mb/s
eth3 Duplex            : Full
DNS Suffix            : storage.local
Primary Nameserver    : 10.25.19.15
Secondary Nameserver   : 10.25.19.16

```

network --delete

Description

The command deletes a network interface.

Syntax

```

network --delete    [--bondif <bond0,bond1,...,bondN>]
                    [--member <eth0,eth1,...,ethN>]
                    [--nwif <eth0,eth1,...,ethN>]

--bondif      Bond interface(s) to delete.
--member     Bond member interface(s) to delete.
--nwif       Eth interface(s) to delete.

```

For example, to delete network interface eth2, run the command: `network --delete --nwif eth2`

Result

Interface delete successful. Please restart networking for the changes to take effect.

network --restart

Description

Restarts the current networking configuration for a DR Series system.



Syntax

```
network --restart
```

Result

```
Shutting down interface eth0: [ OK ]
Shutting down interface eth1: [ OK ]
Shutting down interface eth2: [ OK ]
Shutting down interface eth3: [ OK ]
Shutting down loopback interface: [ OK ]
Bringing up loopback interface: [ OK ]
Bringing up interface bond0:
Determining IP information for bond0... done. [ OK ]
DNS Updated hostname: acme11.storage.local
```

network --setdhcp

Description

Configures the DR Server system to use the dynamic host configuration protocol (DHCP) form of IP addressing. (The options bondif and nwif are only available on a Physical DR.)

Syntax

```
network --setdhcp [--bondif <bondN>] [--nwif <ethN>]
--bondif    Bond interface to create (dhcp).
--nwif     Eth interface to create (dhcp).
```

Result

Bond device operation successful. Please run 'network --restart' for the changes to take affect.

network --setstatic_ip [--bondif <bondN>] [--nwif <ethN>] --ip <IPv4/IPv6 address not already in use> --netmask <netmask> [--gateway <IPv4/IPv6 address>]

Description

Configures the DR Series system to use a static IP address and configures the corresponding netmask (and/or the routing gateway for a DR Series system). The options bondif and nwif are only available on a Physical DR.

Syntax

```
network --setstatic_ip --ip 10.20.20.20 --netmask 255.255.222.0 --gateway
10.25.20.10
--bondif    Bond interface to create (static).
--nwif     Eth interface to create (static).
--ip      Static IP address to use.
--netmask  Netmask for the static IP address.
--gateway  Gateway for routing ('bond0' only).
```

Result

Bond device operation successful. Please run 'network --restart' for the changes to take effect.

network --create_bond

Description

The command allows individual network interfaces to be selected to create a bond. Only non-bonded interfaces can be used to create a bond. When a bond is created, all the individual interfaces chosen for the bond lose their existing settings and their settings are managed by the bond. Interface bonding requires all the network devices in the bond to



support the same speed. Interfaces of different devices like twisted pair or fibre can be bonded as long as they support the bonding speed. Currently, only devices which support the same speed can be bonded together. You can create multiple bonds, but each bond must be created individually and the maximum number of bonds cannot exceed the number of devices.

Syntax

```
--create_bond --bondif <bondN>
    [--dhcp]
    [--static]
    --nwif <eth0,eth1,...,ethN>
    [--mode < ALB | 802.3ad>]
    [--name < DNS name >]
    [--mtu <Supported MTU range 512 - 9000>]
    [--ip <IPv4/IPv6 address not already in use>]
    [--netmask <netmask>]
    [--gateway <IPv4/IPv6 address>]
    [--restart]

--bondif      Bond interface to create.
--dhcp       Create dhcp interface.
--static      Create static interface.
--nwif       Eth interfaces to bond.
--mode        Bonding mode to use.
--name        DNS name for the interface.
--mtu         Ethernet MTU to use (valid range is 512 - 9000).
--ip          Static IP address to use.
--netmask     Netmask for the static IP address.
--gateway    Gateway for routing.
--restart    Restarts networking after creation.
```

For example, to create bond1 using eth3 and eth4, run the command: network --create_bond --bondif bond1 --dhcp --nwif eth3,eth4 --mode ALB --restart

Result

```
Shutting down interface bond0:  [  OK  ]
Shutting down interface bond1:  [  OK  ]
Shutting down loopback interface: [  OK  ]
Bringing up loopback interface: [  OK  ]
Bringing up interface bond0:Determining IP information for bond0... done.
[  OK  ]
Bringing up interface bond1:Determining IP information for bond1... done.
[  OK  ]
Updating DNS entry for SW-01.local to 10.250.xxx.x ..
Skipping DNS Update 10.250.xxx.x: IP already updated.
```

network --create_eth

Description

The command creates eth interface for the system.

Syntax

```
network --create_eth --nwif <ethN>
    [--dhcp]
    [--static]
    [--name < DNS name >]
    [--mtu <Supported MTU range 512 - 9000>]
    [--ip <IPv4/IPv6 address not already in use>]
    [--netmask <netmask>]
    [--restart]

--nwif      Eth interface to create.
--dhcp      Create dhcp interface.
```



```
--static      Create static interface.  
--name       DNS name for the interface.  
--mtu        Ethernet MTU to use (valid range is 512 - 9000).  
--ip         Static IP address to use.  
--netmask    Netmask for the static IP address.  
--restart    Restarts networking after creation.
```

For example, to create eth2, run the command: `network --create_eth --nwif eth2 --dhcp`

Result

Interface operation successful. Please restart networking for the changes to take effect.

network --add_member

Description

Add an interface to an existing bond.

Syntax

```
network --add_member --bondif <bondN>  
                  --nwif <eth0, eth1, . . . ,ethN>  
  
--bondif     Bond interface to add to.  
--nwif       Eth interfaces to add.
```

For example, to add eth2 to bond1, run the command: `network --add_member --bondif bond1 --nwif eth2`

Result

Interface add successful. Please restart networking for the changes to take effect.

network --setdns [--suffix <dns suffix>] [--primary <IPv4/IPv6 address>] [--secondary <IPv4/IPv6 address>]

Description

Configures the domain name system (DNS) for a DR Series system, which includes the corresponding DNS suffix and a primary name server IP address (and optionally, a secondary name server IP address).

Syntax

```
network --setdns --suffix storage.local --primary 10.25.20.21 --secondary  
10.25.20.25
```

network --setbonding --bondif <bondN> [--mode <ALB | 802.3ad>] [--mtu <supported MTU range 512 - 9000>]

Description

Configures or updates the bonding mode or sets the maximum transmission unit (MTU) number to use for a DR Series system.

Syntax

```
network --bondif bond1 --setbonding --mode ALB --mtu 1750
```

Result

Bond device operation successful. Please run '`network --restart`' for the changes to take effect.



-  **NOTE:** ALB load balancing does not balance the load properly when the backup servers are on a remote subnet. This is because ALB uses the address resolution protocol (ARP) and ARP updates are subnet-specific. Because of this, ARP broadcasts and updates are not sent across the router. Instead, all traffic is sent to the first interface in the bond. To resolve this ARP-specific issue, make sure that the data source systems reside on the same subnet as the DR Series system.
-  **NOTE:** When setting or changing the MTU value, make sure to verify that the Ethernet network switch is capable of supporting an MTU size that is equal to or larger than the value being set. Any mismatch in MTU values between the clients, the Ethernet network switch, and the DR Series system will make it inoperable. The relationship of jumbo frames to MTU is discussed in this topic.
-  **NOTE:** When using the DR Series system CLI --setbonding and --mtu commands, a warning dialog displays with the following message:

Incorrectly setting the MTU size will cause the DR4000 to not respond. You will need to log in to the system console and use the **network --setbonding --bondif bond0 --mtu 1500** command to resolve the issue. Please verify that the switch is enabled and capable of supporting an MTU size that is equal to or larger than the value being set. Do you want to continue (yes/no) ?

 **CAUTION:** If the existing bonding setting is changed, the connection to the DR Series system may be lost unless you are sure that the DR Series system can accept this bonding type.

In computer networking, jumbo frames are Ethernet frames with more than 1500 bytes of payload (but in some cases, jumbo frames can carry up to 9000 bytes of payload).

Many Gigabit Ethernet switches and Gigabit Ethernet network interface cards support jumbo frames. Some Fast Ethernet switches and Fast Ethernet network interface cards (NICs) also support jumbo frames.

Some computer manufacturers use 9000 bytes as the conventional limit for jumbo frame sizes. Internet Protocol (IP) subnetworks require that all hosts in a subnet have an identical MTU.

Consequently, interfaces that use a standard frame size and those that use a jumbo frame size should not be in the same subnet. To reduce the chance of interoperability issues, NICs capable of jumbo frames require special configurations to use jumbo frames. For more information, contact your Technical Support representative for assistance.

To verify that the destination system can support a specific frame size you want to attempt, use the following DR Series system CLI commands and specify the frame size in bytes using the following command as an example:

```
network --ping --destination <ip address> --size <number of bytes>
```

network --update

Description

The command updates bonding and individual interface information.

Syntax

```
network --update [--bondif <bondN>]
                [--nwif <ethN>]
                [--mode < ALB | 802.3ad>]
                [--name < DNS name >]
                [--mtu <Supported MTU range 512 - 9000>]

--bondif      Bond interface to update.
--nwif        Eth interface to update.
--mode        Bonding mode to use.
--name        DNS name for the interface.
--mtu         Ethernet MTU to use (valid range is 512 - 9000).
```

For example, to update bond1 to use a different MTU parameter, run the command: `network --update --bondif bond1 --mtu 5000`



Result

WARNING: Incorrectly setting the MTU size will cause the DR appliance to not respond.

Please verify that the switch is enabled and capable of supporting an MTU size that is equal to or larger than the value being set.

Do you want to continue (yes/no) [n] ? y

Interface update successful.

network --factory_reset

Description

The command resets bond0 Slave Interfaces according to the option of auto_bonding_speed.

Syntax

```
network --factory_reset [--auto_bonding_speed <1G|10G>]
    --auto_bonding_speed      The speed of the device (1G or 10G)
                                to bond on restart.
```

Result

WARNING: This will reset network configuration to factory settings and will require a system reboot. Existing configuration will be lost.

Do you want to continue (yes/no) [n]?yes

Reboot the system using the command 'system --reboot' to complete the network factory reset.

network --host

Description

The command manages local hosts.

Syntax

```
network --host [--add] [--ip <IPv4/IPv6 address>] [--name <host name>]
    [--delete] [--ip <IPv4/IPv6 address>] [--name <host name>]
    --add      Add local host.
    --delete   Delete local host.
    --ip       Host IP address to manage.
    --name     Host name (FQDN or alias) to manage.
```

network --route

Description

The command helps to manage local routes.

Syntax

```
network --route [--add] [--network <destination networks>] [--netmask
    <netmask>] [--gateway <gateway addresses>] [--interface <bondN|ethN|lo>]
    [--delete] [--network <destination networks>] [--netmask <netmask>] [--gateway
    <gateway addresses>] [--interface <bondN|ethN|lo>]
    --add      Add local route.
    --delete   Delete local route.
    --network  Destination network.
    --netmask  Destination network mask.
```



```
--gateway      Gateway to destination network.  
--interface   Interface to route through.
```

Result

network --nslookup --destination <ip address | hostname>

Description

Performs a domain name system (DNS) lookup for a DR Series system.

Syntax

```
network --nslookup --destination 10.25.20.15
```

Result

```
10.25.20.15 has name sys-59.storage.local.
```

network --traceroute --destination <ip address | hostname>

Description

Performs a trace route for packets that were sent to a DR Series system.

Syntax

```
network --traceroute --destination 10.25.20.20
```

Result

```
traceroute to 10.15.10.21 (10.15.10.21), 30 hops max, 40 byte packets  
 1  10.25.24.1 (10.25.24.1)  0.510 ms  0.654 ms  0.673 ms  
 2  10.20.12.16 (10.20.12.16)  7.095 ms  7.564 ms  7.843 ms  
 3  10.16.16.2 (10.16.16.2)  1.092 ms  1.097 ms  1.130 ms  
 4  10.16.0.9 (10.16.0.9)  1.006 ms  0.980 ms  1.017 ms  
 5  10.18.14.97  6.864 ms  5.703 ms  6.264 ms  
 6  10.13.19.5)  7.230 ms  7.230 ms  7.260 ms  
 7  10.16.19.6)  8.540 ms  8.624 ms  8.848 ms  
 8  10.15.15.11 (10.15.15.11)  8.772 ms  9.032 ms  8.859 ms  
 9  10.18.15.18 (10.158.15.18)  10.540 ms  10.674 ms  10.285 ms  
10  10.15.0.21 (10.15.0.21)  9.153 ms  9.051 ms  9.216 ms
```

network --ping --destination <ip address | hostname> [--tries <number>] [--size <number>] [--interface <bondN | ethN>]

Description

Pings any target DR Series system by sending five **ICMP ECHO_REQUEST** packets to the specified destination to verify that it can be reached. The interface option is only available on a Physical DR.

Syntax

```
network --ping --destination 10.25.19.5
```

Result

```
PING 10.25.19.5 (10.25.19.5) from 10.20.14.15 bond0: 56(84) bytes of data.
```

```
64 bytes from 10.25.19.5: icmp_seq=1 ttl=64 time=0.039 ms  
64 bytes from 10.25.19.5: icmp_seq=2 ttl=64 time=0.049 ms  
64 bytes from 10.25.19.5: icmp_seq=3 ttl=64 time=0.041 ms  
64 bytes from 10.25.19.5: icmp_seq=4 ttl=64 time=0.041 ms  
64 bytes from 10.25.19.5: icmp_seq=5 ttl=64 time=0.049 ms
```

```
--- 10.25.19.5 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 3999ms  
rtt min/avg/max/mdev = 0.039/0.043/0.049/0.009 ms
```



Other Command Options

--tries

Specify the number of ping attempts by entering a value using the DR Series system CLI **--tries** command option.

Example

```
network --ping --destination 10.25.19.5 --tries 3

PING 10.25.19.5 (10.25.19.5) from 10.20.14.15 bond0: 56(84) bytes of data.

64 bytes from 10.25.19.5: icmp_seq=1 ttl=64 time=0.032 ms
64 bytes from 10.25.19.5: icmp_seq=2 ttl=64 time=0.049 ms
64 bytes from 10.25.19.5: icmp_seq=3 ttl=64 time=0.047 ms

--- 10.25.19.5 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 5999ms
rtt min/avg/max/mdev = 0.032/0.043/0.049/0.005 ms
```

--size

Specify a desired ping packet size by entering a value using the DR Series system CLI **--size** command option.

Example

```
network --ping --destination system-69 --size 35

PING 10.20.19.20 (10.20.19.20) from myDR4000 bond0: 35(63) bytes of data.

43 bytes from 10.20.19.20: icmp_seq=1 ttl=64 time=0.129 ms
43 bytes from 10.20.19.20: icmp_seq=2 ttl=64 time=0.163 ms
43 bytes from 10.20.19.20: icmp_seq=3 ttl=64 time=0.166 ms
43 bytes from 10.20.19.20: icmp_seq=4 ttl=64 time=0.237 ms
43 bytes from 10.20.19.20: icmp_seq=5 ttl=64 time=0.179 ms

--- 10.20.19.20.acme.local ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4000ms
rtt min/avg/max/mdev = 0.129/0.174/0.237/0.038 ms
```

--interface

Specify an interface address to use as the source address by entering a value using the DR Series system CLI **--interface** command option.

Example

```
network --ping --destination system-69 --interface bond0
```

network --blink

Description

The command blinks the LED on the specific ethernet device.

Syntax

```
network --blink --nwif <ethN> --time <N>

--nwif    Eth interface to blink.
--time   Blink duration time in seconds (default 10, max 300).
```

For example, to blink the LED for eth3, run the command: `network --blink --nwif eth3 --time 30`

Result

Check the LED on the ethernet card on the back of the system for identification.



network --enable

Description

The command starts the specific ethernet device(s) on restart.

Syntax

```
network --enable [--bondif <bond0,bond1,...,bondN>]
                  [--nwif <eth0,eth1,...,ethN>]

                  --bondif    Bond interface(s) to delete.
                  --nwif     Eth interface(s) to dele
```

For example, to enable eth2, run the command: `network --enable --nwif eth2`

Result

Interface device operation successful. Please restart networking for the changes to take effect.

network --disable

Description

The command does not start the specific ethernet device(s) on restart.

Syntax

```
network --disable [--bondif <bond0,bond1,...,bondN>]
                  [--nwif <eth0,eth1,...,ethN>]

                  --bondif    Bond interface(s) to delete.
                  --nwif     Eth interface(s) to dele
```



NOTE: You cannot disable eth interfaces which are part of a bond.

For example, to disable eth2, run the command: `network --disable --nwif eth2`

Result

Interface device operation successful. Please restart networking for the changes to take effect.

network --troubleshoot [--links] [--gateway] [--ntp] [--dns] [--active_domain] [--nis] [--clients] [--port_mapper] [--network_config] [--show_active <NFS|CIFS|OST|RDS|NDMP|ISCSI|FC>] [--interface <bondN | ethN>]

Isolates a variety of networking issues that you might encounter while running a DR Series system. When you can isolate a problem or issue to a specific cause, you can better understand and resolve it. The DR Series system CLI `network --troubleshoot` command and its options allow you to perform basic troubleshooting checks on the state of a DR Series system.

Description

A small icon of a notepad with a pencil, indicating a note or important information.

NOTE: When entering the `network --troubleshoot` command string, the DR Series system checks and displays the current state for all of the --troubleshoot options. To limit the type of network troubleshooting check you want to display, define the command string to a specified check (or checks). For example, using `network --troubleshoot --gateway`, displays the status of the gateway for a DR Series system (for details, see [network --troubleshoot --gateway](#)).



Syntax

```
network --troubleshoot
```

Result

```
*** Checking link status for each interface
bond0 : Link detected: yes
eth0 : Link detected: yes
eth1 : Link detected: yes
eth2 : Link detected: yes
eth3 : Link detected: yes
lo : Link detected: yes

*** Getting local IP addresses
bond0 addr:10.25.20.23 Mask:255.255.245.0

*** Getting bond information
Ethernet Channel Bonding Driver: v3.4.0 (October 7, 2008)

Bonding Mode: transmit load balancing
Primary Slave: None
Currently Active Slave: eth0
MII Status: up
MII Polling Interval (ms): 100
Up Delay (ms): 0
Down Delay (ms): 0

Slave Interface: eth0
MII Status: up
Link Failure Count: 0
Permanent HW addr: 00:50:56:93:59:7a

Slave Interface: eth1
MII Status: up
Link Failure Count: 0
Permanent HW addr: 00:50:56:93:59:7b

Slave Interface: eth2
MII Status: up
Link Failure Count: 0
Permanent HW addr: 00:50:56:93:59:7c

Slave Interface: eth3
MII Status: up
Link Failure Count: 0
Permanent HW addr: 00:50:56:93:59:7d

*** Getting Gateway status
Gateway IP address is 10.25.20.1
Route to the gateway is up and uses bond0 interface.
Pinging gateway 10.25.20.1
Ping successful. No packet loss.
RTT timings min/avg/max/mdev = 0.332/1.612/3.742/1.274 ms

*** Checking NTP configuration
Network time is enabled.
System is configured with following NTP servers:
0.centos.pool.ntp.org
1.centos.pool.ntp.org
2.centos.pool.ntp.org

Checking if NTP servers are reachable...
Pinging 0.centos.pool.ntp.org
Ping successful. No packet loss.
RTT timings min/avg/max/mdev = 75.696/76.042/76.541/0.506 ms
Pinging 1.centos.pool.ntp.org
```



```

Ping successful. No packet loss.
RTT timings min/avg/max/mdev = 49.150/50.098/52.292/1.212 ms
Pinging 2.centos.pool.ntp.org
Ping successful. No packet loss.
RTT timings min/avg/max/mdev = 77.854/77.999/78.075/0.085 ms

*** Checking DNS configuration
DNS Suffix: storage.local
Primary Nameserver: 10.25.19.5
Secondary Nameserver: 10.25.19.6
Pinging 10.25.19.5
Ping successful. No packet loss.
RTT timings min/avg/max/mdev = 0.253/0.451/1.123/0.336 ms
Pinging 10.25.19.6
Ping successful. No packet loss.
RTT timings min/avg/max/mdev = 0.239/0.537/1.149/0.326 ms

*** Checking Active Directory configuration
AD configuration: This node has not joined any domain.

*** Checking NIS configuration
NIS domain configuration not found.

*** Checking NFS and CIFS clients configured for various containers
NFS/CIFS clients configured for containers:
-no specific clients-
*** Checking if there is another host with same name
Local system name: acme-01.storage.local
Local system IP: 10.25.20.23
Pinging acme-01.storage.local 3 times
Got IP address as 10.25.20.23
Got IP address as 10.25.20.23
Got IP address as 10.25.20.23
No duplicate hostname found on the network.

*** Checking portmapper
portmap (pid 3716) is running
Checking ports currently being used by portmapper
  program vers proto   port
  100000    2   tcp     111  portmapper
  100000    2   udp     111  portmapper

```

network --troubleshoot --gateway --interface <bondN | ethN>

Description

Performs a basic troubleshooting on the current state of the gateway connected to the DR Series system.

Syntax

```
network --troubleshoot --gateway --interface bond0
```

Result

```

*** Getting Gateway status
Gateway IP address is 10.250.240.1
Route to the gateway is up and uses bond0 interface.

```

```

Pinging gateway 10.250.240.1
Ping successful. No packet loss.
RTT timings min/avg/max/mdev = 0.261/1.907/5.244/1.830 ms

```



network --troubleshoot [--show_active <NFS| CIFS|OST|NDMP|iSCSI|RDS>]

Description

Displays the current network activity for NFS, CIFS, OST, NDMP, iSCSI, or RDS clients on a DR Series system (the example that follows shows CIFS).

Syntax

```
network --troubleshoot --show_active cifs
```

Result

```
tcp      0      0      10.25.19.10:45      10.25.20.82:52596  
ESTABLISHED  
tcp      0      0      10.25.19.10:45      10.250.201.68:60163      ESTABLISHED  
tcp      0      0      10.25.19.10:45      10.250.208.235:29587      ESTABLISHED  
tcp      0      0      10.25.19.10:45      10.250.209.210:13828      ESTABLISHED
```

network --tcpdump [--port <nfs | windows | replication | ost | rds>] [--pkt_size <128 - 32768>] [--file_size <0 - 100>] [--stop] [--host <ip address list>] [--interface <bondN | ethN>]

Intercepts TCP/IP packets being transmitted or received over the network to which the DR Series system is attached. You can filter the packets being collected by using the following options to the DR Series system CLI **network --tcpdump** command:

- **--port** by its type: NFS, CIFS, replication, OST, or RDS port
- **--pkt_size** by the packet size you specify
- **--file_size** by the file size you specify
- **--host** by the IP address (or addresses) that you specify
- **--interface** by the interface that you specify

The tcpdump files are collected on the DR Series system (in /store/tcpdump/), and they can be a valuable resource of information about how your system and network interact. To stop collecting tcpdump files, use the DR Series system CLI **network --tcpdump --stop** command.

network --tcpdump [--pkt_size <128 - 32768>]

Description

Collects TCP/IP packet information based on a specific packet size (for example, 256 Kilobytes or KB).

 **NOTE:** To stop the tcpdump process, use the DR Series system CLI **network --tcpdump --stop** command.

Syntax

```
network --tcpdump --pkt_size 256
```

Result

Successfully started tcpdump, please use "network --tcpdump --stop" to stop.

For more information, see [network --tcpdump \[--port <nfs | windows | replication | ost | rds>\] \[--pkt_size <128 - 32768>\] \[--file_size <0 - 100>\] \[--stop\] \[--host <ip address list>\]](#).

network --tcpdump [--file_size <0 - 100>]

Description

Collects TCP/IP packet information based on a specific file size that you can configure (such as 3 Megabytes or MB).



 **NOTE:** To stop the tcpdump process, use the DR Series system CLI network --tcpdump --stop command.

Syntax

```
network --tcpdump --file_size 3
```

Result

Successfully started tcpdump, please use "network --tcpdump --stop" to stop.

For more information, see [network --tcpdump \[--port <nfs | windows | replication | ost>\] \[--pkt_size <128 - 32768>\] \[--file_size <0 - 100>\] \[-stop\] \[--host <ip address list>\]](#)

network --tcpdump [--host <ip address list>]

Description

Collects TCP/IP packet information based on a specific host IP address (for example, 10.10.11.12).

 **NOTE:** To stop the tcpdump process, use the DR Series system CLI network --tcpdump --stop command.

Syntax

```
network --tcpdump --host 10.10.11.12
```

Result

Successfully started tcpdump, please use "network --tcpdump --stop" to stop.

 **NOTE:** You can also specify a number of host IP addresses using this command in a comma-delimited format (--host 10.10.11.12,10.12.12.13,10.10.12.14).

network --tcpdump [--port <nfs | windows | replication | ost | rds>]

Description

Filters TCP/IP packet information based on a specific port type. In this example, by specifying an OpenStorage Technology (OST) port type using the DR Series system CLI **network --tcpdump --port ost** command.

Syntax

```
network --tcpdump --port ost
```

Result

Successfully started tcpdump, please use "network --tcpdump --stop" to stop.

For more information, see [network --tcpdump \[--port <nfs | windows | replication | ost | rds>\] \[--pkt_size <128 - 32768>\] \[--file_size <0 - 100>\] \[-stop\] \[--host <ip address list>\]](#)

network --iperf_client --server <ip address | hostname> [--port <number>] [--window_size <num bytes [KB/MB]>] [--interval <num seconds>] [--time <num seconds>]

The DR Series system provides the **--iperf** set of DR Series system CLI commands (**--iperf_client** and **--iperf_server**) that let you test network performance between any client and server on the network that you designate. In addition to testing the network performance between these two designated endpoints, this set of **--iperf** commands also let you test if the firewall allows a connection between these two points. You can filter the network performance test by using the following options:

- **--server**, by the IP address or host name that you specify
- **--port**, by the port number that you specify
- **--window_size**, by the number of bytes, Kilobytes or Megabytes (KB/MB), that you specify
- **--interval**, by the number of seconds that you specify



- **--time**, by the number of seconds that you specify

 **NOTE:** There are two conditions you must meet: 1) you must use ports with the **--iperf_client** and **--iperf_server** commands that are not in use by any other system operations (if you do not define specific ports, the **--iperf_client** and **--iperf_server** commands default to port 5001), and 2) these commands must be issued simultaneously.

Description

Tests network performance between a client and server using a designated port (use this command at the same time you use the other **--iperf** command).

```
network --iperf_client --server acme-sw-02 --port 5001 --window_size 7KB --
interval 30 --time 60
```

Result

```
-----
Client connecting to acme-sw-02, TCP port 5001
TCP window size: 14.0 KByte (WARNING: requested 7.00 KByte)
-----
[ 6] local 10.20.21.23 port 5812 connected with 10.20.20.3 port 5001
[ ID] Interval Transfer Bandwidth
[ 6] 0.0-30.0 sec 193 MBytes 54.0 Mbits/sec
[ 6] 30.0-60.0 sec 205 MBytes 57.4 Mbits/sec
[ 6] 0.0-60.0 sec 398 MBytes 55.7 Mbits/sec
```

network --iperf_server [-port <number>] [--window_size <num bytes [KB/MB]>]

The DR Series system provides the **--iperf** set of DR Series system CLI commands (**--iperf_client** and **--iperf_server**) that let you test network performance between any client and server on the network that you designate. In addition to testing the network performance between these two designated endpoints, this set of **--iperf** commands also let you test if the firewall allows a connection between these two points. You can filter the network performance test by using the following options:

- **--port**, by the port number that you specify
- **--window_size**, by the number of bytes, Kilobytes (KB) or Megabytes (MB) that you specify

 **NOTE:** There are two conditions you must meet: 1) you must use ports with the **--iperf_client** and **--iperf_server** commands that are not in use by any other system operations (if you do not define specific ports, the **--iperf_client** and **--iperf_server** commands default to port 5001), and 2) these commands must be issued simultaneously.

Description

Tests network performance between a client and server using a designated port (use this command at the same time you use the other **--iperf** command).

Syntax

```
network --iperf_server --port 5001 --window_size 7KB
```

Result

```
-----
Server listening on TCP port 5001
TCP window size: 14.0 KByte (WARNING: requested 7.00 KByte)
-----
[ 7] local 10.20.21.23 port 5812 connected with 10.20.20.3 port 5001
[ ID] Interval Transfer Bandwidth
[ 7] 0.0-60.0 sec 398 MBytes 55.7 Mbits/sec
```

network --help

Description

Displays the list of network-related options that can be used as a reference when using the DR Series system CLI.



Syntax

```
network --help
```

Result

```
network --show [--bondif <bond0,bond1,...,bondN>]
               [--nwif <eth0,eth1,...,ethN>]
               [--hosts]
               [--routes]
               [--interface <bondN|ethN>]

network --delete [--bondif <bond0,bond1,...,bondN>]
                 [--member <eth0,eth1,...,ethN>]
                 [--nwif <eth0,eth1,...,ethN>]

network --restart

network --setdhcp [--bondif <bondN>]
                  [--nwif <ethN>]

network --setstatic_ip [--bondif <bondN>]
                      [--nwif <ethN>]
                      --ip <IPv4/IPv6 address>
                      --netmask <netmask>
                      [--gateway <IPv4/IPv6 address>]

network --create_bond --bondif <bondN>
                [--dhcp]
                [--static]
                --nwif <eth0,eth1,...,ethN>
                [--mode < ALB | 802.3ad >]
                [--name < DNS name >]
                [--mtu <Supported MTU range 512 - 9000>]
                [--ip <IPv4/IPv6 address>]
                [--netmask <netmask>]
                [--gateway <IPv4/IPv6 address>]
                [--restart]

network --create_eth --nwif <ethN>
                [--dhcp]
                [--static]
                [--name < DNS name >]
                [--mtu <Supported MTU range 512 - 9000>]
                [--ip <IPv4/IPv6 address>]
                [--netmask <netmask>]
                [--restart]

network --add_member --bondif <bondN>
                 --nwif <eth0,eth1,...,ethN>

network --setdns [--suffix <dns suffix>]
                  [--primary <IPv4/IPv6 address>]
                  [--secondary <IPv4/IPv6 address>]

network --setbonding [--bondif <bondN>]
                     [--mode < ALB | 802.3ad >]
                     [--mtu <Supported MTU range 512 - 9000>]

network --update [--bondif <bondN>]
                 [--nwif <ethN>]
                 [--mode < ALB | 802.3ad >]
                 [--name < DNS name >]
                 [--mtu <Supported MTU range 512 - 9000>]

network --factory_reset [--auto_bonding_speed <1G|10G>]
```



```

network --host [--add] [--ip <IPv4/IPv6 address>] [--name <host name>]
              [--delete] [--ip <IPv4/IPv6 address>] [--name <host name>]

network --route [--add] [--network <destination networks>] [--netmask
<netmask>] [--gateway <gateway addresses>] [--interface <bondN|ethN>]
              [--delete] [--network <destination networks>] [--netmask
<netmask>] [--gateway <gateway addresses>] [--interface <bondN|ethN>]

network --nslookup --destination <ip address | hostname>

network --traceroute --destination <ip address | hostname>
              [--interface <bondN|ethN>]

network --ping --destination <ip address | hostname>
              [--tries <number>]
              [--size <number>]
              [--interface <bondN|ethN>]

network --blink --nwif <ethN>

network --enable [--bondif <bond0,bond1,...,bondN>]
                [--nwif <eth0,eth1,...,ethN>]

network --disable [--bondif <bond0,bond1,...,bondN>]
                [--nwif <eth0,eth1,...,ethN>]

network --troubleshoot [--links]
              [--gateway]
              [--ntp]
              [--dns]
              [--active_domain]
              [--nis]
              [--clients]
              [--port_mapper]
              [--network_config]
              [--show_active <NFS|CIFS|OST|RDS|NDMP|ISCSI|FC>]
              [--interface <bondN|ethN>]

network --tcpdump [--port <NFS|Windows|Replication|OST|RDA>]
                [--pkt_size <128 - 32768>]
                [--file_size <0 - 100>]
                [--stop]
                [--host <ip address list>]
                [--interface <bondN|ethN>]

network --iperf_client --server <ip address | hostname>
              [--port <number>]
              [--window_size <num bytes [KB/MB]>]
              [--interval <num seconds>]
              [--time <num seconds>]

network --iperf_server [--port <number>]
              [--window_size <num bytes [KB/MB]>]

network --help

network <command> <command-arguments>
<command> can be one of:
    --show           Display network settings.
    --delete         Delete network interfaces(s).
    --restart        Restarts networking.
    --setdhcp        Configures bond interface to use DHCP.
    --setstatic_ip   Assigns a static IP address to the bond
interface.
    --create_bond   Create bond interfaces for the machine.
    --create_eth    Create eth interfaces for the machine.
    --add_member    Add an interface to an existing bond.

```



```

--setdns          Configures the Domain Name Servers.
--setbonding      Updates bonding mode or MTU information.
--update          Updates bonding and individual interface
information.

--factory_reset   Reset networking to factory configuration.
--host            Manage local hosts.
--route           Manage local routes.
--nslookup        Looks up the IP address/hostname.
--traceroute     Displays the packets route to network host.
--ping            Sends ICMP ECHO_REQUEST to destination host.
--blink           Blink LED on the specific ethernet device.
--enable          Start the specific ethernet device(s) on
restart.

--disable         Don't start the specific ethernet device(s)
on restart.

--troubleshoot    Troubleshoots network issues.
--tcpdump          Capture network traffic.
--iperf_client    Run iperf (Network Performance) in client
mode.

--iperf_server    Run iperf (Network Performance) in server
mode.

For command-specific help, please type network --help <command>
eg:
    network --help show

```

OST

This topic introduces the set of OpenStorage Technology-related DR Series system CLI commands that enable you to perform the following tasks:

- Display command-specific information
- Delete the OST client
- Update the attributes of the OST client
- Limit the bandwidth consumed by OST
- List or clean up partial images

OST Command Usage

This topic introduces the **ost** command usage:

- **ost --show [options]**
- **ost --update --opdup_encryption [options]**
- **ost --delete_client [options]**
- **ost --update_client [options]**
- **ost --limit --speed --target [options]**
- **ost --partial_images --containerid [options]**
- **ost --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.



ost --show [--config] [--file_history] [--name <name>] [--active_files] [--name <name>] [--clients] [--limits]

Description

Displays the current OpenStorage Technology (OST) configuration information for a DR Series system. Parameter are described as follows:

- config — Displays OST configuration.
- file_history — Display(s) history of last 10 OST optimized duplication image file(s).
- name — OST container name.
- active_files — Display(s) current OST image files being replicated.
- name — OST container name.
- clients — Displays OST clients.
- limits — Replication speed limits.

Syntax

ost --show

Result

```
OST Login Entry User      : backup_user
OST OPDUP Encryption     : Not Enabled
```

 **NOTE:** To display other types of OST configuration information, substitute the --file_history, --name <name>, or --clients options in the DR Series system CLI command.

Other Examples

Display the last 10 replicated files that were processed via the DMA optimized duplication process for an OST container (in this example, the container is "ost.") by running the following:

```
ost --show --file_history --name ost
Data replication history:
File          Peer IP      Peer ID      Savings      Bytes
Throughput    Replicated At:   Encryption
/1481068800/w1 10.250.240.232 10       100.00%    107374182400Bytes
1075139KiB/s  2016-12-07 07:58:19  None
```

Display the OST clients, by running the command: **ost --show --clients**

```
OST Client(s)  IP Address      Type      Plugin
OS           Backup Software
Connection(s) Mode
sekhar-w12-h58 10.250.213.14  OST      4.0.273.0  Windows Server 2012 64-
bit NetBackup 7.702.16        --          0          Dedupe
```

 **NOTE:** The displayed output when using the DR Series system CLI ost --show --clients command could indicate a fourth type of mode value. Depending upon the client, this value would normally display Auto, Dedupe, or Passthrough. However, you could potentially display a mode value of Mixed, which indicates that you had changed the mode using the DR Series system CLI while the client is still connected.

 **NOTE:** Be aware that the mode for clients that were connected to the OST media server before configuration changes might be different than what is shown in the displayed output when using the DR Series system CLI ost --show --clients command. The configuration changes will be updated and reflect any future connections.

To verify the current state of an OST client, you can check these two sources:

- DR Series system CLI, using the **ost --show --clients** command
- DR Series system GUI, displaying the **Clients** page



These sources display information about the connected and configured clients. For example, when a system is connected to multiple times, these sources show the number of connections to that client and the mode. You can also change the mode from dedupe to the other supported modes. When this is done the displayed mode will change, but any active connections will remain. There are essentially two possible modes: **Dedupe** and **Passthrough**. To verify the current mode of an OST client, you can check these two sources of client statistics:

- DR Series system CLI, using the **stats --container --name** command
- DR Series system GUI, displaying the **Container Statistics** page

In the **Container Statistics** page, click the **Client Statistics** tab (under Connection Type: OST) to display the Client Statistics table. If the Network Savings level in this table displays some savings and the displayed Bytes Ingested value is different from the displayed Bytes Transferred, this indicates that the OST clients are working in the **Dedupe** mode. If not, this indicates that the OST containers are working in the **Passthrough** mode.

ost --update --opdup_encryption <none | aes128 | aes256>

Description

Sets the type of encryption that will be used by OST initiated opdup replication.

Syntax

```
ost --update --opdup_encryption aes128
```

Result

```
OST OPDUP encryption updated to aes128
```

ost --delete_client --name <OST Client Hostname>

Description

The command deletes the OST client and any edits that have been made to its default values. The next time a connection is established between the client and the DR Series system, the default OST connection settings will be used. Deleting an OST client using this CLI command does not affect data already written to the DR Series system.

Syntax

```
ost --delete_client --name acme-99
```

Result

```
Successfully deleted OST client acme-99.
```

ost --update_client --name <OST Client Hostname> --mode <auto | passthrough | dedupe>

Description

Updates the attributes of an OST client (OST client name and mode). The OST client modes are **auto**, **passthrough**, and **dedupe**. If an OST client has four or more CPU cores, it is considered to be dedupe-capable. However, the OST client operating mode depends upon how it is configured in the DR Series system.

- **Auto** — Sets the mode to **dedupe** or **passthrough** as determined by the media server. The mode used is based on how many cores the OST client has and whether it is 32-bit or 64-bit. If the OST client has four or more CPU cores, it will run in the **dedupe** mode. If the OST client has less than four CPU cores, it will run in **passthrough** mode. For details, see the table below.
- **Passthrough** — The OST client passes all data to the DR Series system for dedupe processing. This is also known as “appliance-side dedupe”.
- **Dedupe** — The OST client processes hashing on the data. This is also known as “source-side dedupe” and is the default mode. Keep in mind that the OST client must be dedupe-capable (four or more CPU cores) in order for this mode to be in effect. If the OST client is not dedupe-capable, it will run in **passthrough** mode regardless of its **dedupe** mode setting.



The following table shows the relationship between the configured OST client mode types and the supported client mode based on client architecture type and corresponding number of CPU cores.

Table 2. Supported OST Client Modes and Settings

OST Client Mode Settings	32-Bit OST Client (4 or more CPU Cores)	64-Bit Client (4 or more CPU Cores)	32-Bit OST Client (Less than 4 CPU Cores)	64-Bit OST Client (Less than 4 CPU Cores)
Auto	Passthrough	Dedupe	Passthrough	Passthrough
Dedupe	Not Supported	Supported	Not Supported	Not Supported
Passthrough	Supported	Supported	Supported	Supported

Syntax

```
ost --update_client --name acme-81 --mode dedupe
```

 **NOTE:** You may be able to force writes for OST clients running in the Passthrough mode using the DR Series system CLI mode --dedupe command. The change in OST client mode is effective on the next backup operation when you are using Veritas NetBackup. (If you are using Veritas Backup Exec, you will need to restart this service for it to recognize that a new mode has been configured.)

Result

```
OST client updated successfully.
```

```
ost --limit --speed <>num><KBps | MBps | GBps | default> --target <ip address | hostname>
```

Description

Limits the bandwidth consumed by OST (OpenStorage Technology) for a system you define by IP address or hostname (**--target**), by which you define the speed in kilobytes/second (KBps), megabytes/second (MBps), gigabytes/second (GBps), or an unlimited bandwidth (default).

Syntax

```
ost --limit --speed 10mbps --target acmesys-49
```

Result

```
Successfully updated bandwidth limit for acmesys-49 to 10 MBps.  
Changing traffic control policies ... done.
```

```
ost --partial_images --containerid <Container id> [--delete <Partial image path>] [--timeout <>0>]
```

Description

Lists or cleans up partial images.

- Container id — ID of container.
- Partial image path — OST partial image path to delete.
- Timeout — Maximum timeout (in seconds) to list partial images.

Syntax

```
ost --partial_images --containerid 6
```

Results

```
Image Name: K12  
Image Date: 1481535029  
Image Policy: DPA  
Image Path: /1481500800/K12
```



```
Image Size: 251821817856
Image Status: 0
```

ost --help

Description

Displays the list of OpenStorage Technology (OST) ost-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
ost --help
```

Result

Usage:

```
    ost --show [--config]
                [--file_history] [--name <name>]
                [--active_files] [--name <name>]
                [--clients]
                [--limits]

    ost --update --opdup_encryption <none | aes128 | aes256>

    ost --delete_client --name <OST Client Hostname>

    ost --update_client --name <OST Client Hostname>
                    --mode <auto|passthrough|dedupe>

    ost --limit --speed <>num> <KBps|MBps|GBps> | default>
                    --target <ip address | hostname>

    ost --partial_images --containerid <Container id>
                    [--delete <Partial image path>]
                    [--timeout <> 0>]

    ost --help

ost <command> <command-arguments>
<command> can be one of:
    --show           Displays command specific information.
    --update          Updates the OST settings.
    --delete_client   Deletes the OST client.
    --update_client    Updates attributes of the OST client.
    --limit            Limits bandwidth consumed by OST when
replicating over a WAN link.
    --partial_images  List or cleanup partial images.
```

RDA

The set of RDA commands have the following functions:

- Displays command specific information.
- Deletes the Rapid Data Access (RDA) client.
- Updates attributes of a Rapid Data Access (RDA) client.
- Limits bandwidth consumed by Rapid Data Access (RDA) when replicating over a WAN link.
- Lists or cleans up partial images.

RDA Command Usage

The following commands are run for RDA:



- **rda --show**
- **rda --update**
- **rda --delete_client rda --update_client**
- **rda --limit**
- **rda --partial_images --containerid [options]**

rda --show [--config] [--file_history] [--name <name>] [--active_files] [--name <name>] [--clients] [--limits]

Description

The command displays the RDA-specific configurations.

Syntax

```
rda --show      [--config]
                  [--file_history]  [--name <name>]
                  [--active_files]  [--name <name>]
                  [--clients]
                  [--limits]

--config        Displays RDA configuration.
--file_history  Display(s) history of last 10 RDA optimized
                 deduplication image file(s).
--name          RDA container name.
--active_files  Display(s) current active RDA image files being
                 replicated.
--name          RDA container name.
--clients       Displays RDA clients.
--limits        Replication speed limits.
```

For example, to show the RDA clients, run the command: `rda --show --clients`

Results

RDA Client(s)	Type	Plugin	OS	Backup Software	Last Access	Connecti on(s)	Mode
BabuK-W2K8-02	RDS	2.1.17 7	Windows Server 2008 R2	NetVault Backup	Jul 18 05:42:53	1	Passthrough

 **NOTE:** The displayed output when using the `rda --show --clients` command indicates a fourth type of mode value. Depending upon the client, this value equals Auto, Dedupe, Passthrough, or Mixed. Mixed indicates that you changed the mode while the client is still connected.

 **NOTE:** The mode for clients that are connected to the RDA media server before configuration changes might be different than what is displayed when using the `rda --show --clients` command. The configuration changes are updated to reflect any future connections.

To verify the current state of an RDA client, you can check the two sources:

- DR Series system CLI, using the `rda --show --clients` command
- DR Series system GUI, displaying the **Clients** page

These sources display information about the connected and configured clients. When a system is connected multiple times, these sources show the number of connections to that client and the mode. You can also change the mode from



dedupe to the other supported modes. When this is done the displayed mode changes, but any active connections remains. There are essentially two possible modes: **Dedupe** and **Passthrough**. To verify the current mode of an RDA client, you can check the two sources of client statistics:

- DR Series system CLI, using the `stats --container --name` command
- DR Series system GUI, displaying the **Container Statistics** page

In the **Container Statistics** page, click the **Client Statistics** tab (under Connection Type: RDS) to display the **Client Statistics** table. If the **Network Savings** level in this table displays some savings and the displayed **Bytes Ingested** value is different from the displayed **Bytes Transferred**, it indicates that the RDA clients are working in the **Dedupe** mode. If not, it indicates that the RDA containers are working in the **Passthrough** mode.

rda --update --opdup_encryption <none | aes128 | aes256>

Description

Sets the type of encryption that will be used by RDA initiated opdup replication.

Syntax

```
rda --update --opdup_encryption aes128
```

Result

```
RDS OPDUP encryption updated to aes128
```

rda --delete_client --name <RDA Client Hostname>

Description

The command deletes the Rapid Data Access (RDA) client and any edits that were made to its default values. The next time a connection is established between the client and the DR Series system, the default RDA connection settings will be used. Deleting an RDA client using this CLI command does not affect data already written to the DR Series system.

Syntax

```
rda --delete_client --name <RDA Client Hostname>
      --name   Host name
```

For example, to delete the client TEST-W2K8-02, run the command: `rda --delete_client --name TEST-W2K8-02`

Result

```
Rapid Data Access (RDA) client TEST-W2K8-02 deleted successfully.
```

rda --update_client --name <RDA Client Hostname> --mode <auto|passthrough| dedupe>

Description

The command updates the attributes of a Rapid Data Access (RDA) client. The RDA client modes are **auto**, **passthrough**, and **dedupe**. If a RDA client has four or more CPU cores, it is considered to be dedupe-capable. However, the RDA client operating mode depends upon how it is configured in the DR Series system. For details, see [ost --update_client --name <OST Client Hostname> --mode <auto|passthrough|dedupe>](#).

Syntax

```
rda --update_client --name <RDA Client Hostname> --mode <auto|passthrough| dedupe>
      --name   Hostname of client
      --mode   RDA modes (auto, dedupe, passthrough)
```

For example, to update the client mode as passthrough for the **BabuK-W2K8-02** client, run the command: `rda --update_client --name BabuK-W2K8-02 --mode passthrough`



Result

Rapid Data Access (RDA) client BabuK-W2K8-02 with mode Pass-through added successfully.

rda --limit --speed <>num><KBps| MBps| GBps> | default> --target <ip address | hostname>

Description

The command limits the bandwidth consumed by RDA when replicating over a WAN link.

Syntax

```
rda --limit --speed 4 GBps --target testbackup
```

Result

Successfully updated bandwidth limit for testbackup to 4 GBps.

rda --partial_images --containerid <Container id> [--delete <Partial image path>] [--timeout <> 0>]

Description

Lists or cleans up partial images.

- Container id — ID of container.
- Partial image path — RDA partial image path to delete.
- Timeout — Maximum timeout (in seconds) to list partial images.

Syntax

```
rda --partial_images --containerid container1
```

Results

```
Image Name: rda_SOAK-MAX_DR4300-20_100M_soakw78_20160916053405-seed273481828
Image Date: 00
Image Policy: RDA
Image Path: /0000000000/rda_SOAK-MAX_DR4300-20_100M_soakw78_20160916053405-
seed273481828
Image Size: 104857600
Image Status: 0
```

rda --help

Description

Displays the list of RDA-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
rda --help
```

Result

```
rda --show [--config]
          [--file_history] [--name <name>]
          [--active_files] [--name <name>]
          [--clients]
          [--limits]

          rda --delete_client --name <RDA Client Hostname>
          rda --update_client --name <RDA Client Hostname>
                      --mode <auto|passthrough|dedupe>
          rda --limit --speed <>num><kbps|mbps|gbps> | default>
```



```

--target <ip address | hostname>

rda --partial_images --containerid <Container id> [--delete <Partial
image path>]
[--timeout <> 0>]

rda --help

rda <command> <command-arguments>
<command> can be one of:
    --show           Displays command specific information.
    --delete_client Deletes the Rapid Data Access (RDA) client.
    --update_client Updates attributes of a Rapid Data Access
(RDA) client.
    --limit          Limits bandwidth consumed by Rapid Data
Access (RDA) when replicating over a WAN link.
    --partial_images Lists or cleans up partial images.

For command-specific help, please type rda --help <command>
eg:
    rda --help show

```

Stats

This set of DR Series system CLI commands let you display the current statistics for a DR Series system in the following categories:

- All containers (cumulative): **--system**
- CPU: **--cpu**
- Memory: **--memory**
- Network interfaces: **--network**
- Online data verification: **--datacheck**
- NFS: **--nfs**
- CIFS: **--cifs**
- OST media server: **--ost**
- RDS media server **--rds**
- A specific container: **--container --name**
- Replication: **--replication**
- Seeding: **--seed**
- Cleaner: **--cleaner**
- Clients: **--clients --type**

In addition, this DR Series system CLI command also allows you to reset the following statistic types:

- NFS: **--reset --nfs**
- CIFS: **--reset --cifs**
- OST: **--reset --ost**
- RDS **--reset --rds**
- Data Check: **--reset --datacheck**

 **NOTE:** For information on the stats --datacheck commands that are associated with the Data Check feature, see [stats --datacheck](#).



Stats Command Usage

This topic introduces the **stats** command usage:

- **stats --system**
- **stats --cpu**
- **stats --memory**
- **stats --network**
- **stats --datacheck**
- **stats --nfs**
- **stats --cifs**
- **stats --ost**
- **stats --rds**
- **stats --ndmp**
- **stats --ndmp_completed**
- **stats --iscsi [options]**
- **stats --fc**
- **stats --container --name**
- **stats --storage_group --name**
- **stats --replication [options]**
- **stats --seed**
- **stats --cleaner**
- **stats --clients [options]**
- **stats --reset [options]**
- **stats --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

stats --system

Description

Displays the current cumulative system statistics for all of the configured containers on a DR Series system.

Syntax

```
stats --system
```

Result

Capacity Used	:	4.4 GiB
Capacity Used in GB	:	4.716
Capacity Free	:	7987.8 GiB
Capacity Free in GB	:	8576.854
Read Throughput	:	0.00 MiB/s
Write Throughput	:	0.00 MiB/s
Current Files	:	2
Current Bytes	:	2097152000
Post Dedupe Bytes	:	2097152000
Post Compression Bytes	:	2097152000
Post Encryption Bytes	:	2097799056
Post Encryption Bytes in GiB	:	2.0 GiB
Compression Status	:	Done
Cleaner Status	:	Done
Encryption Status	:	Done
Total Inodes	:	4



```
Bytes decrypted : 6761218080
Dedupe Savings : 0.00 %
Compression Savings : 0.00 %
Total Savings : 0.00 %
```

stats --cpu

Description

Displays the current cumulative CPU statistics for a DR Series system.

Syntax

```
stats --cpu
```

Result

```
13:00:00 up 9 days, 19:24, 2 users, load average: 1.12, 1.20, 1.18
Cpu(s): 1.4%us, 2.3%sy, 4.0%ni, 99.3%id, 0.0%wa, 0.0%hi, 0.0%si, 0.0%st
```

stats --memory

Description

Displays the current memory statistics in kilobytes (kB) for a DR Series system.

Syntax

```
stats --memory
```

Result

```
MemTotal : 32425580 kB
MemFree : 12015828 kB
Buffers : 46186022 kB
Cached : 1778860 kB
SwapCached : 0 kB
Active : 18802964 kB
Inactive : 1054936 kB
HighTotal : 0 kB
HighFree : 0 kB
LowTotal : 32425580 kB
LowFree : 12015828 kB
SwapTotal : 25165812 kB
SwapFree : 25165812 kB
Dirty : 860 kB
Writeback : 0 kB
AnonPages : 17617000 kB
Mapped : 585304 kB
Slab : 270200 kB
PageTables : 46228 kB
NFS_Unstable : 0 kB
Bounce : 0 kB
CommitLimit : 55970112 kB
Committed_AS : 20335148 kB
VmallocTotal : 34359738367 kB
VmallocUsed : 393184 kB
VmallocChunk : 34359343591 kB
HugePages_Total : 0
HugePages_Free : 0
HugePages_Rsvd : 0
Hugepagesize : 2048 kB
```



stats --network

Description

Displays the current network interfaces (eth0, eth1, eth2, eth3, and bond0) statistics for a DR Series system.

Syntax

```
stats --network
```

Result

eth0 Rx Bytes	:	105604787051
eth0 Rx Packets	:	9999546789
eth0 Rx Errors	:	0
eth0 Rx Drops	:	0
eth0 Rx Fifo Errors	:	0
eth0 Rx Frame Errors	:	0
eth0 Tx Bytes	:	108732530699
eth0 Tx Packets	:	1646686197
eth0 Tx Errors	:	0
eth0 Tx Drops	:	0
eth0 Tx Fifo Errors	:	0
eth0 Tx Collision	:	0
eth0 Tx Carrier Error	:	0
eth1 Rx Bytes	:	10360478700
eth1 Rx Packets	:	123465437
eth1 Rx Errors	:	0
eth1 Rx Drops	:	0
eth1 Rx Fifo Errors	:	0
eth1 Rx Frame Errors	:	0
eth1 Tx Bytes	:	10960478703
eth1 Tx Packets	:	195604783
eth1 Tx Errors	:	0
eth1 Tx Drops	:	0
eth1 Tx Fifo Errors	:	0
eth1 Tx Collision	:	0
eth1 Tx Carrier Error	:	0
eth2 Rx Bytes	:	10760478702
eth2 Rx Packets	:	133604783
eth2 Rx Errors	:	0
eth2 Rx Drops	:	0
eth2 Rx Fifo Errors	:	0
eth2 Rx Frame Errors	:	0
eth2 Tx Bytes	:	1235875909
eth2 Tx Packets	:	13578213
eth2 Tx Errors	:	0
eth2 Tx Drops	:	0
eth2 Tx Fifo Errors	:	0
eth2 Tx Collision	:	0
eth2 Tx Carrier Error	:	0
eth3 Rx Bytes	:	1996047831
eth3 Rx Packets	:	133404782
eth3 Rx Errors	:	0
eth3 Rx Drops	:	0
eth3 Rx Fifo Errors	:	0
eth3 Rx Frame Errors	:	0
eth3 Tx Bytes	:	1195604722
eth3 Tx Packets	:	193460478
eth3 Tx Errors	:	0
eth3 Tx Drops	:	0
eth3 Tx Fifo Errors	:	0
eth3 Tx Collision	:	0
eth3 Tx Carrier Error	:	0



```

bond0 Rx Bytes : 105604787051
bond0 Rx Packets : 135791120
bond0 Rx Errors : 0
bond0 Rx Drops : 0
bond0 Rx Fifo Errors : 0
bond0 Rx Frame Errors : 0
bond0 Tx Bytes : 108732530699
bond0 Tx Packets : 1646686197
bond0 Tx Errors : 0
bond0 Tx Drops : 0
bond0 Tx Fifo Errors : 0
bond0 Tx Collision : 0
bond0 Tx Carrier Error : 0

```

stats --datacheck

Description

Displays the current set of datacheck statistics on a DR Series system.

 **NOTE:** The Progress field in the statistics can indicate one of three values: Waiting, Running, and Idle.

- **Waiting:** Data Check is in this state because another operation is now running.
- **Running:** Data Check is in this state when running the scans.
- **Idle:** Data Check is in this state waiting for the next opportunity to run the Data Check scans.

The following example shows the status of active DR Series system operations in response to the **stats --datacheck** command on a DR Series system when Data Check is enabled.

Syntax

```
stats --datacheck
```

Result

```

Data Check : Enabled -
namespace,blockmap,throttle:75%
Progress : Idle
Active Writes : No
Active System Operations : No
Total Detected Errors : 0
Last Complete Namespace Scan : 2012-02-02 17:48:18
Last Complete Blockmap Scan : 2012-02-02 16:33:08
Namespace Scans Completed : 183
Namespace Scan Entries : 6
Namespace Scan Errors : 0
Namespace Scan Start Time : 2012-02-02 17:43:08
Namespace Scan Progress : 100.00%
Blockmap Scans Completed : 8
Blockmap Scan Entries : 3
Blockmap Scan Errors : 0
Blockmap Scan Start Time : 2012-02-02 16:33:06
Blockmap Scan Progress : 100.00%

```

Other Examples

This example shows the output from the **stats --datacheck** command used on a DR Series system when Data Check is disabled.

```
stats --datacheck
```

```

Online Data Verification : Disabled
Progress : Disabled
Active Writes : No
Active System Operations : No
Total Detected Errors : 0
Last Complete Namespace Scan : 2012-01-24 15:50:10
Last Complete Blockmap Scan : 2012-01-24 15:55:59

```



stats --nfs

Description

Displays the current NFS statistics for a DR Series system.

Syntax

```
stats --nfs
```

Result

NFS Per Op Statistics				
Procedure	Calls	Avg (us)	Max (us)	Errors
NULL	94	277	4172	0
GETATTR	52552	19946	19905631	0
SETATTR	1031	629602	166232015	0
LOOKUP	2227	18897	1918992	1673
ACCESS	26221	543	416780	0
READLINK	0	0	0	0
READ	5302595	240217	856398852	1
WRITE	12872	188647	6853027	0
CREATE	1031	917970	23587115	0
MKDIR	0	0	0	0
SYMLINK	0	0	0	0
MKNOD	0	0	0	0
REMOVE	44996	155136	6458023	0
RMDIR	0	0	0	0
RENAME	0	0	0	0
LINK	0	0	0	0
REaddir	0	0	0	0
REaddirplus	85566	30674	28308673	0
FSSTAT	30	321247	1133437	0
FSINFO	104	55279	2402344	0
PATHCONF	52	30217	1466732	0
COMMIT	1031	102190	5506293	0
XWRITE	676364	0	0	0

stats --cifs

Description

Displays the current CIFS statistics for a DR Series system.

Syntax

```
stats --cifs
```

Result

CIFS Per Op Statistics				
Procedure	Calls	Avg (us)	Max (us)	Errors
CONNECT	240	536311	1545946	0
DISCONNECT	214	1979	13127	0
CREATE	271	147101	1170580	0
OPEN	0	0	0	0
CLOSE	0	0	0	0
PREAD	1223941	6167	856679104	0
IOV_PREAD	0	0	0	0
PWRITE	4629174	26376	529148935	0
IOV_PWRITE	0	0	0	0
FTRUNCATE	0	0	0	0
LSTAT	0	0	0	0
FCNTL	0	0	0	0
CANCEL	0	0	0	0
FSTAT	548246	325	7495992	0



FSTAT_BY_PATH	0	0	0	0
REaddir	5064	106833	13550728	0
OPendir	2478	160	3671	0
OPendir_BY_PATH	0	0	0	0
Closedir	2477	22	1434	0
Mkdir	0	0	0	0
Mkdir_BY_PATH	0	0	0	0
Remove	0	0	0	0
Remove_BY_PATH	18026	90875	4900538	0
Rename	0	0	0	0
Rename_BY_PATH	0	0	0	0
Rmdir	0	0	0	0
Rmdir_BY_PATH	0	0	0	0
Fchmod	0	0	0	0
Fchmod_BY_PATH	0	0	0	0
Fchown	0	0	0	0
Fchown_BY_PATH	0	0	0	0
Fsync	226	16257	561552	0
Statvfs	0	0	0	0
Statvfs_BY_PATH	0	0	0	0
Utime	0	0	0	0
Utime_BY_PATH	0	0	0	0
Mkfifo	0	0	0	0
Mknod	0	0	0	0
Readlink	0	0	0	0
Readlink_BY_PATH	0	0	0	0
Link	0	0	0	0
Link_BY_PATH	0	0	0	0
Symlink	0	0	0	0
Symlink_BY_PATH	0	0	0	0
Flock	0	0	0	0
Setxattr	271	87332	565006	0
Setxattr_BY_PATH	512	95902	896865	0
Getxattr	922	21916	687777	0
Getxattr_BY_PATH	354219	18363	3902905	0
Listxattr	676	25103	551572	0
Listxattr_BY_PATH	261591	9222	4276854	0
Removexattr	0	0	0	0
Removexattr_BY_PATH	0	0	0	0
Fd_From_Path	610645	1609	856224591	0
Get_Real_Filename	1358	17105	860143	0
Xwrite	0	0	0	0

CIFS I/O Statistics

Procedure	Avg (bytes)	Max (bytes)	Min (bytes)
<hr/>			
READ	52429	61440	61440
WRITE	65536	65536	65536
XWRITE	0	0	0

stats --ost

Description

Displays the current OpenStorage Technology (OST) statistics categories for a DR Series system.

Syntax

```
stats --ost
```

Result

OST Server Statistics	Calls	Avg (us)	Max (us)	Errors
<hr/>				
GET_AUTH	2	0	0	0
OPEN_SERVER	2	0	0	0



CLOSE_SERVER	1	0	0	0
CREATE_FILE	0	0	0	0
OPEN_FILE	9871	0	28	0
CLOSE_FILE	9871	0	27	0
UNLINK_FILE	0	0	0	0
WRITE_FILE	6	0	0	0
READ_FILE	19676	0	0	0
REPLICATE_FILE	0	0	0	0
LIST_LSU	2	0	0	0
OPENDIR	0	0	0	0
CLOSEDIR	0	0	0	0
REaddir	0	0	0	0
SET_LSU_INFO	0	0	0	0
GET_LSU_INFO	3279	0	22	0
REPL_SVR_SETUP	0	0	0	0
GET_IMAGE_INFO	0	0	0	0
MKDIR	0	0	0	0
RMDIR	0	0	0	0
RENAME	0	0	0	0
ACCESS	9906	0	0	0
TRUNCATE	0	0	0	0
GETSCID	9871	0	0	0
REaddir_PLUS	0	0	0	0

stats --rds

Description

Displays statistics for RDS server.

Syntax

stats --rds

Result

RDS Server Statistics				
Procedure	Calls	Avg (us)	Max (us)	Errors
GET_AUTH	2	0	0	0
OPEN_SERVER	2	0	0	0
CLOSE_SERVER	1	0	0	0
CREATE_FILE	0	0	0	0
OPEN_FILE	9901	0	28	0
CLOSE_FILE	9901	0	27	0
UNLINK_FILE	0	0	0	0
WRITE_FILE	6	0	0	0
READ_FILE	19736	0	0	0
REPLICATE_FILE	0	0	0	0
LIST_LSU	2	0	0	0
OPENDIR	0	0	0	0
CLOSEDIR	0	0	0	0
REaddir	0	0	0	0
SET_LSU_INFO	0	0	0	0
GET_LSU_INFO	3289	0	22	0
REPL_SVR_SETUP	0	0	0	0
GET_IMAGE_INFO	0	0	0	0
MKDIR	0	0	0	0
RMDIR	0	0	0	0
RENAME	0	0	0	0
ACCESS	9936	0	0	0
TRUNCATE	0	0	0	0
GETSCID	9901	0	0	0
REaddir_PLUS	0	0	0	0



stats --ndmp

Description

Displays statistics for current NDMP sessions for a DR Series system.

Syntax

```
stats --ndmp
```

Result

Bytes Written	Bytes Read
3632267264	0

stats --ndmp_completed

Description

Displays statistics for completed NDMP sessions for a DR Series system.

Syntax

```
stats --ndmp_completed
```

Result

Bytes Written	Bytes Read
1247953038336	2253404205

stats --iscsi [--verbose]

Description

This command displays statistics for iSCSI sessions on the current DR system. The --verbose option provides detailed session information for the cartridges in the VTL.

Syntax

```
stats --iscsi --verbose
```

Result

```
# stats - iscsi
Bytes Written          Bytes Read
1247953038336        2253404205
```

```
# stats -iscsi -verbose
```

```
Container: vtl-1
TGT LUN      Model SID Read [ bytes cmd ] Write[ bytes cmd ] Errs
  1   1   L700    3   34367   435      0     0   1
  1   2   ULT3580-TD4  3 125487488328 638396    176    12  177
  1   3   ULT3580-TD4  3   72052   101      44     3  166
  1   4   ULT3580-TD4  3   72032   100      44     3  165
  1   5   ULT3580-TD4  3   72032   100      44     3  165
  1   6   ULT3580-TD4  3   6176    90       0     0  158
  1   7   ULT3580-TD4  3   72032   100      44     3  165
  1   8   ULT3580-TD4  3   72032   100      44     3  165
  1   9   ULT3580-TD4  3   468220  212 601296470516 3058393 158
  1  10   ULT3580-TD4  3 601299559400 3058553    352    24  171
  1  11   ULT3580-TD4  3   72032   100      44     3  165
```



stats --fc [--iostat] [--linkstat]

Description

This command displays statistics for Fibre Channel (FC) sessions on the current DR system. You can specify the following parameters with this command:

- iostat — returns input/output statistics, such as bytes read
- linkstats — provides statistics like frames received/sent, loss of sync, loss of signal, and link failures.

Syntax

stats --fc

Result

Target port: 50:00:65:b6:33:63:14:88

```
Link Failure: 1
Loss Of Sync: 0
Loss Of Signal: 0
Primitive Sequence Protocol Error: 0
Invalid Transmission Word: 0
Invalid CRC: 0
NOS Received: 1
Rx Frames: 295069
Tx Frames: 590099
```

Bytes Written	Bytes Read
0	51678208
Initiator: 10:00:00:90:fa:a0:ae:0a	
Bytes Written	Bytes Read
0	24576
Initiator: 50:0a:09:80:00:88:a7:71	
Bytes Written	Bytes Read
0	1900544
Initiator: 50:0a:09:80:06:8d:9a:40	
Bytes Written	Bytes Read
0	1900544
Initiator: c0:03:ff:bd:1d:69:00:48	
Bytes Written	Bytes Read
0	47851520

Target port: 50:00:65:b6:33:63:14:89

```
Link Failure: 3
Loss Of Sync: 0
Loss Of Signal: 0
Primitive Sequence Protocol Error: 0
Invalid Transmission Word: 63
Invalid CRC: 0
NOS Received: 2
Rx Frames: 555628
Tx Frames: 1111214
```

Bytes Written	Bytes Read
0	96420864
Initiator: 10:00:00:90:fa:cf:49:5e	
Bytes Written	Bytes Read
0	0



```
Initiator: c0:03:ff:bd:1d:69:00:54
    Bytes Written          Bytes Read
        0                      734208

Initiator: c0:03:ff:bd:1d:69:00:58
    Bytes Written          Bytes Read
        0                      94950400

Initiator: c0:03:ff:bd:1d:69:00:60
    Bytes Written          Bytes Read
        0                      734208
```

```
stats --fc --iostat
Target port: 50:00:65:b8:14:26:78:78

    Bytes Written          Bytes Read
138577053696                  3776857088

Initiator: 20:01:00:0e:1e:d0:79:f8
    Bytes Written          Bytes Read
138577053696                  3776857088

Target port: 50:00:65:b8:14:26:78:79

    Bytes Written          Bytes Read
    0                      0
```

```
stats --fc --linkstat
Target port: 50:00:65:b8:14:26:78:78

Link Failure: 4
Loss Of Sync: 3
Loss Of Signal: 3
Primitive Sequence Protocol Error: 0
Invalid Transmission Word: 0
Invalid CRC: 0
NOS Received: 4
Rx Frames: 70594737
Tx Frames: 7700330
Abort Task Set: 0
Clear Task Set: 0
Clear ACA: 0
LUN Reset: 0
Target Reset: 0
```

```
Target port: 50:00:65:b8:14:26:78:79

Link Failure: 0
Loss Of Sync: 0
Loss Of Signal: 0
Primitive Sequence Protocol Error: 0
Invalid Transmission Word: 0
Invalid CRC: 0
NOS Received: 0
Rx Frames: 0
Tx Frames: 0
Abort Task Set: 0
Clear Task Set: 0
Clear ACA: 0
LUN Reset: 0
Target Reset: 0
```



stats --container --name <name>

Description

Displays the current statistics for a specific container in a DR Series system that you define by name using the DR Series system CLI **--name <name>** command.

Syntax

```
stats --container --name backupsys-60_replicate
```

Result

Container Name	:	backupsys-60_replicate
Container ID	:	3
Total Inodes	:	1
Read Throughput	:	3.91 MiB/s
Write Throughput	:	3.45 MiB/s
Current Files	:	109931
Current Bytes	:	6193231169
Cleaner Status	:	Done

stats --storage_group --name <name>

Description

This command displays statistics for a specific storage group as referenced by the **--name <name>** command option.

Syntax

```
stats --storage_group --name DefaultGroup
```

Result

Storage_group ID	:	0
Capacity Used	:	380.4 GiB
Capacity Used in GB	:	408.425
Capacity Free	:	3572.8 GiB
Capacity Free in GB	:	3836.313
Total Inodes	:	810
Read Throughput	:	0.00 MiB/s
Write Throughput	:	0.00 MiB/s
Current Files	:	682
Current Bytes	:	1351703380026
Post Dedupe Bytes	:	408536589100
Post Compression Bytes	:	408424845453
Post Encryption Bytes	:	0
Post Encryption Bytes in GiB	:	0.0 GiB
Bytes decrypted	:	0
Cleaner Status	:	Pending
Compression Status	:	Done
Encryption Status	:	Disabled
Dedupe Savings	:	69.78 %
Compression Savings	:	0.03 %
Total Savings	:	69.78 %

stats --replication [--name <name>]

Description

Displays the current replication statistics for all containers in a DR Series system or for a specific container in a DR Series system that you define using the DR Series system CLI **--name <name>** command.

Syntax

```
stats --replication --name backup-acme-60_replicate
```



Result

```
Container Name : backup
Replication Target Container : backup
Replication Target System : 10.25.19.16
Peer Status : Stopped
Replication State : INSYNC
Schedule Status : Outside window
(starts in 0 days 10 hours 6 min 0 sec)
Replication Average Throughput : 4154 KiB/s
Replication Maximum Throughput : 15710 KiB/s
Network Average Throughput : 3759 KiB/s
Network Maximum Throughput : 14999 KiB/s
Network Bytes Sent : 154.45 MiB
Network Savings : 56.60 %
Last INSYNC Time : 2012-06-20 09:11:42
Estimated Time To Sync : 0 days 7 hours 3 minutes 19
seconds
```

Data replication history

```
File : /vargen/source/Office_Docs/Email/Outlook/3244.flate, 44.70%, 88773
bytes, 1305 KB/s, replicated at : 2012-06-19 11:47:03

File : /vargen/source/status/DEV/August11/dev-status.doc, 100.00%, 86200 bytes,
4310 KB/s, replicated at : 2012-06-19 11:47:03

File : /vargen/source/MKT/whitepaper/eng/324.tar.gz, 0.00%, 5182 bytes, 259
KB/s, replicated at : 2012-06-19 11:47:03

File : /vargen/source/acctspay/status/Sept11/3242.tar.gz, 65.23%, 94616 bytes,
1456 KB/s, replicated at : 2012-06-19 11:47:03

File : /vargen/source/revenue/Q311/interna/324.xls, 0.00%, 5152 bytes, 286
KB/s, replicated at : 2012-06-19 11:47:03

File : /vargen/source/projects/Q411/europe/3244.tar.gz, 62.94%, 8828 bytes,
1193 KB/s, replicated at : 2012-06-19 11:47:03
```

stats --cleaner

The **stats --cleaner** command displays the current running cleaner progress and the amount of time taken to complete its latest full pass. The Cleaner is an asynchronous process in the DR Series system that reclaims disk storage space by reclaiming space that previously contained unreferenced datastore files.

Syntax

```
stats --cleaner
```

Result

```
Last Run:
Last Files Processed : 0
Last Bytes Processed : 0
Last Bytes Reclaimed : 0
Last Start Time : 11/30/16 01:57:32
Last End Time : 11/30/16 01:57:37
Time To Completion(s) : 5.00

Current Run:
Start Time : 11/30/16 02:00:37
Files Processed : 100
Bytes Processed : 37748736000
Bytes Reclaimed : 15281899829
Phase 1 Start Time : 11/30/16 02:00:38
```



Phase 1 Records Processed	:	0
Phase 1 End Time	:	11/30/16 02:00:38
Phase 2 Start Time	:	11/30/16 02:00:38
Phase 2 Records Processed	:	1172436
Phase 2 End Time	:	11/30/16 02:00:39
Phase 3 Start Time	:	11/30/16 02:00:39
Phase 3 Records Processed	:	1600
Phase 3 End Time	:	11/30/16 02:00:47
Phase 4 Start Time	:	11/30/16 02:00:51
Phase 4 Records Processed	:	1637
Phase 4 End Time	:	11/30/16 02:00:51
Phase 5 Start Time	:	11/30/16 02:00:51
Phase 5 Records Processed	:	0
Phase 5 End Time	:	11/30/16 02:00:51
Last Completed Run:		
Last Completed Start Time	:	11/30/16 01:50:15
Last Completed End Time	:	11/30/16 01:50:30
Last Completion time(s)	:	15.00
Cleaner Pending Work:		
Estimated Logical Bytes Left	:	3130982400

```
stats --clients [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI|FC>]
```

Description

Displays the current NFS, CIFS, OST, RDS, NDMP, iSCSI, or FC clients that are configured on the DR Series system.

To filter the list of clients to display a specific client type (for example, NFS clients) on a DR Series system, use the DR Series system CLI **--type** command option.



NOTE: For OST clients, the value under Connections is 0 (zero) when the connection is configured (but it is not in use), and 1 when the connection is in use.

Syntax

```
stats --clients
```

Result

No NFS client(s) are connected.

No CIFS client(s) are connected.

No OST client(s) are connected.

RDS Client(s)	Type	Plugin	OS	Backup Software	Last Access
Connection(s)	Mode				
BabuK-W2K8-02	RDS	2.1.201	Windows Server 2008 R2	NetVault 9.20 Build 12	Aug 13 07:53:26 1
	Passthrough		R72xd-Netvault		
RDS	--	--	--	--	0
Default					

No ndmp sessions found.

iSCSI client(s) information:

Container: iscsi-1

Target ION: ian.1984-05.com.dell:dr4000.2149308.iscsi-1.50

Initiators Connected: ign.1991-05.com.microsoft:test-w2k8-03.test.local



stats --reset [--nfs] [--cifs] [--ost] [--rds] [--datacheck]

Description

Resets the current NFS, CIFS, OST, RDS, or Data Check statistics for a DR Series system. The following example shows **--nfs**; to reset another statistic type, just replace that option type in the DR Series system CLI command.

Syntax

```
stats --reset -nfs
```

Result

Successfully reset NFS stats.

stats --reset --datacheck

Description

Resets the current set of Data Check statistics on a DR Series system.

Syntax

```
stats --reset --datacheck
```

Result

Datacheck statistics reset successfully.

stats --seed

Description

Use to monitor the seeding progress.

Syntax

```
stats --seed
```

Result

Seeding Source Stats:

Seed state:	SEED_STARTED
Seed status:	FINISHED
Seed device mount:	/mnt/.__seed_device
Blockmaps read:	12
Seeding Dictionary updates:	1065
Streams read:	196042
Comp bytes read:	5959925818
Streams committed:	196042
Streams deduped:	141245
DS's committed:	475
Total bytes processed:	10401873920
Total bytes deduped:	4441947702
Total inline bytes:	400
Total orig bytes committed:	5959925818
Total comp bytes committed:	5959925818
Device orig bytes committed:	5959925818
Device comp bytes committed:	5959925818
Logical Avg Throughput:	0.000 KB/s
Logical Max Throughput:	2462955.935 KB/s
Physical Avg Throughput:	0.000 KB/s
Physical Max Throughput:	151010.166 KB/s
Estimated time to sync:	0 days 0 hours 0 minutes 0 seconds

.....
.....
.....



stats --help

Description

Displays the list of all stats-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
stats --help
```

Result

Usage:

```
    stats --system
    stats --cpu
    stats --memory
    stats --network
    stats --datacheck
    stats --nfs
    stats --cifs
    stats --ost
    stats --rds
    stats --ndmp
    stats --ndmp_completed
    stats --iscsi [--verbose]

    stats --fc [--iostat]
              [--linkstat]

    stats --container --name <name>

        stats --storage_group --name <name>
        stats --replication [--name <name>]

    stats --cleaner

    stats --clients [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI|FC>]

    stats --reset [--nfs]
                  [--cifs]
                  [--ost]
                  [--rds]
                  [--datacheck]

    stats --seed

    stats --help

stats <command> <command-arguments>
<command> can be one of:

--system      Displays cumulative statistics for all containers.
--cpu         Displays CPU statistics.
--memory     Displays statistics for memory.
--network    Displays statistics for network interfaces.
--datacheck   Displays statistics for online data verification.
--nfs          Displays statistics for NFS.
--cifs         Displays statistics for CIFS.
--ost          Displays statistics for OST server.
--rds          Displays statistics for RDS server.
--ndmp        Displays statistics for current NDMP sessions.
--ndmp_completed Displays statistics for completed NDMP sessions.
--iscsi       Displays statistics for iSCSI sessions.
--fc          Displays statistics for FC sessions.
--container   Displays statistics for a specific container.
--storage_group Displays statistics for a specific storage group.
--replication  Displays statistics for replication.
```



```
--cleaner      Displays statistics for cleaner.  
--clients     Displays client information.  
--reset       Resets statistics.  
--seed        Seeding statistics.
```

For command-specific help, please type stats --help <command>

For example:
stats --help reset

stats --datacheck

This set of DR Series system CLI commands allow you to display the current Data Check statistics gathered by the system, reset the Data Check statistics for the system, and display the statistic-based Data Check help-related options. For more information, see [Stats --Datacheck Command Usage](#).

stats --datacheck Command Usage

This topic introduces the **stats --datacheck** command usage:

- **stats --datacheck**
- **stats --reset --datacheck**
- **stats --help datacheck**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

stats --help datacheck

Description

Displays the list of stats command-based Data Check options that can be used as a reference when using the DR Series system CLI.

Syntax

```
stats --help datacheck  
--datacheck - Displays statistics for online data verification.
```

Result

Usage:
stats --datacheck

Storage Group commands

This set of DR Series system CLI commands let you manage the storage groups on a DR Series system, enabling you to perform tasks, such as adding or deleting a storage group, updating a storage group, updating encryption settings, updating compression settings, and setting a passphrase.

Storage Group Command Usage

This topic introduces the **storage_group** command usage:

- **storage_group --show**
- **storage_group --add --name**
- **storage_group --update --name**
- **storage_group --encryption --name**



- `storage_group --delete --name`
- `storage_group --setpassphrase --name`
- `storage_group --help`

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

storage_group --show [--name <name>] [-verbose]

Description

Displays the current list of storage groups on the DR Series system. If you specify the `--name` option, you can view details of a specific storage group. The `-verbose` option displays more details.

Syntax

```
storage_group --show --name DefaultGroup --verbose
```

Result

```
Storage_group Entry ID      : 0
Storage_group Name          : DefaultGroup
Storage_group Compression Type : Fast
Storage_group Encryption Set   : Off
Storage_group Encryption Mode  : Off
Storage_group Rotate Period    : 0
Storage_group Passphrase set   : No
Storage_group Created On      : Thu Nov 17 00:40:14 2016 PST
Storage_group Created Bld      : 62141
DefaultGroup's Containers
-----
backup
vtl-iscsi
```

storage_group --add --name <name> [--compression_mode <fast|best>]

Description

Adds a new storage group to the DR Series system with the name specified by the `--name` command option.

 **NOTE:** When adding a name, valid values for the name are (a-z, A-Z, 0-9, '_', and '_')

You can also set the compression mode for the storage group as fast or best, described as follows:

- Fast — Results in shorter backup time, but with less space savings.
- Best — Provides the highest space savings, but with a longer backup time.

Syntax

```
storage_group --add --name StorageGroup_1 --compression_mode best
```

Result

```
Storage Group "StorageGroup_1" created successfully.
```

storage_group --update --name <name> [--compression_mode <fast|best>]

Description

Allows you to modify the compression mode for the specified storage group. The compression mode for the storage group can be set as fast or best, described as follows:

- Fast — Results in shorter backup time, but with less space savings.
- Best — Provides the highest space savings, but with a longer backup time.



Syntax

```
storage_group --update --name StorageGroup_1 --compression_mode fast
```

Result

Storage Group "StorageGroup_1" updated successfully.

storage_group --encryption --name <name> [--set <ON | OFF>] [--mode <static|internal> --interval <7 days to 70 years>]

Description

Allows you to set the encryption level for a specified storage group on the DR Series system. You turn encryption on or off by using the --set ON or --set OFF command options. The --mode option sets the mode of key lifecycle management as one of the following:

- static—A global, fixed key is used to encrypt all data.
- internal—Content encryption keys are generated and rotated on a specified period of days.

If you select Internal as the mode of key management, you need to set the --interval option, which specifies the number of days for key rotation when a new key is to be generated.

 **NOTE:** In Internal mode there is a maximum limit of 1023 keys. The key rotation period is set to 30 days by default when the passphrase is set and/or encryption is turned on. You can later change the key rotation period from 7 days to 70 years for internal mode.

 **NOTE:** After encryption is enabled, all of the data that is backed up is encrypted and is kept encrypted until it is expired and cleaned by the system cleaner. Note that encryption is an irreversible process.

 **NOTE:**

Due to export regulations, the encryption at rest feature is not available in certain markets, and, therefore, may not be available in your locale.

Syntax

```
storage_group --encryption --name StorageGroup_1 --set ON --mode internal --interval 120
```

Result

Storage Group "StorageGroup_1" updated successfully.

storage_group --setpassphrase --name <name>

Description

Sets the passphrase for the specified storage group to be used to encrypt content encryption keys. (The passphrase string can take up to 255 characters. And, alphanumeric and special characters can be entered as part of the passphrase string.) This command will prompt you to enter and confirm a passphrase. This command also requires a filesystem server restart.

 **NOTE:** It is mandatory to define a passphrase to enable encryption for a storage group. If the passphrase is compromised or lost, the administrator should change it immediately so that the content encryption keys do not become vulnerable.

Syntax

```
storage_group --setpassphrase --name StorageGroup_1
```

Result

Storage Group "StorageGroup_1" updated successfully.
Passphrase updated successfully.



storage_group --delete --name <name>

Description

Deletes the specified storage group from the DR Series system.

 **NOTE:** Before a storage group can be deleted, all of the containers inside the storage group must first be deleted.

Syntax

```
storage_group --delete --name StorageGroup_1
```

Result

```
Storage Group "StorageGroup_1" has been deleted.
```

storage_group --help

Description

Displays the list of all storage_group-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
storage_group --help
```

Result

Usage:

```
storage_group --show [--name <name>]
[--verbose]
```

```
storage_group --add --name <name>
[--compression_mode <fast|best>]
```

```
storage_group --update --name <name>
[--compression_mode <fast|best>]
```

```
storage_group --encryption --name <name>
[--set <ON|OFF>]
[--mode <static | internal>]
[--interval <7 days to 70 years>]
```

```
storage_group --delete --name <name>
```

```
storage_group --setpassphrase --name <name>
```

```
storage_group --help
```

```
storage_group <command> <command-arguments>
command can be one of:
```

--show	Displays the current list of storage_group.
--add	Adds a new storage_group.
--update	updates a storage_group.
--encryption	updates encryption settings of a storage_group.
--delete	Deletes an existing storage_group.
--setpassphrase	sets passphrase to a storage_group.

For command-specific help, please type `storage_group --help <command>`

eg:

```
storage_group --help show
```



System

This DR Series system CLI command and its options allow you to perform the a variety of system-related tasks, including the following:

- Displaying the current system configuration
- Initializing, rebooting, or shutting down the DR Series system
- Upgrading the DR Series system software
- Setting the system date and time
- Setting the network time protocol (NTP)
- Updating the login password
- Enabling or disabling telnet access
- Enabling or disabling marker detection status

 **NOTE:** For information on the `system --datacheck` commands that are associated with the Data Check feature, see [system --datacheck](#).

System Command Usage

This topic introduces the `system` command usage:

- `system --show [options]`
- `system --init [options]`
- `system --reboot`
- `system --shutdown`
- `system --upgrade`
- `system --license [options]`
- `system --setname --name`
- `system --setdate [options]`
- `system --setntp [options]`
- `system --setlogin`
- `system --telnet [options]`
- `system --datacheck [options]`
- `system --marker [options]`
- `system --verify_on_read [options]`
- `system --add_storage --enclosure` (*Option only available on a physical hardware DR Series system*)
- `system --storage [options]`
- `system --mgmt_traffic` (*Option only available on a physical hardware DR Series system*)
- `system --backup_traffic` (*Option only available on a physical hardware DR Series system*)
- `system --replication_traffic` (*Option only available on a physical hardware DR Series system*)
- `system --opdup_traffic` (*Option only available on a physical hardware DR Series system*)
- `system --support_agent [options]`
- `system --help`

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.



system --show [--config]

Description

Displays the current system configuration summary for a DR Series system.

For specific sources of additional system configuration information, see the following **system --show** command options:

- **--hardware**
- **--storage** [-type <boot |internal |external>] [-service_tag <service tag>]
- **[--license]** [**--verbose**]
- **[--ntp]**
- **--version**
- **--timezones** [Region]
- **--upgradefile**
- **--upgradehistory**
- **[--marker]**
- **[--replication_traffic]**
- **[--opdup_traffic]**
- **[--backup_traffic]**
- **[--mgmt_traffic]**
- **--encryption** [options]

Syntax

```
system --show --config
```

Result

System Name	:	swsys-53
Current Time	:	Tue Apr 7 04:37:37 2015 PDT
Service Tag	:	8MWT8Q1
Product Name	:	Dell DR4000
BIOS Version	:	1.11.0
Version	:	3.2.0192.0
Build	:	56073
Build Date	:	Mon Apr 6 20:33:45 PDT 2015
IP Addr	:	10.250.240.91
Mac Addr	:	00:1B:21:9E:73:B8
Telnet State	:	Disabled
Compression Level	:	Balanced
Time Zone	:	US/Pacific
Data Check	:	Enabled - namespace,blockmap,throttle:50%
Marker Detection	:	Enabled
Storage Usage Alert	:	90%
Encryption	:	Enabled - Mode: internal, Interval: 10
NTPD Service is	:	UP
System State	:	Operational Mode
Reason	:	Filesystem is fully operational for I/O.
Diagnostics Collector	:	RUNNING Apr 6 23:42:26
Configuration Server	:	RUNNING Apr 7 00:27:16
System State	:	Operational Mode
Reason	:	Filesystem is fully operational for I/O.
Diagnostics Collector	:	RUNNING Nov 13 23:02:11
Configuration Server	:	RUNNING Nov 15 02:24:51
Filesystem Server	:	RUNNING Nov 15 02:24:53
NDMP Daemon	:	RUNNING Nov 15 02:28:04
Windows Access Server	:	RUNNING Nov 17 03:46:30
HTTP Server	:	RUNNING Nov 13 22:59:44
Hardware Health Monitor	:	RUNNING Nov 13 23:02:58
Windows Active Directory Client	:	RUNNING Nov 13 23:07:07



```

Filesystem Checker : STOPPED
VTL Daemon : RUNNING Nov 15 02:28:06
ISCSI Server : RUNNING Nov 15 02:29:35
FC Server : RUNNING Nov 15 02:29:38
Global View Process : RUNNING Nov 13 22:59:44
Support Portal Agent Process : STOPPED

```

system --show [--hardware]

Description

Displays the current DR Series system hardware status for the system hardware components. This option is only available on a Physical DR.

 **NOTE:** Due to length, the following example only shows a partial listing of the DR Series system hardware status that is displayed when using this DR Series system CLI command.

Syntax

```
system --show --hardware
```

Result

Component	Type	Signature	Health	PD_Count				
Storage Controller	PERC H700	HDB ST00	optimal	14				
Storage Controller	PERC H800	HDB ST01	optimal	48				
Component	Signature	State	Health	Raid_Level	Agg_Status	PD_Count	Name	
Virtual Disk	HDB VD00	ready	optimal	1	1	2		
Virtual Disk	0							
Virtual Disk	HDB VD01	ready	optimal	6	1	11	DATAVol	
Component	Signature	State	Spare_Config	Spare_State	Health	Slot	Serial	Alert
Size	Type							
Phys Disk	HDB PD00	online	global		no	optimal 0	9WK4ZJ82	no
1 TB	Internal							

system --show [--storage] [--type <boot | internal | external>] [--service_tag <service tag>]

Description

Displays current configuration information about the storage types installed in a DR Series system.

Syntax

```
system --show --storage --type external --service_tag HCM0PT3
```

Result

Component	Signature	State	Health	Raid_Level	Agg_Status			
PD_Count	Name							
Virtual Disk	HDB VD02	background_init	optimal	6	1			
16	ENCLVol_1							
Component	Signature	State	Spare_Config	Spare_State	Health	Slot	Serial	Alert
Size	Type							
Phys Disk	HDB PD14	ready	dedicated	no	optimal 0	Z1P1Z5AG		no
2 TB	Encl - 1							
Phys Disk	HDB PD15	ready	no	no	optimal 1	Z1P1YVFW		no
2 TB	Encl - 1							
Phys Disk	HDB PD16	ready	no	no	optimal 2	Z1P27A94		no
2 TB	Encl - 1							
Phys Disk	HDB PD17	ready	no	no	optimal 3	Z1P229LJ		no
2 TB	Encl - 1							
Phys Disk	HDB PD18	ready	no	no	optimal 4	Z1P26VKC		no
2 TB	Encl - 1							



Phys Disk HDB PD19	ready	no	no	optimal	5	Z1P26SLK
no 2 TB Encl - 1						
Phys Disk HDB PD20	ready	no	no	optimal	6	Z1P26QBM
no 2 TB Encl - 1						
Phys Disk HDB PD21	ready	no	no	optimal	7	Z1P1R6T3
no 2 TB Encl - 1						
Phys Disk HDB PD22	ready	no	no	optimal	8	Z1P26TK6
no 2 TB Encl - 1						
Phys Disk HDB PD23	ready	no	no	optimal	9	Z1P26MZ8
no 2 TB Encl - 1						
Phys Disk HDB PD24	ready	no	no	optimal	10	Z1P27C4S
no 2 TB Encl - 1						
Phys Disk HDB PD25	ready	no	no	optimal	11	Z1P1WR0F
no 2 TB Encl - 1						
Component	Signature	Health	Name	NexusId		
EMM	HDB EM00	optimal	"EMM 0"	"\\1\\0\\0\\0\\0"		
EMM	HDB EM01	optimal	"EMM 1"	"\\1\\0\\0\\1"		
Component	Signature	Health	Name	Vendor		
PartNumber						
Power Supply	HDB EP00	optimal	"Power Supply 1"	"DELL"		
"ONFCG1A02"						
Power Supply	HDB EP01	optimal	"Power Supply 2"	"DELL"		
"ONFCG1A02"						
Component	Signature	Health	Temp_Reading			
Name	Vendor					
Temperature Probe	HDB ET00	optimal	27.0	"Temperature		
Probe 0" "DELL"						
Temperature Probe	HDB ET01	optimal	29.0	"Temperature		
Probe 1" "DELL"						
Temperature Probe	HDB ET02	optimal	21.0	"Temperature		
Probe 2" "DELL"						
Temperature Probe	HDB ET03	optimal	21.0	"Temperature		
Probe 3" "DELL"						
Component	Signature	Health	Speed	Name	Vendor	
Fan	HDB EF00	optimal	0	"ONFCG1A02"	"DELL"	
Fan	HDB EF01	optimal	0	"ONFCG1A02"	"DELL"	
Fan	HDB EF02	optimal	0	"ONFCG1A02"	"DELL"	
Fan	HDB EF03	optimal	0	"ONFCG1A02"	"DELL"	

system --show [--storage]

Description

Displays the service tag, size, configuration state, RAID level, the percentage used, and the state of the storage type (or types) installed on a DR Series system.

Syntax

```
system --show --storage
```

Result

Type	Service Tag	RawSize	Configured	RAIDLevel	Used	State
Boot	16TGJTR	278.88 GB	Yes	1	--	ready
Internal	16TGJTR	8.18 TB	Yes	6	2.69%	ready
Enclosure-1	DCGTXR1	8.18 TB	No	--	--	ready

For more information about a system storage, see [system --add_storage --enclosure <service tag>](#) and [system --show \[--storage\] \[-type <boot | internal | external>\] \[-service_tag <service tag>\]](#).



system --show [--license] [--verbose]

Description

Displays the summary license status (using the **system --show --license** command) or the detailed license status (using the **system --show --license --verbose** command) for the current data storage expansion shelves (enclosures) installed in a DR Series system. For more information on validating or adding licenses for data storage expansion shelves, see [system --license \[--validate\] \[--add\]](#).

Syntax

```
system --show --license
```

Result

ID	Description	Status
1	1 Storage Enclosure	Enabled

 **NOTE:** To display a more detailed license status, use the following DR Series system CLI command:

```
system --show --license --verbose
Feature ID          : 1
Description         : 1 Storage Enclosure
Status              : Enabled
Entitlement ID     : XKE00000003387477
Start Date          :
End Date            :
Is Eval             : No
In Use              : No
```

system --show [--ntp]

Description

Displays the current NTP service configuration for the DR Series system.

Syntax

```
system --show --ntp
```

Result

NTPD Service is	:	UP
Server 1	:	0.centos.pool.ntp.org
Server 2	:	1.centos.pool.ntp.org
Server 3	:	2.centos.pool.ntp.org

system --show [--version]

Description

Displays the currently installed version of the DR Series system software, and the date and time in which it was installed.

Syntax

```
system --show --version
```

Result

Version	:	4.0.0272.0 Mon Dec 5 20:02:24 PST 2016
---------	---	--

system --show [--timezones [Region]]

Description

Displays the entire set of time zones that can be selected for a DR Series system, and also displays the time zones that can be selected in a specific region.



Syntax

```
system --show --timezones
```

Result

Following are the time zone regions.					
Africa	America	Antarctica	Arctic		
Asia	Atlantic	Australia			
Brazil	CET	CST6CDT		Canada	
Chile	Cuba		EET		
EST		EST5EDT	Egypt		
Eire		Etc	Europe		Factory
GB		GB-Eire	GMT		GMT
+0	GMT0		Greenwich	HST	
Hongkong	Iceland		Indian		
Iran		Israel	Jamaica	Japan	
Kwajalein	Libya		MET		
MST		MST7MDT	Mexico	Mideast	
NZ		NZ-CHAT	Navajo		
PRC		PST8PDT	Pacific	Poland	
Portugal	ROC		ROK		
Singapore	Turkey		UCT	US	
UTC		Universal	W-SU		
WET		Zulu			

 **NOTE:** To display the time zones that can be selected in a specific region, use the following command:

```
system --show --timezones Chile  
Following are the time zones in Chile region:  
Continental  
Easter Island
```

system --show [--upgradefile]

Description

Displays the current version of the DR Series system software upgrade file that resides on the system appliance.

Syntax

```
system --show --upgradefile
```

Result

```
Version : 4.0.0273.0  
MD5 Checksum : 6cc18503cc555cb3cdf9bb8dbe487b4a
```

system --show [--upgradehistory]

Description

Displays the upgrade history for a DR Series system.

Syntax

```
system --show --upgradehistory
```

Result

```
Update Manager started at : 2016/12/05 23:20:56  
Version : 3.1.2219.1  
Update status : SUCCESS, REBOOT REQUIRED  
Update Manager finished at : 2016/12/05 23:42:09  
Update Manager started at : 2016/12/07 09:53:13  
Version : 4.0.0273.0
```



```
Update status : SUCCESS, REBOOT REQUIRED
Update Manager finished at : 2016/12/07 10:10:40
```

system --show [--marker]

Description

Displays the current state of marker detection in a DR Series system.

Syntax

```
system --show --marker
```

Result

```
Marker Detection : Enabled
```

system --show [--replication_traffic]

Description

Displays configured dedicated replication network interface(s). This option is only available on a Physical DR.

Syntax

```
system --show --replication_traffic
```

Result

```
Application: replication
Application Interface(bond0): 10.250.xxx.x
```

system --show [--opdup_traffic]

Description

Displays the configured dedicated optimized copy network interface(s). This option is only available on a Physical DR.

Syntax

```
system --show --opdup_traffic
```

Result

```
Application: opdup_incoming
Application Interface(bond1): 10.250.xxx.x
```

system --show [--backup_traffic]

Description

Displays the configured dedicated backup network interface(s). This option is only available on a Physical DR.

Syntax

```
system --show --backup_traffic
```

Result

```
Application: OST
Application Interface(bond1): 10.250.xxx.x
```

system --show [--mgmt_traffic]

Description

Displays the configured dedicated appliance management network interface(s). This option is only available on a Physical DR.



Syntax

```
system --show --mgmt_traffic
```

Result

```
Application: webserver
Application Interface(bond3): 10.250.xxx.x
```

system --init

Description

This command initializes the system.

Syntax

```
system --init
```

Result

Please enter the administrator password:

```
Node name      = dr6300-22
IP address (bond0) = 10.250.209.65
IP address (bond2) = 10.250.240.221
```

Please verify the above information is correct.

WARNING: This operation will destroy all data in the system!
Do you want to continue (y/n)?y

```
Deleted CIFS user administrator.
Stopping Filesystem services... Done.
Updating configuration files... Done.
Cleaning diagnostics... Done.
Removing all Replication Snapshot(s)... Done.
Removing Seeding device mount... Done.
Shutting down all storage volumes... Done.
Clearing data... Done.
Creating NVRAM Partitions... Done.
Initializing NVRAM... Done.
Create NVMFS... Done.
Initializing Dictionary... Done.
Resetting alert(s)... Done.
Verifying user accounts... Done.
Stopping xinetd:                               [ OK ]
Starting xinetd:                               [ OK ]
Restarting Filesystem services... Done.
```

Node successfully initialized.

Enable Default settings

```
NTP enable... ok
NDMP set default login... ok - User exists
NDMP set default port... ok
NDMP enable... ok
```

Telnet State	:	Disabled
Compression Level	:	Balanced
Time Zone	:	US/Pacific-New
Data Check	:	Enabled - namespace,blockmap,throttle:50%
Marker Detection	:	Enabled
Storage Used Alert	:	90%
Read Verification	:	Disabled
Encryption	:	Disabled (Mode: none, Period: 0 Days)



system --init --secure_erase <1-pass/3-passes/7-passes>

Description

Secure Erase is a process for securely deleting data that follows standards developed by the Defense Security Service (DSS). These standards were developed to solve the problem of secure and permanent removal of data, and this capability is now used by many commercial enterprises. These standards require multiple passes to erase data. In the process of erasing, the system overwrites data with zeros, a random pattern of data, or ones (1s) to make the original contents unreadable.

In the DR Series system, two modes of secure erase have been adopted: 3-pass and 7-pass standards. This command securely erases all data with a 3-pass or 7-pass mode and runs during system initialization. This command erases all of the stored data while keeping the system intact.

Syntax

```
system --init --secure_erase 3-passes
system --init --secure_erase 1-pass
system --init --secure_erase 7-passes
```

Result

```
Please enter the root password:
Node name      = DR4300e-05
IP address (bond0) = 10.250.208.107

Please verify the above information is correct.

WARNING: This operation will destroy all data in the system!
Do you want to continue (y/n)?y

Deleted CIFS user administrator.
Stopping Filesystem services... Done.
Updating configuration files... Done.
Cleaning diagnostics... Done.
Removing all Replication Snapshot(s)... Done.
Removing Seeding device mount... Done.
Shutting down all storage volumes... Done.

Securely Erasing Storage Volume: /dev/sdb5
-----
Pass: 1 ... 100%
Pass: 2 ... 100%
Pass: 3 ... 100%
Securely Erased all Storage Volume(s)... Done.
Clearing data... Done.
Creating NVRAM Partitions... Done.
Initializing NVRAM... Done.
Create NVMFS... Done.
Initializing Dictionary... Done.
Resetting alert(s)... Done.
Verifying user accounts... Done.
Stopping xinetd:                               [ OK ]
Starting xinetd:                             [ OK ]
Restarting Filesystem services... Done.

Node successfully initialized.

Enable Default settings
-----
NTP enable... ok
NDMP set default login... ok - User exists
NDMP set default port... ok
NDMP enable... ok
```



The following example is the sample output of Secure Erase with 3-passes with an Enclosure attached.

Please enter the root password:

```
Node name      = DR4300E-02
IP address (bond0) = 10.250.212.50
```

Please verify the above information is correct.

WARNING: This operation will destroy all data in the system!

Do you want to continue (y/n)?

Deleted CIFS user administrator.

Stopping Filesystem services... Done.

Updating configuration files... Done.

Cleaning diagnostics... Done.

Removing all Replication Snapshot(s)... Done.

Removing Seeding device mount... Done.

Shutting down all storage volumes... Done.

```
Securely Erasing Storage Volume: /dev/sdb5
-----
Pass: 1 ... 100%
Pass: 2 ... 100%
Pass: 3 ... 100%
```

```
Securely Erasing Storage Volume: /dev/sdc5
-----
Pass: 1 ... 100%
Pass: 2 ... 100%
Pass: 3 ... 100%
```

Securely Erased all Storage Volume(s)... Done.

Clearing data... Done.

Creating NVRAM Partitions... Done.

Initializing NVRAM... Done.

Create NVMFS... Done.

Initializing Dictionary... Done.

Resetting alert(s)... Done.

Verifying user accounts... Done.

Stopping xinetd:

[OK]

Starting xinetd:

[OK]

Restarting Filesystem services... Done.

Node successfully initialized.

```
Enable Default settings
-----
NTP enable... ok
```

```
NDMP set default login... ok - User exists
```

```
NDMP set default port... ok
```

```
NDMP enable... ok
```

Following is the sample output of Secure Erase with 1-pass.

Please enter the root password:

```
Node name      = dr6300-11
IP address (bond0) = 10.250.247.254
```

Please verify the above information is correct.

WARNING: This operation will destroy all data in the system!

Do you want to continue (y/n)?y

Deleted CIFS user administrator.

Stopping Filesystem services... Done.

Updating configuration files... Done.

Cleaning diagnostics... Done.

Removing all Replication Snapshot(s)... Done.



```

Removing Seeding device mount... Done.
Shutting down all storage volumes... Done.

Securely Erasing Storage Volume: /dev/sdb5
-----
Writing Pass: 1 ... 100%
Securely Erased all Storage Volume(s)... Done.
Clearing data... Done.
Creating NVRAM Partitions... Done.
Initializing NVRAM... Done.
Create NVMFS... Done.
Initializing Dictionary... Done.
Resetting alert(s)... Done.
Verifying user accounts... Done.
Stopping xinetd: [ OK ]
Starting xinetd: [ OK ]
Restarting Filesystem services... Done.

Node successfully initialized.

Enable Default settings
-----
NTP enable... ok
NDMP set default login... ok - User exists
NDMP set default port... ok
NDMP enable... ok

```

Following is the sample output of Secure Erase with 7-passes:

```

Please enter the root password:
Node name = DR4300e-05
IP address (bond0) = 10.250.208.107
Please verify the above information is correct.
WARNING: This operation will destroy all data in the system!
Do you want to continue (y/n)?y
Deleted CIFS user administrator.
Stopping Filesystem services... Done.
Updating configuration files... Done.
Cleaning diagnostics... Done.
Removing all Replication Snapshot(s)... Done.
Removing Seeding device mount... Done.
Shutting down all storage volumes... Done.
Securely Erasing Storage Volume: /dev/sdb5
-----

Writing Pass: 1 ... 100%
Writing Pass: 2 ... 100%
Writing Pass: 3 ... 100%
Writing Pass: 4 ... 100%
Writing Pass: 5 ... 100%
Writing Pass: 6 ... 100%
Writing Pass: 7 ... 100%
Securely Erased all Storage Volume(s)... Done.
Clearing data... Done.
Creating NVRAM Partitions... Done.
Initializing NVRAM... Done.
Create NVMFS... Done.
Initializing Dictionary... Done.
Resetting alert(s)... Done.
Verifying user accounts... Done.
Stopping xinetd: [ OK ]
Starting xinetd: [ OK ]
Restarting Filesystem services... Done.
Node successfully initialized.
Enable Default settings
NTP enable... ok
NDMP set default login... ok - User exists

```



```
NDMP set default port... ok
NDMP enable... ok
```

system --reboot

Description

Reboots a DR Series system when you provide the required “administrator” password for the system.

Syntax

```
system --reboot
```

Result

```
Please enter administrator password:
Broadcast message from root (pts/0) (Wed Jun 20 11:00:58 2012):
The system is going down for reboot NOW!
```

system --shutdown

Description

Shuts down a DR Series system when you use this command and provide the required password.

 **CAUTION:** The system --shutdown command powers off the appliance on which the DR Series system software is installed. Once the appliance is in a powered off state, you may only be able to power on the appliance in two ways: at its physical location, or by using an iDRAC connection on the network.

Syntax

```
system --shutdown
```

Result

```
Please enter administrator password:
Broadcast message from root (pts/0) (Wed Oct 20 11:00:58 2012):
The system is being shutdown NOW!
```

system --upgrade

Description

Upgrades the version of the DR Series system software installed on a supported DR Series hardware appliance.

Syntax

```
system --upgrade
```

-  **NOTE:** To obtain the latest DR Series system upgrade image, go to the Support website (support.quest.com/DR-Series), enter your service tag or select your product, and download the latest DR Series system software upgrade image file to the local system using WinSCP.
-  **NOTE:** Prior to performing a DR Series system CLI-based upgrade, make sure to download the DR Series system upgrade image. To initiate a DR Series system software upgrade for Windows users using the DR Series system CLI, the system software upgrade image file (in tar.gz format) is validated by the DR Series system, renamed to DRSeries_payload.tar.gz, and transferred to a directory/store location known to the DR Series system.

When you use the DR Series system CLI **system --upgrade** command, the DR Series system looks in this known directory/store location for the DRSeries_payload.tar.gz file, and starts the system software upgrade process.

-  **NOTE:** If the SSH session is lost for any reason during the upgrade process, this loss terminates the SSH session and also terminates the upgrade process that was running. If this SSH session loss occurs during an upgrade process and results in a terminated session, you should reboot the DR Series system and retry the system software upgrade process.



system --license [--validate] [--add]

Description

Validates and installs the license for the external data storage you can add using the expansion shelf enclosures to the base DR Series system. The expansion shelf licenses are based on the size of the expansion shelves; for details on expansion shelves, see [DR Series System Drive and System Capacities](#). There are two ways that expansion shelf licenses can be purchased: point of sale (POS) and after point of sale (APOS).

- POS licenses are those ordered from the factory with the DR Series system hardware appliance and the expansion shelf enclosures.
- APOS licenses are those ordered later separately for new expansion shelves or for existing Dell MD1200 storage arrays intended for use as expansion shelf enclosures.

 **NOTE:** The 300 Gigabyte (GB) drive capacity (2.7 TB) version of the DR Series system does not support the addition of expansion shelf enclosures.

There are two ways to obtain the expansion shelf enclosure license (license.xml):

- By downloading the license file from the Support website ([support.quest.com/DR-Series](#)), in which you enter your service tag or navigate to your DR Series system type, then click **Get Drivers**.
- By using an email link from Dell where the license file resides.

Once you have located the license file for expansion shelf enclosure use WinSCP to copy it to the /store/license, which is a location known by the DR Series system software.

 **NOTE:** Each added expansion shelf enclosure must be equal to or greater than each DR Series system internal drive slot capacity (0–11). Because 1 TB drives are the smallest ones supported by the expansion shelf enclosure you add, the 600 Gigabyte (GB) DR Series systems need to use 1 TB or larger sized drives in any expansion shelf enclosure added to the base system.

Syntax

```
system --license --validate
```

Result

License file is valid and can be installed.

To add a validated license for a data storage expansion shelf (enclosure), use the following DR Series system CLI command:

```
system --license --add  
License file has successfully installed.
```

 **NOTE:** The recommended process for adding an expansion shelf enclosure involves the following tasks:

- Use the **system --license [--validate] [--add]** command to validate and install the license for the expansion shelf enclosure.
- Power off (if needed) the Dell MD1200 storage array, physically connect the expansion shelf enclosure to the base DR Series system, and power on the expansion shelf enclosure.
- Use the **system --add_storage --enclosure** command (for specific information, see [system --add_storage --enclosure <service tag>](#)).

system --setname --name <node_name>

Description

Sets the hostname for a DR Series system.

Syntax

```
system --setname --name acme-60
```



Result

Successfully updated hostname.
Restarting syslog service ... done.

system --setdate [--date <date>] [--timezone <Region/Zone>]

Description

Sets the date and time zone on a DR Series system.

 **NOTE:** To set a date (month/day/hour/minute) for the DR Series system, enter values using the following format where the specifying of a four-digit year [[CC]YY] and seconds [.ss] are optional: MMDDhhmm [[CC]YY][.ss].

For example, September 29, 2011 13:20:00 can be entered in any of the following ways:

- 0929132012 and 092913202012: where 0929 represents September 29, 1320 represents 13:20 in a 24-hour time format, and 12 and 2012 both represent 2012.
- 0929132012.00 and 092913202021.00: where 0929 represents September 29, 1320 represents 13:20 in a 24-hour time format, 12 and 2012 both represent 2012, and .00 represents 13:20:00.

Syntax

 **NOTE:** Respond to the prompt to stop the NTP service by issuing a system --setntp --disable command.

```
system --setdate --date 092913202012 --timezone US/Pacific
```

Please stop NTP service before changing time.

```
system --setntp --disable
```

Result

```
Shutting down ntpd: [ OK ]
Fri Jun 29 13:20:00 PDT 2012

NTP service is already disabled.
Changed the time zone to US/Pacific
Thu Jun 29 13:20:00 PDT 2012
```

system --setntp [--add <server name>]

Description

Adds a new NTP server for use with the DR Series system.

Syntax

```
system --setntp --add 2.centos.pool.ntp.org
```

Result

```
Stopping NTP service ... Done
Adding NTP server ... Done
Starting NTP service ... Done
NTP server 2.centos.pool.ntp.org added.
```

Enter the following DR Series system CLI command to verify that the NTP server was successfully added:

```
system --show --ntp
```

```
NTP Service is      : UP
Server 1            : 0.centos.pool.ntp.org
Server 2            : 1.centos.pool.ntp.org
Server 3            : 2.centos.pool.ntp.org
```



system --setntp [--delete <server name>]

Description

Deletes an existing NTP server.

Syntax

```
system --setntp --delete 2.centos.pool.ntp.org
```

Result

```
Stopping NTP service ... Done  
Removing NTP server ... Done  
Starting NTP service ... Done  
NTP server 2.centos.pool.ntp.org deleted.
```

system --setntp [--enable]

Description

Enables the NTP service for your DR Series system.

Syntax

```
system --setntp --enable
```

Result

ntpd: Synchronizing with time server:	[OK]
Starting ntpd:	[OK]

To verify whether the NTP service was enabled, use the following command:

```
system --setntp --enable  
NTP service is already enabled.
```

system --setntp [--disable]

Description

Disables the NTP service for your DR Series system.

Syntax

```
system --setntp --disable
```

Result

```
Shutting down ntpd: [ OK ]
```

system --setntp [--adjust_time]

Description

Synchronizes a DR4000 system with the NTP server.

Syntax

```
system --setntp --adjust_time
```

Result

```
Time difference less than 2 seconds. Not adjusting with server  
0.centos.pool.ntp.org  
Time difference less than 2 seconds. Not adjusting with server  
1.centos.pool.ntp.org  
Time difference less than 2 seconds. Not adjusting with server  
2.centos.pool.ntp.org
```



system --setlogin

Description

Updates or resets the login password for the administrator of a DR Series system.

Syntax

```
system --setlogin
```

Result

```
Please enter administrator password:  
Please enter administrator's new password:  
Please re-enter administrator's new password:  
Changed administrator's password.
```

system --telnet [--enable | --disable]

Description

Displays the current telnet access status, or you can use the command options to enable or disable telnet access for a DR Series system.

Syntax

```
system --telnet
```

Result

```
Telnet State : Disabled
```

 **NOTE:** In this example, the system --telnet command output showed the telnet access status as disabled. The following example shows the command for enabling telnet access on your DR Series system. To disable telnet access, use the system --telnet --disable command.

```
system --telnet --enable  
Successfully enabled telnet.
```

system --datacheck --enable

Enables one or both Data Check scan options that can be used on a DR Series system. The enable option can be set to all, namespace, or blockmap. You can individually enable **namespace** or **blockmap** scan options, or both options using the **all** scan option (which means that both the **namespace** and **blockmap** scan types will be enabled).

Description

Enables an individual Data Check scan option type (or both scan types) when used in a DR Series system CLI command.

Syntax

```
system --datacheck [--enable <all | namespace | blockmap>]
```

Result

```
Data Check configuration successful: namespace and blockmap scans currently enabled.
```

 **NOTE:** This example shows all Data Check scan options enabled. To enable only the **namespace** or only the **blockmap** scan, use those options respectively in the DR Series system CLI command, for example, --enable --namespace, or --enable --blockmap.



system --datacheck --disable

Disables one or both Data Check scan option types that can be used on a DR Series system. You can individually disable **namespace** or **blockmap** scan options, or both options using the **all** scan option (which means that both the **namespace** and **blockmap** scan types will be disabled).

Description

Disables an individual Data Check scan option type (or both scan types) when used in a DR Series system CLI command.

Syntax

```
system --datacheck [--disable <all | namespace | blockmap>]
```

Result

Data Check configuration successful: all scans currently disabled.

 **NOTE:** This example shows all Data Check scan options being disabled. To disable only the **namespace** or the **blockmap** scan, use those options respectively in the DR Series system CLI command, for example, **--disable --namespace**, or **--disable --blockmap**.

system --datacheck --throttle

Use the Data Check **--throttle** option to specify the percentage of available DR Series system resources you want to use when running Data Check scans when the other system operations (data ingest, Replication, and Cleaner processes) are idle. The range is between 1 to 100 percent (%), and the default is 50%.

Description

Enables Data Check scans to use any percentage (1–100) of available DR Series system resource that you define. In this example, 75% of the available DR Series system resources are selected.

Syntax

```
system --datacheck [--throttle <1-100>]
```

Result

Data Check configuration successful: throttle set to 75%.

system --marker [--enable] [--disable]

Description

Enables or disables the marker detection status for all of the supported backup software used with a DR Series system based on the option you use with the command.

Syntax

```
system --marker
```

Result

Please enter either **--enable** or **--disable** to change system-level marker settings.

For more information about enabling or disable marker detection settings on a DR Series system, see [system --marker \[--enable\]](#) or [system --marker \[--disable\]](#).



 NOTE: To display the current status of the marker detection settings, use the DR Series system CLI command:

```
system --show --marker
```

```
Marker Detection : Enabled
```

system --verify_on_read [--enable] [--disable]

Description

Enables or disables data verification on read.

Syntax

```
system --verify_on_read --enable
```

Result

Verification of read data Enabled.

system --add_storage --enclosure <service tag>

Description

Adds a data storage expansion shelf (enclosure) to a DR Series system. Each expansion shelf that is added to a DR Series system requires an individual service tag and a license. For information about the maximum allowable expansion shelves and their capacities, see the *DR Series System Interoperability Guide* and the *DR Series System Administrator Guide* at support.quest.com/DR-Series.

 NOTE: The 300 Gigabyte (GB) drive capacity (2.7 TB) version of the DR Series system does not support the addition of expansion shelf enclosures.

For more information about the required licenses, see [system --show \[-license\] \[--verbose\]](#) and [system --license \[-validate\] \[--add\]](#).

 NOTE: The recommended process for adding an expansion shelf enclosure involves the following tasks:

- Use the `system --license [-validate] [--add]` command to validate and install the license for the expansion shelf enclosure. For specific information, see [system --license \[-validate\] \[--add\]](#).
- Power off (if needed) the Dell MD1200 storage array, physically connect the expansion shelf enclosure to the base DR Series system, and power on the expansion shelf enclosure.
- Use the `system --add_storage --enclosure <service tag>` command .

 NOTE: Each added expansion shelf enclosure must be equal to or greater than each DR Series system internal drive slot capacity (0–11). Because 1 TB drives are the smallest one supported by the expansion shelf enclosure you add, the 600 Gigabyte (GB) DR Series system needs to use 1 TB or larger sized drives in any expansion shelf enclosure added to the base system.

 NOTE: To verify the current types of storage on a DR Series system, use the DR Series system CLI command: `system --show --storage`. For more information, see [system --show \[-storage\]](#).

Syntax

```
system --add_storage --enclosure CTKHVW1
```

Result

WARNING: IO to the box will be stopped during enclosure addition.

```
Do you want to continue (yes/no) [n]? y  
Enclosure: "CTKHVW1" added successfully.
```



system --storage [--set_usage_alert <70% - 90%>]

Description

Used to specify at what storage utilization percentage an alert should be sent.

Syntax

```
system --storage --set_usage_alert 90
```

Result

System storage usage alert has been set at 90%.

system --storage [--blink] [--type <internal | external>] [--service_tag <service tag>] [--disk <slot num>]

Description

Turns on an LED that is used in locating a specific physical disk or data storage expansion shelf (using the **system --storage** command) in the DR Series system. Select from the following DR Series system CLI command options:

- **--blink**: turns on LED on the physical disk or expansion shelf to identify it.
- **--type <internal | external>**: identifies storage as an internal physical disk or external expansion shelf.
- **--service_tag <service tag>**: identifies physical disk or expansion shelf by its unique service tag.
- **--disk <slot num>**: identifies the disk slot number (if no disk slot is defined, it globally affects all disks).

 **NOTE:** There is a counterpart to this command, in which you can turn off the LED that aids in locating the physical disk or expansion shelf. For more information, see [system --storage \[--unblink\] \[--type <internal | external>\] \[--service_tag\] \[--disk <slot num>\]](#).

 **NOTE:** The above options are only available on a Physical DR.

Syntax

```
system --storage --blink --type external --service_tag HCM0PT3
```

Result

Turned on blinking for all disks in enclosure "HCM0PT3".

system --storage [--unblink] [--type <internal | external>] [--service_tag <service tag>] [--disk <slot num>]

Description

Turns off an LED that is used in locating a specific physical disk or data storage expansion shelf (using the **system --storage** command) in the DR Series system. Select from the following DR Series system CLI command options:

- **--unblink**: turns off LED on the physical disk or expansion shelf.
- **--type <internal | external>**: identifies storage as an internal physical disk or external expansion shelf.
- **--service_tag <service tag>**: identifies physical disk or expansion shelf by its unique service tag.
- **--disk <slot num>**: identifies the disk slot number (if no disk slot is defined, it globally affects all disks).

 **NOTE:** The above options are only available on a Physical DR.

Syntax

```
system --storage --unblink --type external --service_tag CTKHVW3
```

Result

Turned off blinking for all disks in enclosure "CTKHVW3".



system --mgmt_traffic

Description

The command configures Webserver or Telnet to use a specific network interface.

Syntax

```
system --mgmt_traffic [--add] [--type <Webserver|Telnet>] [--interface <bondN|  
ethN|lo>]  
                           [--update] [--type <Webserver|Telnet>] [--interface <bondN|  
ethN|lo>]  
                           [--delete] [--type <Webserver|Telnet>]  
  
--add          Add access network configuration.  
--update       Update access network configuration.  
--delete       Delete access network configuration.  
--type         Access type <Webserver|Telnet> to configure.  
--interface   Interface to use for access [bond(0-N)|eth(0-N)].
```

Result

```
Successfully added application webserver.  
Restarting webserver service ... done.
```

system --backup_traffic

Description

The command specifies the network interfaces to use for backup network traffic.

Syntax

```
system --backup_traffic [--add] [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI>] [--  
interface <bond(0-N)|eth(0-N)>]  
                           [--update] [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI>] [--interface  
<bond(0-N)|eth(0-N)>]  
                           [--delete] [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI>]  
  
--add          Add backup network configuration.  
--update       Update backup traffic network configuration.  
--delete       Delete backup traffic network configuration.  
--type         Backup traffic type [NFS|CIFS|OST|RDS|NDMP|ISCSI] to  
configure.  
--interface   Interface to use for backup traffic.
```

Result

```
WARNING: This operation requires filesystem server restart. IO to the box will  
be stopped.  
Do you want to continue (yes/no) [n]? y  
Successfully added application.  
Restarting file system ... done.
```

system --replication_traffic

Description

The command sets the default network interface for replicating 'source' data.

Syntax

```
system --replication_traffic [--add] [--interface <bondN|ethN|lo>]  
                           [--update] [--interface <bondN|ethN|lo>]  
                           [--delete]
```



```
--add          Add default replication network configuration.  
--update       Update default replication network configuration.  
--delete        Delete default replication network configuration.  
--interface    Interface to use for replicating 'source' data.
```

For example, to add the replication, run the command, system --replication_traffic --add --interface bond0

Result

Successfully added application replication.

system --opdup_traffic

Description

The command sets the default network interfaces for optimized copy data transfer.

Syntax

```
system --opdup_traffic [--add] [--incoming_interface <bondN|ethN|lo>] [--  
outgoing_interface <bondN|ethN|lo>]  
                           [--update] [--incoming_interface <bondN|ethN|lo>] [--  
outgoing_interface <bondN|ethN|lo>]  
                           [--delete]  
  
                           --add          Add default optimized copy configuration.  
                           --update       Update default optimized copy configuration.  
                           --delete        Delete default optimized copy configuration.  
                           --incoming_interface   Interface to use for receiving optimized copy  
data.  
                           --outgoing_interface   Interface to use for sending optimized copy data.
```

For example, to add the default network interface for incoming traffic, run the command: system --opdup_traffic --add --incoming_interface bond0

Result

Successfully added application opdup_incoming.

system --support_agent --register

Description

Registers the current DR Series system with the Support Portal. If the administrator address is not configured, you will be prompted to enter one when you run this command.

After you run this command, an email message is sent to the DR Series administrator email address that provides further instructions for completing the registration process. The registered DR Series system will collect certain information that it will transmit to Quest Support. Such information can include operational statistics, performance metrics, diagnostic information and configuration settings of the DR Series system. This enables support personnel to monitor and capture information to proactively help troubleshoot issues with your system.

Syntax

```
system --support_agent --register
```

Result

Admin email address is not configured !!

Enter the email address to where the registration email should be sent :
customer@company.com



Registration has been initiated! An email with a registration link is sent to customer@company.com. Please use the following private code to finish registration.

public code is: EOC227private code is: WJ5ZX

system --support_agent --unregister

Description

Unregisters the current DR Series system from the Support Portal.

Syntax

```
system --support_agent --unregister
```

Result

system --support_agent --stats

Description

Displays statistics of the registered DR Series system.

Syntax

```
system --support_agent --stats
```

Result

system --support_agent --status

Description

Displays the current status of the registered DR Series system.

Syntax

```
system --support_agent --status
```

Result

system --help

Description

Displays the list of all system-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
system --help
```

Result

Usage:

```
    system --show [--config]
                  [--hardware]
                  [--storage] [--type <boot|internal|external>] [--service_tag
<service tag>]
                  [--license] [--verbose]
                  [--ntp]
                  [--version]
                  [--timezones [Region]]
                  [--upgradefile]
                  [--upgradehistory]
                  [--marker]
                  [--verify_on_read]
                  [--replication_traffic]
                  [--opdup_traffic]
```



```

[--backup_traffic]
[--mgmt_traffic]

system --reboot
system --shutdown
system --upgrade
system --license [--add]

system --setname --name <node_name>

system --setdate [--date <date>]
[--timezone <Region/Zone>]

system --setntp [--add <server name>]
[--delete <server name>]
[--enable]
[--disable]
[--adjust_time]

system --setlogin
system --telnet [--enable | --disable]

system --datacheck [--enable <all|namespace|blockmap>]
[--disable <all|namespace|blockmap>]
[--throttle <1-100>]

system --marker [--enable]
[--disable]

system --verify_on_read [--enable]
[--disable]

system --add_storage --enclosure <service tag>

    system --storage [--blink] [--type <internal|external>] [--service_tag <service tag>] [--disk <slot num>]
        [--unblink] [--type <internal|external>] [--service_tag <service tag>] [--disk <slot num>]

    system --mgmt_traffic [--add] [--type <Webserver|Telnet>] [--interface <bondN|ethN|lo>]
        [--update] [--type <Webserver|Telnet>] [--interface <bondN|ethN|lo>]
        [--delete] [--type <Webserver|Telnet>]

    system --backup_traffic [--add] [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI|FC>] [--interface <bond(0-N)|eth(0-N)|lo>]
        [--update] [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI|FC>] [--interface <bond(0-N)|eth(0-N)|lo>]
        [--delete] [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI|FC>]

    system --replication_traffic [--add] [--interface <bondN|ethN|lo>]
        [--update] [--interface <bondN|ethN|lo>]
        [--delete]

    system --opdup_traffic [--add] [--incoming_interface <bondN|ethN|lo>]
    [--outgoing_interface <bondN|ethN|lo>]
        [--update] [--incoming_interface <bondN|ethN|lo>] [--outgoing_interface <bondN|ethN|lo>]
        [--delete]

system --help

system <command> <command-arguments>
<command> can be one of:
    --show          Displays command specific information.
    --reboot        Reboots the machine.

```



```

        --shutdown          Shuts down the machine.
        --upgrade           Upgrades the software on the machine.
        --license            Installs the license on the machine.
        --setname             Sets the name of the machine.
        --setdate             Sets the date and time zone for the
machine.
        --setntp              Uses network time protocol (NTP) source
to update time.
        --setlogin            Updates the login password.
        --telnet              Enables or disables telnet access.
        --datacheck            Enables or disables online data
verification features.
        --marker               Enables or disables markers.
        --verify_on_read       Enables or disables
data verification on read
        --add_storage          Adds an expansion shelf.
        --storage              Locates a disk or expansion shelf.
        --mgmt_traffic         Configure Webserver or Telnet to use a
specific network interface.
        --backup_traffic        Specify network interfaces to use for
backup network traffic.
        --replication_traffic Set default network interface for
replicating 'source' data.
        --opdup_traffic        Set default network interfaces for
optimized copy data transfer.

For command-specific help, please type system --help <command>
eg:
    system --help show

```

User

This topic introduces the DR Series system CLI commands that allow you to manage user accounts by enabling or disabling user accounts, adding and updating users, setting passwords, deleting users, and displaying the list of current active user accounts logged in to a DR Series system.

User Command Usage

This topic introduces the **user** command usage:

- **user --show [options]**
- **user --enable --user [options]**
- **user --disable --user [options]**
- **user --add --name [options]**
- **user --update --name [options]**
- **user --delete --name**
- **user --setpassword --name**
- **user --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

user --show [--users] [--logins] [--verbose][--name <username>] [--roles <cifs|ost|rda|ndmp|iscsi|monitor|administrator|email_recipient>

Description

Displays the current status of the service and root user accounts (using the **user --show --users** command), and also displays the login types and login times on a DR Series system (using the **user --show --logins** command).

Syntax

```
user --show --users
```

Result

Service Account	:	Disabled
Root Account	:	Enabled
User Name	:	backup_user
User Roles	:	OST,RDA
User Name	:	administrator
User Roles	:	administrator,CIFS
User Name	:	iscsi_user
User Roles	:	ISCSI
User Name	:	ndmp_user
User Roles	:	NDMP

Other Examples

Displays the current status of login attempts on a DR Series system.

```
user --show --logins
User Name      Terminal    Login Time
root          pts/1        Oct 24 10:51 (10.15.13.4)
root          pts/2        Oct 23 20:41 (10.18.0.1)
root          pts/3        Oct 23 20:41 (10.15.0.13)
root          pts/5        Oct 24 09:35 (10.20.21.6)
administrator  pts/6        Oct 24 12:32 (acme13.storage.local)
root          pts/7        Oct 24 12:24 (10.18.11.12)
```

user --enable --user <service | root>

Description

Enables the service or root user account on a DR Series system.

Syntax

```
user --enable --user root
```

Result

"root" user enabled.

 **NOTE:** To enable the service user account instead of the root user account, simply substitute the service option with the --user option, as shown in the following example:

```
user --enable --user service
```

 **NOTE:** If root user or service user is enabled, it gets disabled after a reboot. You must enable it again, if required.

user --disable --user <service | root>

Description

Disables the service or root user account on a DR Series system.

Syntax

```
user --disable --user root
```

Result

"root" user disabled.



 **NOTE:** To disable the service user account instead of the root user account, simply substitute the service option with the --user option, as shown in the following example:

```
user --disable --user service
```

user --add --name <user name>

Description

Adds a user account with the specified username.

Syntax

```
user --add --name Test_User
```

Result

Enter new password:

Re-type password:

User "Test_User" created successfully.

```
user --update --name <user name> [--new_name <user name>] [--add_roles <cifs|ost|rda|ndmp|iscsi|monitor|email_recipient>] [--remove_roles <cifs|ost|rda|ndmp|iscsi|monitor|email_recipient>] [--full_name <full name>] [--phone <phone number>] [--email_addr <email address>] [--description <description>]
```

Description

Updates a specified user account. You can update the username, add roles to or remove roles from the account, add information such as full name, phone number, email address, or description.

Syntax

```
user --update --name Test_User --new_name Test_User2 --add_roles ndmp
```

Result

Successfully updated User Test_User.

user --delete --name <user name>

Description

Deletes the specified user account.

Syntax

```
user --delete --name Test_User2
```

Result

User "Test_User2" has been deleted.

user --setpassword --name <user name>

Description

Sets a password for the specified user account.

Syntax

```
user --setpassword --name Test_User2
```



Result

```
Enter new password:  
Re-type password:  
Successfully updated User Test_User2.
```

user --help

Description

Displays the list of all user-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
user --help
```

Result

```
Usage:  
    user --show [--users]  
                [--logins]  
                [--verbose]  
                [--name <user name>]  
                [--roles <cifs|ost|rda|ndmp|iscsi|monitor|administrator|  
email_recipient>  
  
    user --enable --user <service | root>  
  
    user --disable --user <service | root>  
  
    user --add --name <user name>  
                [--roles <cifs|ost|rda|ndmp|iscsi|monitor|email_recipient>]  
                [--full_name <full name>]  
                [--phone <phone number>]  
                [--email_addr <email address (e.g., name@company.com)>]  
                [--description <anything>]  
  
    user --update --name <user name>  
                [--new_name <user name>]  
                [--add_roles <cifs|ost|rda|ndmp|iscsi|monitor|email_recipient>]  
                [--remove_roles <cifs|ost|rda|ndmp|iscsi|monitor|email_recipient>]  
                [--full_name <full name>]  
                [--phone <phone number>]  
                [--email_addr <email address (e.g., name@company.com)>]  
                [--description <anything>]  
  
    user --delete --name <user name>  
  
    user --setpassword --name <user name>  
  
    user --help  
  
user <command> <command-arguments>  
<command> can be one of:  
  
    --show           Displays command specific information.  
    --enable         Enables a user account.  
    --disable        Disables a user account.  
    --add            adds a user account.  
    --update         updates a user account.  
    --delete         delete a user account.  
    --setpassword    sets password to a user account.
```

For command-specific help, please type user --help <command>

For example:



```
user --help show
```

Virtual Machine

This topic introduces the DR Series system CLI commands that allow you to manage the virtual machines (VMs) that are registered to your physical DR Series system hardware appliance. At least one physical DR is required to act as the license server for your VM(s). A VM only needs to be licensed to one physical DR (even if you have more than one physical DR in your environment).

- `virtual_machine --show [options]`
- `virtual_machine --delete [options]`
- `virtual_machine --update [options]`
- `virtual_machine --register [options]`
- `virtual_machine --unregister [options]`
- `virtual_machine --help`

Virtual Machine Command Usage

This topic introduces the virtual machine command usage for managing the Virtual Machines that are registered to your physical DR.

- `virtual_machine --show [options]`
- `virtual_machine --update [options]`
- `virtual_machine --register [options]`
- `virtual_machine --unregister [options]`
- `virtual_machine --delete [options]`
- `virtual_machine --help`

`virtual_machine -- show [--service_tag <service tag>]`

Description

Displays the list of all DR2000v systems registered to the physical machine against which the command is run.

Syntax

```
virtual_machine --show
```

Result

SERVICE TAG	IP ADDRESS	HOSTNAME	CAPACITY (TB)
DR4xVM1-07	10.250.209.254	DR2000v-01.acme.local	2
DR4xVM1-08	10.250.209.255	DR2000v-02.acme.local	2
DR4xVM1-09	10.250.208.232	DR2000v-03.acme.local	1

`virtual_machine --show --summary`

Description

This command is used to display the number of DR2000v licenses consumed and available for a given capacity.

 **NOTE:** This command is applicable only to the DR Series system hardware appliances: DR4000/DR4100/DR6000/DR4300e/DR4300/DR6300.

Syntax

```
virtual_machine --show --summary
```

Result

```
-----  
Capacity  VMsRegistered  LicensesAvailable
```



1TB	2998	2
2TB	17	57
4TB	3	319

virtual_machine --update [--host <ip address | hostname>] [--name <administrator name> [--email <email address>] [--company <company name>] [--comments <comments>]

Updates the host IP address and hostname for the virtual machine.

Syntax

```
virtual_machine --update --host DRhostname1 --name admin --email
name@company.com
```

Results

Successfully updated DR2000v details in server.

virtual_machine --register [--host <ip address| hostname>] [--name <administrator name> [--email <email address>] [--company <company name>] [--comments <comments>]

Registers the virtual DR Series system to the host IP address and hostname.

Syntax

```
virtual_machine --register --host DR_hostname1 --name admin
```

Results

DR2000v registered successfully.

virtual_machine --unregister [--force]

Unregisters the virtual DR Series system from a physical DR Series system.

Syntax

```
virtual_machine --unregister [--force]
```

virtual_machine --delete --service_tag <service tag>

Description

Un-registers a DR2000v based on the specified service tag.

Syntax

```
virtual_machine --delete --service_tag DR4xVM1-09
```

Result

Please enter the administrator password:

WARNING: This command will delete the DR2000v registration!

Do you want to continue? (yes/no) [n]? yes

DR2000v(DR4xVM1-09) deleted successfully.



Maintaining the DR Series System

This topic introduces the CLI commands that are useful for collecting diagnostics information, and managing the filesystem and performing system maintenance-related tasks. These CLI commands are grouped into two categories:

- The **Diagnostics** command and its options are used to collect DR Series system log file information. For more information, see [Diagnostics](#).
- The **Maintenance** command and its options are used to perform filesystem and system maintenance. For more information, see [Maintenance](#).

Diagnostics

The DR Series system CLI **Diagnostics** command lets you display, collect, and manage the diagnostic log file information for your system, which provides these benefits:

- Captures a snapshot of the current state of DR Series system operations.
- Assists Technical Support personnel to understand the sequence of DR Series system operations.
- Records DR Series system operations in the event that Technical Support needs to provide technical assistance.

The **Diagnostics** command works by collecting all system-related information that assists in understanding system operations when diagnosing a problem or error condition in the DR Series system.

The Diagnostics service runs during system startup, and listens for incoming requests sent to the DR Series system. There are two modes in which the diagnostics collection process is started:

- **Admin-Generated Mode:** when a DR Series system CLI or GUI request is made by the administrator (and the default reason is listed as admin-generated).
- **Auto-Generated Mode:** when a process or service failure is reported, the DR Series system starts collecting a wide variety of system-related information. After a successful completion of the auto-generated collection, the DR Series system also generates a system event.

 **NOTE:** Use the `alerts --show --events` or the `alerts --show --alerts` command to display or check the current events or alerts.

The Diagnostics service stores all log information in a primary log directory, and the DR Series system also maintains a backup copy of each log in a separate, secondary log directory. After each new diagnostics log is collected, the Diagnostics process computes the sizes of each of these two log location directories.

Whenever a log directory exceeds its maximum storage capacity, the oldest logs are deleted to free up space for the current logs that the DR Series system generates.

 **NOTE:** Diagnostics that you run from the GUI will run the largest bundle collection routine (the equivalent of running `diagnostics --collect --all` from the CLI). If you want to reduce the bundle collection time and file size for individual files and small bundle collection, see the options in the topics that follow.

Diagnostics Command Usage

This topic introduces the **diagnostics** command usage:

- `diagnostics --show`

- **diagnostics --collect [options]**
- **diagnostics --delete [options]**
- **diagnostics --copy [options]**
- **diagnostics --start-service**
- **diagnostics --help**

 NOTE: If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

diagnostics --start-service

Description

This command can be used to start diagnostics services if they are not running. Typically, diagnostics services will be running; if, however, the system services did not start and diagnostics need to be collected, this command can be used.

Syntax

```
diagnostics --start-service
```

Result

Diagnostics service started successfully.

diagnostics --show

Description

Displays a list of the diagnostics log files, by filename, size, status, and reason for generation. The diagnostics log files are a collection of all DR Series system-related information that describe the current state of your system.

Syntax

```
diagnostics --show
```

Result

Filename	Size	Timestamp
Status	Reason	

```
diags_2012-06-17_09-30-51.lzip 23.3MB Sun Jun 17 16:33:12 2012 Completed
```

[admin-generated] :

generated by Administrator

```
acme_2012-06-20_11-39-43.lzip 36.9MB Wed Jun 20 11:34:04 2012  
Completed
```

[auto-generated] :

Service(s) "ofsck" failed

diagnostics --collect

Description

Generates a new diagnostics log file that represents the current state of a DR Series system. This command option is only available in the CLI.

The resulting bundle has subsets of log files and cores (if they exist) but does not include a DSET report. A DSET can be obtained with the entire bundle by using the **--all** option, or separately by using the **--dset** option.



If a DSET report is not required, running the **--collect** command can save 5 to 10 minutes from the log collection process. If core dumps exist on the system, file size can be affected by system memory capacity.

Syntax

```
diagnostics --collect
```

Result

```
Collecting diagnostics...done.  
Diagnostics file acme9_2011-11-17_17-15-52.lzip created.
```

 **NOTE:** To check how many diagnostic log files have been recently generated, enter the following commands at the system prompt:

```
pwd  
/home/administrator  
  
ls  
acme9_2012-07-18_09-48-26.lzip  
acme9_2012-07-18_10-34-48.lzip  
acme9_2012-07-25_14-09-15.lzip  
acme9_2012-07-30_14-35-30.lzip  
acme9_2012-07-30_15-25-59.lzip
```

diagnostics --collect [--name <name>]

Description

Defines a specific name for the diagnostics file you want to generate using the **--name** option with the DR Series system CLI **diagnostics --collect** command.

Syntax

```
diagnostics -collect --name diag_acme99_10-02-12
```

Result

```
Collecting diagnostics...done.  
Diagnostics file diag_acme99_10_02_12.lzip created.
```

diagnostics --collect [--reason <reason>]

Description

Defines a specific reason for generating a diagnostics file for the DR Series system using the **--reason** option with the DR Series system CLI **diagnostic --collect --name** command.

Syntax

```
diagnostics --collect --name acme9_09_17_12 --reason check-operations
```

Result

```
Collecting diagnostics...done.  
Diagnostics file acme9_09_17_12.lzip created.
```

diagnostics --collect [-force]

Description

Forces an immediate generation of a diagnostics file that collects your current system information using the **--force** option with the DR Series system CLI **diagnostic --collect --name** command.

 **NOTE:** Use the DR Series system CLI **diagnostics --force** command when you want to override any existing system operations to generate a diagnostics log file immediately because it is a priority.



Syntax

```
diagnostics --collect --force
```

Results

```
Collecting diagnostics...done.  
Diagnostics file acme9_2012-09-15_13-53-57.lzip created.
```

diagnostics --collect [--dset]

Description

Collects the current system hardware diagnostics information that may be needed by Technical Support personnel using the **--dset** (E-Support Tool) option with the DR Series system CLI **diagnostics --collect** command.

The DSET log lets you collect hardware, storage, and operating system information from the DR Series system hardware appliance. This information is consolidated into a single System Configuration Report that can be used for troubleshooting or inventory collection of a system. As part of the troubleshooting process, you may be asked to provide a DSET log when you contact Technical Support.

The DSET log file is valuable to have when a smaller file is required and system hardware or firmware needs to be evaluated. This will generally take between 5 and 10 minutes.

Syntax

```
diagnostics --collect --dset
```

Result

```
Collecting diagnostics...  
DSET collection might take about 10 minutes. Please wait...done.  
Diagnostics file dset_2012-09-18_09-28-03.zip created.
```

diagnostics --collect [--logs]

Description

The command collects only logs and system configuration. Use the **--logs** option if a current system state is needed, but file size needs to be smaller for FTP transfer to Technical Support. The **--logs** option puts the current system configuration in the smallest file containing most of what Technical Support needs to start an investigation. File size can be reduced by eliminating core dumps, DSET reports, and archive files.

Syntax

```
diagnostics --collect --logs
```

Result

```
Collecting diagnostics...done.  
Diagnostics file created.
```

diagnostics --collect [--cores]

Description

The command collects only cores. Use this option if a basic bundle already exists and Technical Support only requires new core files. After the core files are collected, they are deleted from the DR Series system.

Syntax

```
diagnostics --collect --cores
```

Result

```
Collecting diagnostics...done.  
Diagnostics file created.
```



diagnostics --collect [--tcpdump]

Description

The command collects only TCP dump reports. TCP dumps may be generated by Technical Support if network troubleshooting is being performed. If a TCP dump is present on the system, run the **diagnostics --collect --tcpdump** command to collect the TCP dump reports without collecting an entire bundle. This reduces file size.

Syntax

```
diagnostics --collect --tcpdump
```

Result

Collecting diagnostics...done.
Diagnostics file created.

diagnostics --collect [--process_dump]

Description

The command collects the file system server dump. This file is only needed if Technical Support requests process dumps.

Syntax

```
diagnostics --collect --process_dump
```

Result

Collecting diagnostics...done.
Diagnostics file created.

diagnostics --collect [--all]

Description

Collects all of the current system information (including --dset) that may be needed during any inventory collection or troubleshooting with the DR Series system. The resulting file can vary between 500MB and 15GB and includes the following:

- Old diagnostics bundles
- Core dumps
- Large archive files
- DSET reports
- Other smaller valuable log files

It will take more than 10 minutes to collect the bundle. If diagnostics are run from the GUI, the **diagnostics --collect --all** is the equivalent command in the CLI.

Syntax

```
diagnostics --collect --all
```

Result

Collecting diagnostics...done.
Diagnostics file dr8-interop-a7_2016-12-11_23-54-17.lzip created

diagnostics --delete [--name <name>]

Description

Deletes a specific existing diagnostics log file by name when using the **--name** option with the DR Series system CLI **diagnostics --delete** command.



Syntax

```
diagnostics --delete --name dr8-interop-a7_2016-12-11_23-54-17.lzip
```

Result

Diagnostics delete: Successful

diagnostics --delete [--all]

Description

Deletes all of the diagnostics files on a DR Series system when using the **--all** option with the DR Series system CLI **diagnostics --delete** command.

 **CAUTION: Carefully consider before using the DR Series system CLI --delete --all command to delete all current diagnostics log files on a DR Series system. If you delete all diagnostics log files without first saving them to another location, all previous system status information that they contained is lost and unrecoverable.**

Syntax

```
diagnostics --delete --all
```

Result

Diagnostics delete: Successful

diagnostics --copy --name <name> --host <user@host | ip:>:<path>>

Description

Copies a specific existing diagnostics log file by name, by appending the **--name** option, and sends this diagnostics log file to a remote system that you can define using the DR Series system CLI **diagnostics --name** and **--host** command (by defining a destination hostname or IP address and path).

Syntax

```
diagnostics --copy --name dr8-interop-a7_2016-12-05_23-01-56_basic.lzip --host
administrator@10.250.207.20:
/var/diagnostics_logs
```

Result

```
administrator@10.250.207.20's password:
dr8-interop-a7_2016-12-05_23-01-56_basic.lzip 100% 297MB 49.5MB/s
00:06 Diagnostics copy: Successful
```

diagnostics --help

Description

Displays the list of all diagnostics-related options that can be used when using the DR Series system CLI.

Syntax

```
diagnostics --help
```

Result

Usage:

```
    diagnostics --show
    diagnostics --collect [--name <name>]
        [--reason <reason>]
        [--force]
        [--dset]
        [--logs]
        [--cores]
        [--tcpdump]
```



```

[--process_dump]
[--all]

diagnostics --delete [--name <name>]
[--all]

diagnostics --copy --name <name>
--host <user><host|ip>:<path>>

diagnostics --help

diagnostics <command> <command-arguments>
<command> can be one of:
    --show      Displays all current diagnostic log files.
    --collect   Collects diagnostic information/creates log file
for support.
    --delete    Deletes one or all existing diagnostic log files.
    --copy      Copies an existing diagnostic log file to a remote
machine.
    --start-service Starts diagnostics service.

```

For command-specific help, please type `diagnostics --help <command>`

eg:

`diagnostics --help show`

Maintenance

The DR Series system CLI **maintenance** commands lets you display the system maintenance repair progress, and manage the data repair and state of a DR Series system. Maintenance tasks let you perform basic repairs and maintain the data and the DR Series system.

 **NOTE: Whenever the DR Series system enters or exits from the Maintenance mode state, all communication via CIFS, NFS, OST, or RDS is lost.**

The set of **maintenance** commands and options should only be used when the DR Series system is in the **Maintenance** mode state. You should contact Technical Support before performing any of these DR Series system CLI commands.

The **--filesystem** commands perform maintenance operations on the DR Series system file system, the **--configuration** commands perform a backup and restore of the system configuration, the **--hardware** commands manage the appliance hardware, the **--disk** commands manage the system disk drives, and the **--vdisk** commands manage the virtual disk drives.

 **NOTE: This set of maintenance commands provide some functionality that is not available in the DR Series system GUI. To check the status of the DR Series system, use the DR Series system CLI system --show command to display the current status.**

Maintenance Command Usage

This topic introduces the **maintenance** command usage:

 **NOTE: Using some of the maintenance command options could result in the deletion of data. Carefully observe the warnings (for example, running the scan without running the repair). If you have questions, do not perform these DR Series system CLI command options without first contacting Technical Support.**

- **maintenance --filesystem [options]**
- **maintenance --configuration [options]**
- **maintenance --hardware [options]**
- **maintenance --disk [options] (Option only available on a Physical DR)**
- **maintenance --remote_access [options] (Option only available on a Physical DR)**
- **maintenance --vdisk --check_consistency --type [options] (Option only available on a Physical DR)**



- **maintenance --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you are prompted to provide the correct value or option.

maintenance --filesystem [--start_scan [verify_data | verify_rda_metadata | verify_metadata] [--storage_group <name>]

Description

Starts filesystem checker to check for consistency issues in storage groups.

 **NOTE:** Argument **verify_data** validates data with pre-built checksum. Argument **verify_rda_metadata** scans only OST and RDA containers. Argument **verify_metadata** scans the namespace for all containers.

 **NOTE:** Using this command places the files system into a read-only mode and pauses all active replications. When the DR Series system enters Maintenance mode, an alert is sent that indicates this operational change.

Syntax

```
maintenance --filesystem --start_scan verify_data --storage_group SGTest1
```

Result

This operation will make the filesystem read-only and pause all active replications.

"**verify_data**" option will check for data consistency issues in the filesystem.

This might take long time to complete.

Do you want to continue (yes/no) [n] ? y

Please enter the administrator password:

Filesystem check started successfully.

To see the status, please execute "maintenance --filesystem --scan_status".

If you enter the **maintenance --filesystem --scan_restart** command when the DR Series system is not in **Maintenance** mode, the following output is displayed at the system prompt:

```
maintenance --filesystem --scan_restart
```

"Operation not supported as system is not in maintenance mode.

To be able to restart scan, filesystem check must be running or waiting".

maintenance --filesystem [--stop_scan]

Description

Stops the filesystem scan process that verifies the data contained in a DR Series system.

Syntax

```
maintenance --filesystem --stop_scan
```

Result

This operation will stop the filesystem checker and put the system back into operational mode.

Do you want to continue (yes/no) [n] ? y

Please enter the administrator password:

Filesystem check stopped successfully.

maintenance --filesystem [--scan_status]

Description

Displays the current filesystem checker status and scan progress for a DR Series system.



Syntax

```
maintenance --filesystem --scan_status
```

Result

```
Filesystem checker : Scan in progress
Filesystem check status:
DataBlock Consistency Checker Stats
=====
Phase : INODE CRAWL
Inode check : IN PROGRESS
Inodes processed : 3200 / 3498
Time left (approx) : 4 secs
Cont Name TotalInodes Checked Corrupted Missing Data
Orphan Status
-----
backup 0 0 0 COMPLETED
container29 0 0 0 COMPLETED
backupsys-60_replicate 71826
71826 0 0 0 COMPLETED
Data block check : COMPLETED
Data blocks processed : 422 / 422
Corrupted data chunks : 0
Data chunk refcount mismatch : 0
Recomputed bytes out : 1383308872
Recomputed bytes in : 6107833613
Recomputed % Savings : 77.351890%
Time left (approx) : 0
Data block check : NOT STARTED
NameSpace Consistency Checker Stats
=====
Namespace check : NOT STARTED
```

maintenance --filesystem [--scan_report [verbose]]

Description

Displays the current filesystem checker report, which is generated by the DR Series system CLI **--start_scan** command.

Syntax

```
maintenance --filesystem --scan_report
```

Result

```
Filesystem check report
=====
Report generated at : Fri Dec 9 08:23:05 2016
```

There are no problems detected.

maintenance --filesystem [--repair_status [verbose]]

Description

Displays the current filesystem repair progress for a DR Series system.

 **NOTE:** If there is no repair status to report, the DR Series system returns the status message shown under Result.

Syntax

```
maintenance --filesystem --repair_status
```



Result

Filesystem checker is not running.

maintenance --filesystem [--repair_history [verbose]]

Description

Displays the filesystem checker history for a DR Series system.

Syntax

```
maintenance --filesystem --repair_history
```

Result

Filesystem check time	:	Wed Nov 23 21:59:10 2016
Dry run finished at	:	Wed Nov 23 21:59:14 2016
Release version	:	4.0.0254.0
Build	:	62141
Data verification	:	Not Enabled
Scan mode	:	Normal scan
Result	:	No inconsistencies discovered.
Storage Group(s)	:	sg2
Filesystem check time	:	Tue Nov 29 22:13:54 2016
Dry run finished at	:	Tue Nov 29 22:15:57 2016
Release version	:	4.0.0254.0
Build	:	62141
Data verification	:	Not Enabled
Scan mode	:	Normal scan
Result	:	No inconsistencies discovered.
Storage Group(s)	:	All
Filesystem check time	:	Tue Nov 29 22:20:12 2016
Dry run finished at	:	Tue Nov 29 22:20:28 2016
Release version	:	4.0.0254.0
Build	:	62141
Data verification	:	Enabled
Scan mode	:	Normal scan
Result	:	No inconsistencies discovered.
Storage Group(s)	:	sg2

maintenance --filesystem [--scan_restart [verify_data | verify_rda_metadata | verify_metadata]]

Description

Restarts file system checker to generate updated report.

 **NOTE:** Argument `verify_data` validates data with pre-built checksum. Argument `verify_rda_metadata` scans only OST and RDA containers. Argument `verify_metadata` scans only the namespace for all containers.

Syntax

```
maintenance --filesystem --scan_restart [verify_data| verify_rda_metadata | verify_metadata]
```

Result

Successfully restarted filesystem scan.



maintenance --filesystem [--repair_now]

Description

Repairs any filesystem issues in a DR Series system based on the repair report findings.

Syntax

```
maintenance --filesystem --repair_now
```

Result

Successfully started repair.

To view repair progress run "maintenance --filesystem --repair_status".

maintenance --filesystem [--reclaim_space]

Description

Reclaims disk space that was formerly occupied by data in the recycle bin in a DR Series system using the Cleaner process. This command is what is commonly referred to as "manually" running the Cleaner process to reclaim disk space.

Syntax

```
maintenance --filesystem --reclaim_space
```

Result

Successfully started cleaner.

maintenance --filesystem [--stop_reclaim_space]

Description

Stops the disk space reclaim process in a DR Series system.

Syntax

```
maintenance --filesystem --stop_reclaim_space
```

Result

Successfully stopped cleaner.

maintenance --filesystem [--clear_quarantine]

Description

Clears a specialized quarantine folder that collects data files considered corrupted after attempts have been made to perform repairs by the filesystem. The **maintenance --filesystem** CLI commands should only be performed when the DR Series system is in its **Maintenance** mode. This command should not need to be run on a regular basis (it should only be run when a lengthy period of time has elapsed or you feel that the space in the quarantine folder needs to be reclaimed).

Syntax

```
maintenance --filesystem --clear_quarantine
```

Result

Successfully performed quarantine cleanup.

maintenance --filesystem --show_throughput

Description

Computes read/write throughput for the internal device.



Syntax

```
maintenance --filesystem --show_throughput
```

Result

```
Throughput from file system devices:  
Internal           Write Throughput: [292 MiBps]  Read Throughput: [157  
MiBps]
```

maintenance --configuration [--backup]

Description

Backs up the current DR Series system configuration.

Syntax

```
maintenance --configuration --backup
```

Result

Configuration saved successfully.

maintenance --configuration [--restore]

Description

Restores a previously backed up DR Series system configuration and overwrites the current configuration on the system.

Syntax

```
maintenance --configuration --restore
```

Result

```
Couldn't find administrator backup file. Restoring from default backup location.  
WARNING: Restore will overwrite existing configuration from previous backup.  
Previous backup was taken at time "Thu Dec  8 18:18:57 2016".  
All configuration changes after previous backup will be lost.
```

WARNING: IO to DR will be stopped during the restore process.

Do you want to continue (yes/no) [n]?

maintenance --configuration [--reinit_dictionary]

Description

Reinitializes the dictionary on a DR Series system. Using the **--reinit_dictionary** command is not considered a commonly performed function. Because the dictionary acts as an index that maps each chunk of data to a specific location, it is referenced during data ingests to determine if the DR Series system has seen this data before. When you reinitialize the dictionary, all entries that indicate whether there were previously archived data locations are removed. As a result, during new data ingests the DR Series system will be unable to detect any duplicates based on the existing archived data.

 **NOTE:** Use caution when considering whether you should reinitialize the dictionary. This type operation is only performed rarely, and when performed, only under special circumstances. Contact and consult with Technical Support before you use this command.



Syntax

You will need to type yes to continue or no to return to the system prompt when you are prompted whether you want to continue with this process.

```
maintenance --configuration --reinit_dictionary
```

Please enter administrator password:

WARNING: ALL DICTIONARY DATA WILL BE ERASED!

Do you want to continue (yes/no) ?

stop Filesystem... Done.

Initializing Dictionary... Done.

Restart Filesystem... Done.

maintenance --configuration [--reset_web_certificate]

Description

The current release supports installation of an SSL certificate. This command can be used to restore the default SSL certificate that ships with the DR.

Syntax

```
maintenance --configuration --reset_web_certificate
```

Result

Successfully restored the default certificate.

maintenance --hardware [--reinit_nvram]

Non-volatile RAM (NVRAM) is the type of memory that retains its contents even when power to it is turned off. This is an important component of the DR Series system that is crucial to normal data operations

Description

Initializes the NVRAM that resides on the DR Series system hardware appliance on which the DR Series system software is installed.

 **CAUTION:** Carefully consider before attempting to use the DR Series system CLI --reinit_nvram command. This command should only be used under the direction of Technical Support because it permanently erases all data stored on the NVRAM in the DR Series system hardware appliance. This command is only to be used when replacing the NVRAM in your hardware appliance. Contact Technical Support and seek assistance before you use this command.

Syntax

```
maintenance --hardware --reinit_nvram
```

Result

Please enter administrator password:

WARNING: ALL NVRAM DATA WILL BE ERASED!

Do you want to continue (yes/no) ?

Type yes to continue or no to return to the system prompt.

maintenance --hardware [--restore_hw_db]

Description

Restores and repairs the Hardware Health Monitor database for a DR Series system.



Syntax

```
maintenance --hardware --restore_hw_db
```

Result

```
WARNING: All previous Event & Alert information will be deleted.  
Do you want to continue? (yes/no) [n]? y  
Please enter the administrator password:  
The Hardware Health Monitor has been successfully restored.
```

maintenance --hardware [--motherboard_replaced]

Description

Updates the motherboard service tag on all signature partitions. The system must be in manual intervention mode for this command to execute. This command applies to systems that have an external enclosure attached.

If a motherboard is replaced in the DR Series system, the service tag should be blank from service inventory. That service tag should be reprogrammed to match the existing system service tag before the on-site technician leaves; therefore, this command should not be required. However, if the service tag is changed for some reason, this command will need to be executed to update the external drives to match the new service tag. A second scenario is when migrating an enclosure from one DR Series system to another. This command would need to be executed to match the migrated enclosures drives to the new service tag.

This option is only available on a Physical DR.

Syntax

```
maintenance --hardware --motherboard_replaced
```

maintenance --disk [--make_standby [slot num]] [--type <internal | external-<num> | service tag>] --clear_foreign]

Description

Creates a standby disk for a DR Series system.

Syntax

The **--make_standby [slot num]** command option changes the state of a physical disk (making disk 3 in this example the standby). The slot number (0-11) that is defined in the command identifies the physical disk to set as the hot-swap spare.

```
maintenance --disk --make_standby 3
```

The **--type <internal | external-<num> | service tag>** command option manages the standby disk type (by specifying it as internal or external, and if external which enclosure number, or by its service tag).

```
maintenance --disk --type external-1
```

The **--clear_foreign** command changes the state of a physical disk. Use this command when inserting a disk from another appliance, or the disk had been used in a different RAID configuration. After installing, you must enter the following command at the system prompt:

```
maintenance --disk --clear_foreign
```

 **NOTE:** The output of the DR Series system CLI system **--show --hardware** command lists the current states of the system disks. One possible state is *foreign*, which indicates that the **--clear_foreign** command needs to be run. In addition, an alert is generated if the DR Series system detects that any of the disks were in a foreign state.

maintenance --remote_access [--show]

Description

The command shows remote access information.



Syntax

```
maintenance --remote_access --show
```

Result

```
Remote Access Device
Device Type : iDRAC7 Enterprise
iDRAC Ports : Present
IPMI Version : 2.0
System GUID : 3157304f-c0b6-4a80-3910-00564cxxxxxx
Number of Possible Active Sessions : 5
Number of Current Active Sessions : 0
Enable IPMI Over LAN : Yes
SOL Enabled : Yes
MAC Address : 78-45-C4-EC-xx-xx

IPv4 Address
IP Address Source : Static
IP Address : 10.250.241.xxx
IP Subnet : 255.255.xxx.x
IP Gateway : 10.250.xxx.x
```

maintenance --remote_access [--enable]

Description

The command enables the iDRAC access (default: DHCP).

Syntax

```
maintenance --remote_access --enable
```

Result

Successfully enabled remote access.

maintenance --remote_access [--racreset]

Description

This command resets the Integrated Dell Remote Access Controller (iDRAC) .

Syntax

```
maintenance --remote_access --racreset
```

maintenance --remote_access [--static_ip] [--ip <IPv4/IPv6 address>] [--netmask <netmask>] [--gateway <IPv4/IPv6 address>] [--device <lom1|lom2|lom3|lom4>]

Description

The command assigns a static IP address for Integrated Dell Remote Access Controller (iDRAC).

Syntax

```
maintenance --remote_access [--static_ip] [--ip <IPv4/IPv6 address>] [--netmask <netmask>] [--gateway <IPv4/IPv6 address>] [--device <lom1|lom2|lom3|lom4>]
```

```
--static_ip Assign a static IP address for Integrated Dell Remote
Access Controller (iDRAC).
--ip Static IP address to use.
--netmask Netmask for the assigned static IP address.
--gateway Gateway for routing.
--device Network device for iDRAC. By default, if you do not
specify a device, the iDRAC port will be used.
```



For example, to enable the remote access, you can run a similar command like the one below:

```
maintenance --remote_access --enable --static_ip --ip 10.250.241.167 --netmask  
255.255.252.0 --gateway 10.250.240.1
```

Result

```
Successfully enabled remote access
```

maintenance --remote access [--disable]

Description

The command disables the iDRAC access (default: DHCP).

Syntax

```
maintenance --remote access --disable
```

Result

```
Successfully disabled remote access
```

maintenance --vdisk --check_consistency --type <boot|internal|external> [--service_tag <service tag>]

Description

Manages virtual disk drives.

- check_consistency — Starts vdisk consistency check.
- type — Type of the vdisk (boot/internal/external).
- service_tag — Service tag of the external storage.

Syntax

```
maintenance --vdisk --check_consistency --type internal
```

Result

```
Vdisk check: Successful.
```

maintenance --help

Description

Displays the list of maintenance-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
maintenance --help
```

Result

Usage:

```
    maintenance --filesystem [--scan_status]  
        [--scan_report [verbose]]  
        [--repair_status [verbose]]  
        [--repair_history [verbose]]  
        [--scan_restart [verify_data | verify_rda_metadata |  
    verify_metadata]]  
        [--repair_now]  
        [--reclaim_space]  
        [--stop_reclaim_space]  
        [--clear_quarantine]  
        [--start_scan [verify_data | verify_rda_metadata |  
    verify_metadata]] [--storage_group <name>]  
        [--stop_scan]  
  
    maintenance --configuration [--backup]
```



```

[--restore]
[--reinit_dictionary]

maintenance --hardware [--reinit_nvram]
[--restore_hw_db]
[--network_reconfigure]
[--motherboard_replaced]

maintenance --disk [--make_standby [slot num]] [--type <internal | external-<num> | service tag>]
[--clear_foreign]

maintenance --remote_access [--show]
[--enable] [--static_ip] [--ip <IPv4/IPv6 address>] [--netmask <netmask>]
[--gateway <IPv4/IPv6 address>]
[--device <lom1|lom2|lom3|lom4>]
[--disable]

maintenance --vdisk --check_consistency --type <boot | internal | external> [--service_tag <service tag>]

maintenance --help

maintenance <command> <command-arguments>
<command> can be one of:
--filesystem      Maintenance operations on filesystem.
--configuration   Backup/Restore system configuration.
--hardware        Manage appliance hardware.
--disk            Manage disk drives.
--remote_access   Manage Integrated Remote Access Controller (iDRAC).
--vdisk           Manage virtual disk drives.

```

For command-specific help, please type maintenance --help <command>
 eg:
 maintenance --help filesystem

Managing DR Series System Storage Operations

This topic introduces the DR Series system CLI commands that you can use for configuring and managing DR Series system backup operations, replication operations, and scheduling when to run Replication and disk Cleaner operations. The DR Series system CLI commands that provide these capabilities are grouped into the following categories:

- **Connections:** configuring/managing connections to storage containers
- **Containers:** configuring/managing storage and replication relationships
- **Replication:** configuring/managing replication operations
- **Seeding:** managing seeding import and export
- **Schedule:** configuring/managing Replication and Cleaner schedules for the DR Series system

System Storage Operation Commands

This topic introduces the DR Series system CLI system storage operation commands that allow you to manage the connections to both storage and replication containers, manage these containers, and manage both storage and replication operations.

Connection

This topic introduces the set of DR Series system CLI commands that allow you to manage, configure, and display connection-related settings for containers on a DR Series system. For more information, see [Connection Command Usage](#).

Connection Command Usage

This topic introduces the **connection** command usage:

- **connection --show [options]**
- **connection --add --name --type [options]**
- **connection --update --name --type [options]**
- **connection --delete --name --type [options]**
- **connection --enable --name --type [options]**
- **connection --disable --name --type [options]**
- **connection --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you are prompted to provide the correct value or option.

connection --show [--name <name>]

Description

Displays the status of a specific existing container connection that you define by name (**backup**) on a DR Series system.



Syntax

```
connection --show --name backup
```

Result

Container Name	:	backup
NFS connection IP addresses	:	*
NFS connection Root map	:	root
NFS connection options	:	rw
NFS connection Enabled	:	Yes
NFS connection status	:	Available
CIFS connection IP addresses	:	*
CIFS connection Enabled	:	Yes
CIFS connection status	:	Available

connection --show [--name <name>] [--type <NFS|CIFS|OST|RDS|NDMP|iSCSI|FC>] [--verbose]

Description

Displays the status of all existing container connections on a DR Series system (for example, for NFS, CIFS, None, OST, or RDS connections, and NDMP, iSCSI, and FC for VTL containers).

 **NOTE:** In addition to displaying the current status of an existing container connection, this command also verifies if an existing container connection is disabled (by listing its status as offline).

Syntax

```
connection --show
```

Result

Container Name	Connection Type
backup	NFS, CIFS
Target	RDS
avc	RDS

Other Examples

Display the status of a specific existing CIFS/NFS container connection (**backup**) by defining it by name using the **--name backup** command on a DR Series system:

```
connection --show --name backup
Container Name      : backup
NFS connection IP addresses   : *
NFS connection Root map       : root
NFS connection options        : rw
NFS connection Enabled        : Yes
NFS connection status         : Available
CIFS connection IP addresses  : *
CIFS connection Enabled       : Yes
CIFS connection status        : Available
```

Display the detailed status of a specific container connection (**backup**) by defining it by name using the **--name backup** command and defining the specific filesystem protocol type (**--type nfs**) on a DR Series system:

```
connection --show --name backup --type nfs
Container Name      : backup
NFS connection IP addresses   : *
NFS connection Root map       : root
NFS connection options        : rw
NFS connection Enabled        : Yes
NFS connection status         : Available
```



Display the complete status of all existing container connections by using the **--verbose** command on a DR Series system (this example only shows a partial display of the total output):

```
connection --show --verbose
Container Entry ID      : 1
Container Name          : backup
NFS connection Entry ID : 25
NFS connection IP addresses : *
NFS connection Root map : root
NFS connection options  : rw
NFS connection Enabled  : Yes
NFS connection status    : Available
CIFS connection Entry ID : 26
CIFS connection IP addresses : *
CIFS connection Enabled  : Yes
CIFS connection status    : Available

Container Entry ID      : 2
Container Name          : _1234
NFS connection Entry ID : 3
NFS connection IP addresses : *
NFS connection Root map : root
NFS connection options  : rw
NFS connection Enabled  : Yes
NFS connection status    : Available

Container Entry ID      : 3
Container Name          : 12345678
NFS connection Entry ID : 4
NFS connection IP addresses : 10.3.3.3
NFS connection Root map : nobody
NFS connection options  : ro
NFS connection Enabled  : Yes
NFS connection status    : Available
CIFS connection Entry ID : 5
CIFS connection IP addresses : 10.2.2.2,10.3.3.3,10.3.4.4
CIFS connection Enabled  : Yes
CIFS connection status    : Available
```

connection --show [--verbose]

Description

Displays the complete status of all container connections on a DR Series system.

Syntax

```
connection --show --verbose
```

Result

```
Container Entry ID      : 1
Container Name          : backup
NFS connection Entry ID : 25
NFS connection IP addresses : *
NFS connection Root map : root
NFS connection options  : rw
NFS connection Enabled  : Yes
NFS connection status    : Available
CIFS connection Entry ID : 26
CIFS connection IP addresses : *
CIFS connection Enabled  : Yes
CIFS connection status    : Available

Container Entry ID      : 2
Container Name          : 1234
NFS connection Entry ID : 3
NFS connection IP addresses : *
```



NFS connection Root map	:	root
NFS connection options	:	rw
NFS connection Enabled	:	Yes
NFS connection status	:	Available

connection --add --name <name> --type <NFS|CIFS|OST|RDS|NDMP|iSCSI|FC> [--clients <ip address>][--dma <ip address>][--initiator <IQN, ip address(es), hostname, or WWPN>] [--rootmap <nobody|root|administrator>] [--options <NFS|CIFS mount export options>] [--capacity <positive decimal number>]

Description

Specifies connection type, client IP addresses, sets the DMA or initiator address for restricting NDMP or iSCSI/FC access to the specified host or iSCSI/FC initiator, defines rootmap privileges for NFS, sets mounting options for an NFS or CIFS connection, and sets a capacity in GB for an OST or RDS connection. NFS and CIFS connection types do not recognize a set capacity that is defined using a positive decimal number in the **--capacity** option.

 **NOTE:** NFS mounting options include read-write (rw), read-only (ro), and insecure.

- rw—allows read-write access.
- ro—allows read-only access.
- insecure—allows replies to be made to requests before changes in request are made.

 **NOTE:** CIFS mounting options include hide, unhide.

Syntax

```
connection --add --name ost2 --type ost --capacity 10
```

Result

Successfully added connection entry.		
OST connection Quota	:	10
OST connection Enabled	:	Yes

connection --update --name <name> --type <NFS|CIFS|OST|RDS|NDMP|iSCSI|FC> [--clients <ip address>][--dma <ip address>][--initiator <IQN, ip address(es), hostname, or WWPN>] [--rootmap <nobody|root|administrator>] [--options <NFS|CIFS mount export options>] [--capacity <positive decimal number>]

Description

Updates or modifies the connection values on an existing container connection on a DR Series system.

 **NOTE:** The following DR Series system CLI connection command options (**--clients**, **--dma**, **--initiator**, **--rootmap**, **--options**, and **--capacity**) apply selectively to specific container type connections.

For example:

- **--clients** command option only applies to NFS and CIFS type container connections and specifies to restrict NFS/CIFS access to this list of comma separated hosts.
- **--dma** option only applies to NDMP type container connections and specifies to restrict NDMP access to this DMA host.
- **--initiator** option applies to iSCSI or FC type container connections and specifies to restrict iSCSI/FC access to the specified iSCSI/FC initiator.
- **--rootmap** and **--options** command options apply only to NFS type container connections.
- **--capacity** command option only applies to OST or RDS container connections, and lets you specify a positive decimal number to represent the capacity size in Gigabytes (GB). By default, OST and RDS type container connections are unlimited.



Syntax

```
connection --update --name dataStorage3 --type nfs --clients 10.27.22.11  
--options ro,rw
```

Result

```
Successfully updated connection entry.  
NFS connection IP addresses : 10.27.22.11  
NFS connection Root map : administrator  
NFS connection options : ro,rw  
NFS connection Enabled : Yes
```

connection --delete --name <name> --type <NFS|CIFS|OST|RDS|NDMP|iSCSI|FC> [--clients <ip address>]

Description

Deletes an existing container connection type on a DR Series system.

 **NOTE:** For NDMP, iSCSI, and FC type connections, the "--clients" option does not need to be specified.

Syntax

```
connection --delete --name dataStorage3 --type nfs --clients 10.27.22.11  
connection --delete --name iscsi-vt1 --type iscsi
```

Result

Successfully deleted connection entry.

connection --enable --name <name> --type <NFS|CIFS|OST|RDS>

Description

Enables an existing container connection type (NFS, CIFS, OST, or RDS) that was disabled on a DR Series system.

Syntax

```
connection --enable --name dataStorage3 --type nfs
```

Result

```
Successfully updated connection entry.  
NFS connection IP addresses : 10.27.22.11  
NFS connection Root map : administrator  
NFS connection options : rw,ro  
NFS connection Enabled : Yes
```

connection --disable --name <name> --type <NFS|CIFS|OST|RDS>

Description

Disables an existing container connection type (NFS, CIFS, OST, or RDS) on a DR Series system.

Syntax

```
connection --disable --name acme3 --type ost
```

Result

```
Successfully updated connection entry.  
OST connection Quota : Unlimited  
OST connection Used Capacity : 5.0 GB  
OST connection Enabled : No
```



connection --help

Description

Displays the listing of user and related options that you can use as a reference when using the DR Series system CLI.

Syntax

```
connection --help
```

Results

Usage:

```
connection --show [--name <name>]
                  [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI>]
                  [--verbose]

connection --add --name <name>
              [--type <NFS|CIFS|OST|RDS|NDMP|ISCSI>]
              [--clients <ip_address>]
              [--dma <ip_address>]
              [--initiator <IQN, ip_address(es), hostname, or WWPN>]
              [--rootmap <nobody|root|administrator>]
              [--options <NFS|CIFS mount export options>]
              [--capacity <Positive decimal number>]

connection --update --name <name>
              --type <NFS|CIFS|OST|RDS|NDMP|ISCSI>
              [--clients <ip_address>]
              [--dma <ip_address>]
              [--initiator <IQN, ip_address(es), hostname, or WWPN>]
              [--rootmap <nobody|root|administrator>]
              [--options <NFS|CIFS mount export options>]
              [--capacity <Positive decimal number>]

connection --delete --name <name>
              --type <NFS|CIFS|OST|RDS|NDMP|ISCSI>
              [--clients <ip_address>]

connection --enable --name <name>
              --type <NFS|CIFS|OST|RDS>

connection --disable --name <name>
              --type <NFS|CIFS|OST|RDS>

connection --help
connection <command> <command-arguments>
<command> can be one of:
              --show      Displays the current connections on a container.
              --add       Adds a new connection to a container.
              --update    Updates an existing connection.
              --delete    Deletes an existing connection.
              --enable    Enables access to a container through a connection.
              --disable   Disables access to a container through a connection.
```

For command-specific help, please type `connection --help <command>`

eg:

```
connection --help show
```



Container

This topic introduces the set of DR Series system CLI commands that allow you to perform the following tasks:

- Display the status of all current containers (summary or detail)
- Create (and name) new containers (the DR Series system limits support to 32 containers)
- Delete existing containers

Container Command Usage

This topic introduces the **container** command usage:

- **container --show [options]**
- **container --add --name**
- **container --delete --name [options]**
- **container --marker --name <name> [--enable options] [--disable options]**
- **container --delete_files --name <name>**
- **container --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

container --show

Description

Displays a list of all current containers in a DR Series system.

Syntax

```
container --show
```

Result

```
Container Entries are:  
backup  
acme-59_replicate  
acmeStorage1  
acmeStorage2  
acmeStorage3dataStorage3
```

container --show [--name <name>] [--verbose]

Displays the summary status of an existing container in a DR Series system that you specify using the **container --show --name** command.

Syntax

```
container --show --name acme-41-cifs-1
```

Result

Container Name	:	acme-41-cifs-1
Container Path	:	/containers/acme-41-cifs-1
Container Marker	:	commvault

Other Examples

Displays the detailed status of an existing container that you specify by name using the **container --show --name --verbose** command:

Container Name	:	acme55-S2
Container Path	:	/containers/acme55-S2



```

Container Marker : None
NFS connection IP addresses : *
NFS connection Root map : root
NFS connection options : rw
NFS connection Enabled : Yes
NFS connection status : Available
CIFS connection IP addresses : *
CIFS connection Enabled : Yes
CIFS connection status : Available
Replication Role : Source
Replication Target System : acme-85
Replication Target System IP : 10.20.22.20
Replication Target Container : acme85-S2
Replication Enabled : Yes
Replication Compression Enabled : Yes
Replication Encryption : AES 128-bit

```

container --add --name <name> [--type <VTL>] [--tape_size <tape_size>][--no_of_drives <1-60>][--is_oem <yes|no>][--group_name <name>]

Description

Creates and names a new container in the DR Series system.

- **NOTE:** Container names and storage group names cannot exceed 32 characters in length. The “_” character is allowed for no-VTL containers. Container names cannot start with a number, and the /, #, and @ special characters are not allowed. Valid values for the container and storage group name are [a-z, A-Z, 0-9, and ‘_’].
- **NOTE:** When creating a VTL container type, you must specify the option, --type VTL. Possible values for tape size include:
800GB|400GB|200GB|100GB|50GB|10GB
- **NOTE:** The number of drives parameter is applicable to FC containers only.

Syntax

```
container --add --name acme99
```

Result

Container "acme99" created successfully.

Syntax

```
container --add --name vtlcont --type vtl --is_oem yes --tape_size 100gb
```

Result

Container "vtlcont" created successfully.

container --update --name <name> [--no_of_drives <1-60>]

Description

Updates the specified container with the specified number of drives. This is applicable to FC type containers only.

Syntax

```
container --update --name fc1 --no_of_drives 32
```

Result

The FC service will be restarted for this change to take effect, Do you want to continue? (yes/no) [n]? y
Successfully updated Container FC1's number of drives as 32.



container --delete --name <name>

Description

Deletes an existing container by name from a DR Series system.

Syntax

```
container --delete --name acme49
```

Result

Error: Container has to be empty before deleting the container. Please delete all File(s) and Directories in the container.

Other Examples

Deletes an existing container type and the data files within the specified container by combining the **--delete** and the **--delete_files** DR Series system CLI commands:

```
container --delete --name acme_17 --delete_files
```

WARNING: All the data in the container acme_17 will be deleted!

Do you want to continue? (yes/no) [n]? y

Please enter the administrator password:

Container "acme_17" marked for deletion. Please run "maintenance --filesystem --reclaim_space" to recover the storage space.

 **NOTE: Be aware that it may take a fair amount of time for the DR Series system file and container deletion processes to complete and update the system status. For details on deleting the files within an OST container, see [container --delete_files --name <name>](#).**

container --delete --name <name> [--delete_files]

Description

Deletes the files and the existing container on which the files reside in a DR Series system when using the **--name** option with **--delete_files** command.

Syntax

```
container --delete --name acme4 --delete_files
```

Result

WARNING: All the data in the container acme4 will be deleted!

Do you want to continue? (yes/no) [n]? y

Please enter the administrator password:

Container "weasel_ost" marked for deletion. Please run "maintenance --filesystem --reclaim_space" to recover the storage space.

container --marker [--enable <Auto | CommVault | Networker | TSM | ARCserve | HP_DataProtector | Unix_Dump | BridgeHead>] [--disable <Auto | CommVault | Networker | TSM | ARCserve | HP_DataProtector | Unix_Dump | BridgeHead>] --name <name>

Description

Enables or disables a marker type or an automatic marker setting type (Auto) on an existing container in the DR Series system. To enable or disable the automatic marker setting type on an existing container, substitute **Auto** in place of a specific marker type (for example, **Networker** in the CLI command).

Syntax

```
container --marker --enable networker --name acme99
```



Result

Marker updated successfully.

Other Examples

Disables a Networker marker on an existing container in the DR Series system:

```
container --marker --disable networker --name acme99  
Marker updated successfully.
```

container --delete_files --name <name>

Description

Deletes only the data files on an existing Rapid Data Access containers (OST/RDS type containers) in a DR Series system (and leaves the container intact).

Syntax

```
container --delete_files --name acme99
```

Result

Error: Connection needs to be disabled first.

 **NOTE:** This command is only supported on OST/RDA connection type containers and the connection to the container must be disabled before you can delete its files. For details, see [connection --disable --name <name> --type <NFS|CIFS|OST|RDS>](#). To delete the files and the existing OST container on which the files resides, see [container --delete --name <name> --delete_files](#).

container --help

Description

Displays the list of container-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
container --help
```

Result

Usage:

```
container --show [--name <name>]  
                [--verbose]  
  
container --add --name <name>  
  
container --delete --name <name>  
                [--delete_files]  
  
container --marker [--enable <Auto | CommVault | Networker | TSM | ARCserve |  
                    HP_DataProtector | Unix_Dump | BridgeHead>]  
                [--disable <Auto | CommVault | Networker | TSM | ARCserve |  
                    HP_DataProtector | Unix_Dump | BridgeHead>]  
                --name <name>  
  
container --delete_files --name <name>  
  
container --help  
  
container <command> <command-arguments>  
<command> can be one of:  
--show           Displays the current list of containers.  
--add            Adds a new container.  
--delete         Deletes an existing container.  
--marker         Enables/Disables marker for an existing container.
```



```
--delete_files Deletes the files in the container.

For command-specific help, please type container --help <command>
For example:
    container --help show
```

VTL

The VTL commands allow you to manage the virtual tape library (VTL) containers you have created for your system, including the ability to create additional tapes for your libraries, set drives to read/write, or activate and deactivate replica VTLs.

VTL Command Usage

This topic introduces the DR Series system CLI commands that allow you to manage the virtual tape library (VTL) containers you have created for your system, which include:

- **vtl --show [options]**
- **vtl --update_carts [options]**
- **vtl --activate --name [options]**
- **vtl --deactivate --name**
- **vtl --rescan --name [options]**
- **vtl --set_rw [options]**
- **vtl --show_replstate --name**
- **vtl --help**

vtl --show [--name <name>]

Description

This command allows you to see the status of a specified virtual tape library (VTL). It displays detailed information about VTL, such as media type, vendor, model, generic device information, serial number, library size, and tape status information. The first example below shows the result information for Container vtl1 of type VTL with an NDMP connection. The second example shows Container iscsi-vtl1 of type VTL with an iSCSI connection.

Syntax

```
vtl --show [--name <name>]
```

Result

Type	Vendor	Model	Serial	Info	ID
medi	DELL	DR_L700	81BL3T_00	10 10GB	10
tape	IBM	ULT3580-TD4	81BL3T_01	Not loaded	11
tape	IBM	ULT3580-TD4	81BL3T_02	Not loaded	12
tape	IBM	ULT3580-TD4	81BL3T_03	Not loaded	13
tape	IBM	ULT3580-TD4	81BL3T_04	Not loaded	14
tape	IBM	ULT3580-TD4	81BL3T_05	Not loaded	15
tape	IBM	ULT3580-TD4	81BL3T_06	Not loaded	16
tape	IBM	ULT3580-TD4	81BL3T_07	Not loaded	17
tape	IBM	ULT3580-TD4	81BL3T_08	Not loaded	18
tape	IBM	ULT3580-TD4	81BL3T_09	Not loaded	19
tape	IBM	ULT3580-TD4	81BL3T_10	Not loaded	20

Type	Vendor	Model	Serial	Info	ID
medi	DELL	DR_L700	NQ9VL5_00	110 100GB	30



tape	IBM	ULT3580-TD4	NQ9VL5_01	Not loaded	31
tape	IBM	ULT3580-TD4	NQ9VL5_02	Not loaded	32
tape	IBM	ULT3580-TD4	NQ9VL5_03	Not loaded	33
tape	IBM	ULT3580-TD4	NQ9VL5_04	Not loaded	34
tape	IBM	ULT3580-TD4	NQ9VL5_05	Not loaded	35
tape	IBM	ULT3580-TD4	NQ9VL5_06	Not loaded	36
tape	IBM	ULT3580-TD4	NQ9VL5_07	Not loaded	37
tape	IBM	ULT3580-TD4	NQ9VL5_08	Not loaded	38
tape	IBM	ULT3580-TD4	NQ9VL5_09	Not loaded	39
tape	IBM	ULT3580-TD4	NQ9VL5_10	Not loaded	40

vtl --show --verbose [--name <name>]

Description

Displays detailed information about the specified virtual tape library (VTL).

Syntax

```
vtl --show --verbose
```

Result

Type	Vendor	Model	Serial	Info	ID
medi	DELL	DR_L700	NQ9VL5_00	110 100GB	30
tape	IBM	ULT3580-TD4	NQ9VL5_01	Not loaded	31
tape	IBM	ULT3580-TD4	NQ9VL5_02	Not loaded	32
tape	IBM	ULT3580-TD4	NQ9VL5_03	Not loaded	33
tape	IBM	ULT3580-TD4	NQ9VL5_04	Not loaded	34
tape	IBM	ULT3580-TD4	NQ9VL5_05	Not loaded	35
tape	IBM	ULT3580-TD4	NQ9VL5_06	Not loaded	36
tape	IBM	ULT3580-TD4	NQ9VL5_07	Not loaded	37
tape	IBM	ULT3580-TD4	NQ9VL5_08	Not loaded	38
tape	IBM	ULT3580-TD4	NQ9VL5_09	Not loaded	39
tape	IBM	ULT3580-TD4	NQ9VL5_10	Not loaded	40

Cartridges available in library:

NQ9VL5001 NQ9VL5002 NQ9VL5003 NQ9VL5004 NQ9VL5005 NQ9VL5006 NQ9VL5007 NQ9VL5008
NQ9VL5009 NQ9VL500A NQ9VL500B NQ9VL500C NQ9VL500D NQ9VL500E NQ9VL500F NQ9VL500G
NQ9VL500H NQ9VL500I NQ9VL500J NQ9VL500K NQ9VL500L NQ9VL500M NQ9VL500N NQ9VL500O
NQ9VL500P NQ9VL500Q NQ9VL500R NQ9VL500S NQ9VL500T NQ9VL500U NQ9VL500V NQ9VL500W
NQ9VL500X NQ9VL500Y NQ9VL500Z NQ9VL5010 NQ9VL5011 NQ9VL5012 NQ9VL5013 NQ9VL5014
NQ9VL5015 NQ9VL5016 NQ9VL5017 NQ9VL5018 NQ9VL5019 NQ9VL501A NQ9VL501B NQ9VL501C
NQ9VL501D NQ9VL501E NQ9VL501F NQ9VL501G NQ9VL501H NQ9VL501I NQ9VL501J NQ9VL501K
NQ9VL501L NQ9VL501M NQ9VL501N NQ9VL501O NQ9VL501P NQ9VL501Q NQ9VL501R NQ9VL501S
NQ9VL501T NQ9VL501U NQ9VL501V NQ9VL501W NQ9VL501X NQ9VL501Y NQ9VL501Z NQ9VL5020
NQ9VL5021 NQ9VL5022 NQ9VL5023 NQ9VL5024 NQ9VL5025 NQ9VL5026 NQ9VL5027 NQ9VL5028
NQ9VL5029 ... and more!

Total: 110 cartridges available.

vtl --update_carts --name <name> --add --no_of_tapes <number>

Description

This command allows you to create additional tapes for a library specified in the --name option. Each library is initially created with 10 slots housing 60 tape media. Additional tapes can be added to the library as needed using this command. A library can only contain tapes of the same size. For example, if the library was originally created with 60 tapes of size 10G, additional tapes of size 10G can only be added.

Syntax

```
vtl --update_carts --name test-vtl --add --no_of_tapes 10
```



Result

Created 10 cartridges.

vtl --activate --name <name> [--force <yes|no>]

Description

This command activates a replica VTL.

Syntax

```
vtl --activate --name VTL1_Test --force yes
```

Result

Enter reserialization code for replica [00 (no op), 01 - 99]: 00
VTL processes will be started for container, VTL1_Test ...

vtl --deactivate --name <name>

Description

This command deactivates a replica VTL.

Syntax

```
vtl --deactivate --name VTL1_Test
```

Result

Are you sure you want to de-activate this VTL? [Yes, No] y
VTL VTL1_Test is deactivated !!

vtl --rescan --name <name> [--force <yes|no>]

Description

This command rescans a replica VTL.

Syntax

```
vtl --rescan --name VTL1_Test
```

Result

Rescan replica VTL after new cartridges have been added at source VTL? [Yes|No]
Y

Connections to the library VTL1_Test could be disrupted for a brief period.
Make sure no cartridges are loaded in tape drives and/or backups are in
progress. Proceed? [Yes|No] y
vtllibrary will be re-instantiated for container, VTL1_Test!

vtl --set_rw --name <name> [--id <number>]

Description

This command allows you to set the drives in a VTL container to read/write. The arguments to this command are as follows:

- --name — Specifies the name of a valid VTL container.
- --id — Sets the IO mode of a specific drive to RW.

Syntax

```
vtl --set_rw --name ndmp --id 81
```



Result

I/O mode set to readwrite for the drive with id 81 in container ndmp

vtl --show_replstate --name <name>

Description

This command shows the replication state of a specified VTL replication source container.

Syntax

```
vtl --show_replstate --name VTL1_Test
```

Result

Cartridges with data, INSYNC with peer:

```
-----  
AFNGC6003 AFNGC6004 AFNGC6005 AFNGC6006 AFNGC6007 AFNGC6008 AFNGC6009 AFNGC600A  
AFNGC600B AFNGC600C AFNGC600D AFNGC600E AFNGC600F AFNGC600G AFNGC600H AFNGC600I  
AFNGC600J AFNGC600K AFNGC600L AFNGC600M AFNGC600N AFNGC600O AFNGC600Q AFNGC600R  
AFNGC600S AFNGC600T AFNGC600V AFNGC600W AFNGC600X AFNGC600Y AFNGC600Z AFNGC6010  
AFNGC6011 AFNGC6012 AFNGC6013 AFNGC6014 AFNGC6002 AFNGC6001  
Total 38 cartridges synchronized with peer VTL.
```

Cartridges with data, not INSYNC with peer:

```
-----  
None.  
Total 0 cartridges NOT synchronized with peer VTL.
```

Cartridges that do not have data are not displayed.

vtl --help

Description

Displays the list of vtl-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
vtl --help
```

Result

Usage:

```
    vtl --show [--verbose]  
              [--name <name>]  
  
    vtl --update_carts --name <name>  
          --add  
          --no_of_tapes <number>  
  
    vtl --activate --name <name>  
          [--force <yes|no>]  
  
    vtl --deactivate --name <name>  
  
    vtl --rescan --name <name>  
          [--id <number>]  
  
    vtl --show_replstate --name <name>  
  
    vtl --help  
  
vtl <command> <command-arguments>  
<command> can be one of:  
      --show                               Displays command specific information.
```



```

--update_carts          Add cartridges
--activate              Activate a replica VTL
--deactivate             De-activate a replica VTL
--rescan                Rescan a replica VTL
--set_rw                 Set drives in a vtl container to read
write
--show_replstate        Show replication state of a container

For command-specific help, please type vtl --help <command>
eg:
      vtl --help show

```

NDMP

The NDMP commands allow you to manage NDMP connections when you are using virtual tape library (VTL) containers.

NDMP Command Usage

This topic introduces the DR Series system CLI commands that allow you to manage NDMP connections when you are using virtual tape library (VTL) containers. These commands include:

- **ndmp --show**
- **ndmp --update [options]**
- **ndmp --help**

ndmp --show

Description

This command displays the NDMP username and port number being used in the current DR system.

Syntax

```
ndmp --show
```

Result

```
# ndmp --show
NDMP User: ndmp_user
NDMP Port: 10000
```

ndmp --update [--port <port number>]

Description

This command allows you to update and set the port number of the NDMP server. (The default port is 10000.)

Syntax

```
ndmp --update [--port <port number>]
```

Result

```
WARNING: Updating NDMP port involves restarting NDMP services.
Do you want to continue (yes/no) [n]? y
Successfully updated NDMP to use port 10001.
Restarting NDMP service ... done.
```

ndmp --help

Description

Displays the list of NDMP-related command options that can be used as a reference when using the DR Series system CLI.



Syntax

```
ndmp --help
```

Result

Usage:

```
    ndmp --show
    ndmp --update [--port <number>]
    ndmp --help

    ndmp <command> <command-arguments>
    <command> can be one of:
        --show           Displays command specific information.
        --update         Updates NDMP port (default port is 10000).
```

For command-specific help, please type `ndmp --help <command>`

eg:

```
    ndmp --help show
```

iSCSI

The iSCSI commands allow you to manage iSCSI connections when you are using virtual tape library (VTL) containers.

iSCSI Command Usage

This topic introduces the DR Series system CLI commands that allow you to manage iSCSI connections when you are using virtual tape library (VTL) containers. These commands include:

- `iscsi --show`
- `iscsi --setpassword`
- `iscsi --sessions`

iscsi --show [--user]

Description

This command displays iSCSI information including the iSCSI CHAP user name in the current DR system.

Syntax

```
iscsi --show --user
```

Result

```
user : iscsi_user
```

Syntax

```
iscsi --show
```

Result

```
Target 1 : iqn.1984-05.com.dell:dr2000v.3184868.vtl100.10
  System information:
    Driver: iscsi
    State: ready
  I_T nexus information:
  LUN information:
    LUN: 0
      Type: controller (Controller)
      Backing store path: None
    LUN: 1
      Type: passthrough (L700)
      Backing store path: /dev/sg12
    LUN: 2
      Type: passthrough ( ULT3580-TD4)
```



```

        Backing store path: /dev/sg2
LUN: 3
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg8
LUN: 4
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg11
LUN: 5
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg4
LUN: 6
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg5
LUN: 7
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg6
LUN: 8
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg10
LUN: 9
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg3
LUN: 10
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg9
LUN: 11
        Type: passthrough ( ULT3580-TD4)
        Backing store path: /dev/sg7
Account information:
  iscsi_user
  Target 1 ACL information:          10.250.249.221
administrator@satyan-vml >

```

iscsi --setpassword

Description

This command sets the password for the iSCSI CHAP user.

Syntax

```
iscsi --setpassword
```

Result

```

WARNING: All existing iSCSI sessions will be terminated!
Do you want to continue? (yes/no) [n]? yes
Enter new CHAP password:
Re-type CHAP password:
administrator@test-vml >

```

iscsi --sessions

Description

This command displays the current iSCSI sessions in the current DR system.

Syntax

```
iscsi --sessions
```

Result

```

iSCSI client(s) information:
Container: test_vtl
Target IQN: iqn.1984-05.com.dell:dr4000.7355836.test_vtl.10
  Initiators Connected: iqn.1991-05.com.microsoft:win-
t16n70kqii4.testad.test.local

```



iscsi --help

Description

Displays the list of iSCSI-related command options that can be used as a reference when using the DR Series system CLI.

Syntax

```
iscsi --help
```

Result

Usage:

```
    iscsi --show [--user]  
  
    iscsi --setpassword  
    iscsi --sessions  
    iscsi --help  
  
    iscsi <command> <command-arguments>  
<command> can be one of:  
        --show          Displays command specific information.  
        --setpassword   Set CHAP password  
        --sessions       Show iSCSI sessions
```

For command-specific help, please type `iscsi --help <command>`

eg:

```
    iscsi --help show
```

FC

The FC commands allow you to manage Fibre Channel (FC) connections when you are using virtual tape library (VTL) containers.

FC Command Usage

This topic introduces the DR Series system CLI commands that allow you to manage Fibre Channel connections when you are using virtual tape library (VTL) containers. These commands include:

- **fc --show**
- **fc --sessions**
- **fc --help**

fc --show [--verbose] [--target]

Description

This command displays Fibre Channel information in the current DR Series system.

Syntax

```
fc --show --verbose  
fc --show --target
```

Result

For fc --show --verbose:

Target port: Slot 6 Port 0

```
Port WWN: 50:00:65:b8:36:69:96:00  
Node WWN: 50:00:65:b8:36:69:90:00  
Symbolic node name: "Dell Inc.: Dell DR4300"
```



Card description: QLogic QLE2662 Dual Port FC16 HBA
Firmware version: 8.01.02
Port state: Online
Port type: NPort (fabric via point-to-point)
Port speed: 16 Gbit

Container: test2

LUN: 1
Type: Media changer (L700)
Backing store path: /dev/sg76

LUN: 2
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg36

LUN: 3
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg37

LUN: 4
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg38

LUN: 5
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg39

LUN: 6
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg40

LUN: 7
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg41

LUN: 8
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg42

LUN: 9
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg43

LUN: 10
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg44

LUN: 11
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg45

Initiators:
21:00:00:24:ff:76:58:66

Target port: Slot 6 Port 1

Port WWN: 50:00:65:b8:36:69:96:01
Node WWN: 50:00:65:b8:36:69:90:00
Symbolic node name: "Dell Inc.: Dell DR4300"
Card description: QLogic QLE2662 Dual Port FC16 HBA
Firmware version: 8.01.02
Port state: Online
Port type: NPort (fabric via point-to-point)
Port speed: 16 Gbit

Container: test2

LUN: 1
Type: Media changer (L700)
Backing store path: /dev/sg76

LUN: 2
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg36

LUN: 3
Type: Magnetic tape (ULT3580-TD4)
Backing store path: /dev/sg37

LUN: 4



```

        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg38
LUN: 5
        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg39
LUN: 6
        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg40
LUN: 7
        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg41
LUN: 8
        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg42
LUN: 9
        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg43
LUN: 10
        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg44
LUN: 11
        Type: Magnetic tape (ULT3580-TD4)
        Backing store path: /dev/sg45

Initiators:
21:00:00:24:ff:76:58:66

```

For fc --show --target:

Target port: Slot 6 Port 0

```

Port WWN: 50:00:65:b6:33:63:14:88
Node WWN: 50:00:65:b6:33:63:14:80
Symbolic node name: "Dell Inc.: Dell DR4300"
Card description: QLogic QLE2662 Dual Port FC16 HBA
Firmware version: 8.01.02
Port state: Online
Port type: NPort (fabric via point-to-point)
Port speed: 16 Gbit

```

Target port: Slot 6 Port 1

```

Port WWN: 50:00:65:b6:33:63:14:89
Node WWN: 50:00:65:b6:33:63:14:80
Symbolic node name: "Dell Inc.: Dell DR4300"
Card description: QLogic QLE2662 Dual Port FC16 HBA
Firmware version: 8.01.02
Port state: Online
Port type: NPort (fabric via point-to-point)
Port speed: 16 Gbit

```

fc --sessions [--topology] [--condensed]

Description

This command displays the current Fibre Channel sessions in the current DR system.

Syntax

```
fc --sessions --topology
fc --sessions --condensed
```

Result

For fc --sessions --topology:

```
Target port: 50:00:65:b6:33:63:14:88
  Initiators connected:
    10:00:00:90:fa:a0:ae:0a
```



```

50:0a:09:80:00:88:a7:71
50:0a:09:80:06:8d:9a:40
c0:03:ff:bd:1d:69:00:48

Target port: 50:00:65:b6:33:63:14:89
  Initiators connected:
    10:00:00:90:fa:cf:49:5e
    c0:03:ff:bd:1d:69:00:54
    c0:03:ff:bd:1d:69:00:58
    c0:03:ff:bd:1d:69:00:60

```

For fc --sessions --condensed:

```

Initiators connected.
  10:00:00:90:fa:a0:ae:0a
  50:0a:09:80:00:88:a7:71
  50:0a:09:80:06:8d:9a:40
  c0:03:ff:bd:1d:69:00:48
  10:00:00:90:fa:cf:49:5e
  c0:03:ff:bd:1d:69:00:54
  c0:03:ff:bd:1d:69:00:58
  c0:03:ff:bd:1d:69:00:60

```

fc --help <command>

Description

This command displays the command-specific help for the FC commands.

Syntax

fc --help

Result

Usage:

```

  fc --show [--verbose]
            [--target]

  fc --sessions [--topology]
                [--condensed]

  fc --help

  fc <command> <command-arguments>
  command can be one of:
    --show      Displays command specific information.
    --sessions   Show FC sessions

  For command-specific help, please type fc --help <command>
  eg:
    fc --help show

```

Replication

To allow DR Series system replication operations, ensure that TCP ports 9904, 9911, 9915, and 9916 are enabled. For more information about supported ports for the DR Series system, see the *DR Series System Administrator Guide*.

The Replication DR Series system CLI command and its options allow you to manage the status of all current replication relationships and tasks on a system by:

- Displaying the current replication process status information
- Creating and defining new replication links or relationships to containers
- Deleting specific replication links
- Starting and stopping the replication process between source and target containers
- Limiting the bandwidth consumed during replication



- Resynchronizing replication between source and target containers
- Troubleshooting replication connection issues

Software versions 3.1 and later support cascaded replication, which involves a Source, Primary Target, and Secondary Target. Each relationship must be set up individually using two sets of replication add commands.

 **NOTE:** You can set a replication schedule for daily replication operations. For details, see [schedule --add --day <day of the week> \[--start_time <hh:mm>\] \[--stop_time <hh:mm>\] \[--cleaner\] \[--replication\]](#).

Replication Command Usage

This topic introduces the **replication** command usage:

- **replication --show [options]**
- **replication --add --name --role --peer [options]**
- **replication --update --name --role --peer [options]**
- **replication --delete --name --role [options]**
- **replication --start --name --role [options]**
- **replication --stop --name --role [options]**
- **replication --limit --speed --target [options]**
- **replication --resync --name --role [options]**
- **replication --troubleshoot --peer**
- **replication --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

replication --show [--name <name>] [--role <source | target>] [--verbose] [--limits]

Description

Displays a detailed summary of replication-related information for a specific replication container in the DR Series system.

Syntax

```
replication --show --name backup --role source --verbose
```

Result

Replication Container ID	:	1
Replication Container	:	backup
Replication Entry ID	:	1
Replication Role	:	Target
Replication MDS Port	:	9915
Replication Data Port	:	9916
Replication Source	:	DR2K-01
Replication Source IP	:	10.250.208.232
Replication Source Mgmt Name	:	DR2K-01
Replication Source Mgmt IP	:	10.250.208.232
Replication Local Data Name	:	DR4100-Test
Replication Local Data IP	:	10.250.240.192
Replication Source Container ID	:	1
Replication Source Container	:	backup
Replication Enabled	:	Yes
Replication Compression Enabled	:	Yes
Replication Encryption	:	AES 128-bit

 **NOTE:** To see how to display the limits set for the replication containers, see [replication --limit --speed <>\[<kbps | mbps | gbps> | default\] --target <ip address | hostname>](#).



replication --show

Description

Displays the current status of all existing replication containers (and respective roles) in the DR Series system.

Syntax

```
replication --show
```

Result

Container Name	Replication Role	Status
backup	Source, Target	Enabled
acme-59	Source	Enabled
acmeStorage1	Source	Enabled
acmeStorage2	Source	Enabled
acmeStorage3	Target	Enabled

replication --show [--limits]

Description

Displays the limits set for your replication containers on the DR Series system.

Syntax

```
replication --show --limits
```

Result

Replication limits are enabled.

Host Name	Target IP	Speed Limit
acme-85	10.21.22.20	192 KBps

 **NOTE:** You can limit the bandwidth consumed by the replication process by setting a value in kilobytes/second (kbps), megabytes/second (mbps), gigabytes/second (gbps), or use an unlimited bandwidth (default). The minimum allowed bandwidth setting for a DR Series system is 192 kbps.

For more information, see [replication --limit --speed <> <kbps | mbps | gbps> | default> --target <ip address | hostname>](#).

replication --add --name <name> --role <source | target> --peer <ip address | hostname> [--peer_name <name>] [--peer_group_name <name>] [--replication_traffic <ip address | hostname>] [--encryption <none | aes128 | aes256>] [--username <user name>]

Description

Adds a new replication link to a container on the DR Series system, for which you need to define its name, role, peer appliance IP address/hostname , peer name, peer group name, user name on the peer system, and encryption level to apply. The peer group name is the name of the remote container's group to replicate to/from, and this parameter is applicable only if a remote container is not present.

There are three options for encryption: none, aes128 (Advanced Encryption Standard), using 128-bit cryptographic keys, and aes256 (using 256-bit AES cryptographic keys).

If the username is a domain login (for example, domain\username), ensure that '\' characters and spaces are either escaped or in quotes.

 **NOTE:** Make sure that the data container you intend to replicate already exists. If it does not, the following error message displays: *Error: Container <container_name> does not exist.*

Syntax

```
replication --add --name backup --role source --peer 10.250.240.192 --  
encryption aes128
```



Result

```
Enter password foradministrator@10.250.240.192:  
Replication entry created successfully.  
Replication Container : backup  
Replication Role : Source  
Replication Target : 10.250.240.192  
Replication Target IP : 10.250.240.192  
Replication Target Mgmt Name : 10.250.240.192  
Replication Target Mgmt IP : 10.250.240.192  
Replication Local Data Name : DR2K-01  
Replication Local Data IP : 10.250.208.232  
Replication Target Container : backup  
Replication Enabled : Yes  
Replication Compression Enabled: Yes  
Replication Encryption : AES 128-bit
```

 **NOTE:** To verify that you have successful added a replication link to the DR Series system (or to view the current status of existing containers), see [replication --show](#).

replication --update --name <name> --role <source | target> [--peer <ip address | hostname>] [--encryption <none | aes128 | aes256>] [--username <user name>]

Description

Updates an existing replication link to a container in a DR Series system and allows you to change the corresponding role, peer IP address or host name, the encryption being used, and user name based on the DR Series system CLI command options you specify.

Syntax

```
replication --update --name backup --role source --peer 10.25.19.5
```

Result

 **NOTE:** If you attempt to update a container that already has replication enabled, this displays the following message:

Replication on backup is enabled and cannot be updated, please stop it first.

When replication is enabled on the container, you must first disable it before you can update it. To disable replication on a container, enter the DR Series system CLI **replication --stop** command and define the container name and role:

```
replication --stop --name <name> --role <source | target>
```

 **NOTE:** For more information about disabling replication, see [replication --stop --name <name> --role <source | target>](#).

Disables replication on a container:

```
replication --stop --name backup --role source  
Replication configuration updated successfully.  
Replication Container : backup  
Replication Role : Source  
Replication Target System : acme-85  
Replication Target System IP : 10.25.192.5  
Replication Target Container : acme85-S2  
Replication Enabled : No  
Replication Compression Enabled : Yes  
Replication Encryption : AES 128-bit
```

replication --delete --name <name> --role <source | target> [--force]

Description

Deletes an existing replication link to a container in a DR Series system.



 **NOTE:** It is recommended that the replication be in an INSYNC state for this operation. If replication is not in an INSYNC state, this operation can potentially take a much longer time to execute.

Syntax

```
replication --delete --name acme-59-replica --role target
```

If you attempt to delete a container that already has replication enabled, this displays the following message:

Replication on acme-59-replica is enabled and cannot be deleted, please stop it first.

 **NOTE:** If the replication state of the link is enabled, you must use the replication --stop command to disable replication before you can delete the replication link. For more information, see [replication --stop --name <name> --role <source | target>](#).

Deletes the existing replication link to a container.

```
replication --delete --name acme-59-replica --role source
```

Result

Successfully deleted replication entry.

 **NOTE:** The DR Series system CLI --force command is optional, and this command allows you to force the deletion of an existing replication link (such as when communications between the source and target are not working).

replication --start --name <name> --role <source | target>

Description

Starts the replication process on an existing replication link to a container in a DR Series system.

Syntax

```
replication --start --name container2_replica --role target
```

Result

Replication configuration updated successfully.
Replication Container : container2_replica
Replication Role : Source
Replication Target System : acme-85
Replication Target System IP : 10.20.22.20
Replication Target Container : acme85-S2
Replication Enabled : Yes
Replication Compression Enabled : Yes
Replication Encryption : AES 128-bit

replication --stop --name <name> --role <source | target>

Description

Stops the replication process on an existing replication link to a container in a DR Series system.

Syntax

```
replication --stop --name acme-59_replicate --role source
```

Result

Replication configuration updated successfully.
Replication Container : acme59
Replication Role : Source
Replication Target System : acme-85
Replication Target System IP : 10.20.22.20
Replication Target Container : acme85-S2
Replication Enabled : No



```
Replication Compression Enabled : Yes
Replication Encryption          : AES 128-bit
```

replication --limit --speed <>num><KBps | MBps | GBps> | default> --target <ip address | hostname>

Description

Limits the bandwidth used during replication by defining a bandwidth limit using any of the following settings:

- Kilobytes/second (KBps)
- Megabytes/second (MBps)
- Gigabytes/second (GBps)
- Unlimited bandwidth (this is the default setting); minimum allowed bandwidth setting is 192 KBps

Configures replication limits for a DR Series system.

Syntax

```
replication --limit --speed 10gbps --target acme-60
```

Result

```
Successfully updated replication limit for acme-60 to 10 GBps.
Changing traffic control policies ... done.
```

replication --resync --name <name> --role <source | target>

Description

Resynchronizes the replication process between a source and target container in a replication relationship on a DR Series system. This command should only be used in an emergency situation with the help of Technical Support. Do not mistake this command as an ability to start a replication sync outside of the schedule window. If your intention is to start a replication outside of the window, you can either delete the schedule, or add a temporary replication window to the current schedule and delete it when the systems are in sync.

Syntax

```
replication --resync --name dataStorage3 --role source
```

Result

```
Successfully initiated replication resync on container dataStorage3.
```

replication --troubleshoot --peer <ip address | hostname>

Description

Troubleshoots the replication connections between a source and target container on a DR Series system.

 **NOTE:** This command only reports 9915 and 9916 as succeeding against a replication peer that has native DR Series replication configured to another system. If the peer is not currently using any replication ports, 9915 and 9916 will report as connection refused (by the DR Series system).

Syntax

```
replication --troubleshoot --peer 10.25.19.5
```

Result

The following examples shows both successful and unsuccessful replication connection attempts:

```
Testing connection to port 9904... Connected!
Testing connection to port 9911... Connected!
Testing connection to port 9915... Connected!
Testing connection to port 9916... Connected!
```



```
Replication troubleshooting completed successfully - Connection to all ports is OK!
```

```
replication --troubleshoot --peer acme-205
Testing connection to port 9904... Connected!
Testing connection to port 9911... Connected!
Testing connection to port 9915...
Unable to connect to socket - Connection refused
Could not connect to acme-205 on port 9915 - (Connection refused)
Testing connection to port 9916...
Unable to connect to socket - Connection refused
Could not connect to acme-205 on port 9916 - (Connection refused)
```

replication --help

Description

Displays the list of all replication-related options that can be used as a reference when using the DR4000 system CLI.

Syntax

```
replication --help
```

Result

Usage:

```
replication --show [--name <name>]
                   [--role <source | target>]
                   [--verbose]
                   [--limits]

replication --add --name <name>
              --role <source | target>
              --peer <ip address | hostname>
              [--peer_name <name>]
              [--username <user name>]
              [--encryption <none | aes128 | aes256>]

replication --update --name <name>
              --role <source | target>
              [--peer <ip address | hostname>]
              [--encryption <none | aes128 | aes256>]
              [--username <name>]

replication --delete --name <name>
              --role <source | target>
              [--force]

replication --start --name <name>
              --role <source | target>

replication --stop --name <name>
              --role <source | target>

replication --limit --speed <><num><kbps | mbps | gbps | default>
              --target <ip address | hostname>

replication --resync --name <name>
              --role <source | target>

replication --troubleshoot --peer <ip address | hostname>

replication --help

replication <command> <command-arguments>
<command> can be one of:
  --show           Displays command specific information.
  --add            Adds a replication link to a container.
```



```

--update      Updates a replication link to a container.
--delete      Deletes a replication link from a container.
--start       Starts replication.
--stop        Stops replication.
--limit        Limits bandwidth consumed by replication.
--resync      Initiates a replication re-sync.
--troubleshoot Troubleshoots replication connection.

```

For command-specific help, please type `replication --help <command>`

For example:

```
replication --help show
```

Seed

The DR Series system seed operations allow for exporting data on the source to a portable seed device to then import the seed data to a primary target, and, if required, a secondary target as well. Replication seeding is an alternative to using network bandwidth for the initial re-synchronization of the source and target(s). After the target(s) are seeded, continuous replication can be started, which will keep the target(s) up to date by sending only unique data.

The DR Series CLI seed commands support the following operations:

- Create a job to perform seeding export or import.
- Delete an existing seeding export or import job.
- Specify containers for seeding export.
- Add a device to be used for seeding.
- Remove a device which is already added for seeding.
- Start seeding process (export/import).
- Stop running seeding process (export/import).
- Start cleaner to process seed ZL logs on target.

 **NOTE:** The seeding device must be a CIFS share: a USB device connected to a Windows or Linux system and shared for import as a CIFS-mounted folder.

 **NOTE:** The following scenarios are not supported for seeding:

- Import AND export from one share/device cannot occur at the same time.
- Import from one share/device cannot be completed from multiple locations at the same time.
- Export to a mount point can be completed only from one seed job. Multiple seed export jobs cannot send data to a single mount point.

See the white paper, *Seeding from a DR Series System to an External Device using CLI*, at support.quest.com/DR-Series for more information.

Seed Command Usage

This topic introduces the seed command usage:

- `seed --create --op <options> [--enc_type <options>]`
- `seed --delete`
- `seed --add_container --name <container name>`
- `seed --remove_container --name <container name>`
- `seed --add_device --server <server name> --volume <volume> --username <user name> --domain <domain name>`

- seed --remove_device
- seed --start
- seed --stop
- seed --show
- seed --cleanup
- seed --help

seed --create --op <import | export> [--enc_type <aes128 | aes256>] [--storage_group_name <name>]

Description

Creates a seed export job of type import or export on the source DR. The command will prompt for a password, and this password will be requested on the target to import the data. The command allows you to specify the type of encryption that will be used to encrypt the data on the seed device. The default value is aes256. The default value for storage group name is DefaultGroup.

Syntax

```
seed --create --op export --enc_type aes256 --storage_group_name cust1
```

Result

```
Enter password for seed export:  
Re-enter password for seed export:  
Successfully created seed job details.
```

seed --add_container --name <container name>

Description

Adds the container(s) that you want to seed. A new invocation of seed --add_container command needs to be executed for every container that you want to seed.

Syntax

```
seed --add_container --name acme-container1
```

Result

```
Successfully added seed container.
```

seed --add_device --server <server name> --volume <volume> --username <username> --domain <domain name>

Description

Adds a target device to the job. This is a USB device, which is CIFS shared from a Windows or Linux system.

 **NOTE:** During seeding import, when a device is added to be used as target device, it can be used only for one job. To use it for another job, you need to delete all the seeding contents from the device. You can create separate folders on this device and can use each folder for a job.

Syntax

```
seed --add_device --server 10.250.224.81 --volume seed-device --username administrator --domain testad.acme.local
```

Result

```
Enter password for administrator@10.250.224.81:  
Successfully added seed device.
```



seed --cleanup

Description

Starts the cleaner to remove data not referenced on the target.

 **NOTE:** You should run the seeding cleaner only when the system is idle and no ingest or replication tasks are in progress. When the seeding cleaner is run during replication, for example, there is a chance of missing data during the seeding process. However, this data will eventually be sent during resync.

Syntax

```
seed --cleanup
```

Result

```
Successfully added seed ZL logs to cleaner queue
```

seed --create --op <import> [--enc_type <aes128 | aes256>]

Description

Execute the import steps on the target DR. Create a seed import job. Here you have to choose the same encryption type and password that was used to initially create the seed export job. Add the device to the import job the same way you added the device to the export job by using seed --add_device. You will also need to use seed --start to start importing data.

To see the progress of the data import, use stats --seed. After the job completes, remove the target device and set up replication between the source and target DR. A re-sync will be run to bring the target up to date with the source. After the re-sync completes, issue a seed --cleanup command on the target.

Syntax

```
seed --create --op import --enc_type aes256
```

Result

```
Enter password for seed import:  
Re-enter password for seed import:  
Successfully created seed job details.
```

seed --remove_device

Description

Remove the target device. This is an important step without which stats and other information will not be saved on the target device.

Syntax

```
seed --remove_device
```

Result

```
Successfully deleted device details
```

seed --show

Description

Used to show the configured seed job.

Syntax

```
seed --show
```



Result

```
Device info
=====
Server :10.250.224.81
Volume :seed-device
Username :administrator
Domain :testad.acme.local

Job info
=====
Operation :Export
Status :Started
Container :acme-container1
Encryption type :aes256
```

seed --start

Description

Starts the seeding job. You will be prompted to add additional devices if a single device does not have enough space.

Syntax

```
seed --start
```

Result

Successfully started seed job.

seed --help

Description

Displays the list of all seed command related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
seed --help
```

Result

Usage:

```
    seed --create --op <import|export>
        [--enc_type <aes128 | aes256>]
        [--storage_group_name <name>]

    seed --delete
    seed --add_container --name <container name>

    seed --remove_container --name <container name>

    seed --add_device --server <server name>
        --volume <volume>
        --username <user name>
        [--domain <domain name>]

    seed --remove_device
    seed --start
    seed --stop
    seed --show
    seed --cleanup
    seed --help

seed <command> <command-arguments>
    command can be one of:
```



import.	--create	Create a job to perform seeding export or import.
	--delete	Delete an existing seeding export or import job.
	--add_container	Add a container to be used for seeding export.
seeding export.	--remove_container	Remove a container which is already added for seeding.
	--add_device	Add a device to be used for seeding.
seeding.	--remove_device	Remove a device which is already added for seeding.
	--start	Start seeding process(export/import).
	--stop	Stop running seeding process(export/import).
	--show	Show registered device, job for seeding.
	--cleanup	Start cleaner to process seed ZL logs on target.

For command-specific help, please type `seed --help <command>`
 eg:
`seed --help create`

Schedule

A schedule is the means by which you set aside specific daily time periods for performing disk space reclamation or replication operations. Disk reclamation operations recover unused disk space from DR Series system containers in which files were deleted; replication operations are the process by which the key data is saved only once from multiple devices to minimize excessive or redundant storage of the same data.

This set of DR Series system CLI commands allow you to perform the following tasks on a system:

- Display existing scheduled Replication and Cleaner (disk space recovery) operations
- Create new schedules for Replication and Cleaner operations
- Delete existing scheduled Replication and Cleaner operations

Schedule Command Usage

This topic introduces the **schedule** command usage:

- **schedule --show [options]**
- **schedule --add --day <Day of the week (Sunday|Monday...)> [options]**
- **schedule --delete --day <Day of the week (Sunday|Monday...)> [options]**
- **schedule --help**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

schedule --show [--cleaner]

Description

Displays any existing Cleaner schedule for a DR Series system.

Syntax

`schedule --show --cleaner`

Result

Cleaner Schedule:

		Start	Stop
Sunday		05:00	06:00
Monday		05:00	06:00
Tuesday		05:00	06:00
Wednesday		05:00	06:00
Thursday		05:00	06:00



Friday	05:00	06:00
Saturday	05:00	06:00

schedule --show [--replication] [--name <name>]

Description

Displays any existing replication schedule for a DR Series system. If you do not specify a name parameter, the replication schedules for all containers are returned.

Syntax

```
schedule --show --replication --name acme55-cont1
```

Result

Replication Schedule:

	Start	Stop
Sunday	22:00	05:00
Monday	22:00	05:00
Tuesday	22:00	05:00
Wednesday	22:00	05:00
Thursday	22:00	05:00
Friday	22:00	05:00
Saturday	22:00	05:00

schedule --add --day <day of the week> [--cleaner] [--replication] [--start_time <hh:mm>] [--stop_time <hh:mm>] [--name <name>]

Description

Creates a new Cleaner or Replication schedule for a DR Series system (on a source DR). For a specific container, you would use the **--name <name>** command option with the start time and stop time set points.

-  **NOTE:** Without any Cleaner schedule set, the DR Series system Cleaner process automatically starts within two minutes after it detects that no data ingest operation or other system operation activity is present. So, if your DR Series system runs intermittent or inconsistent ingest, readback, or replication operations, there is no need to set a Cleaner schedule (it will automatically run during periods of low or non-activity). However, if your system runs regular and consistent ingest, readback, or replication operations, you should create a Cleaner schedule that runs only during a known period of low or non-activity (for example, on a day or time period sufficient to complete this process). If your system does not meet either of these cases, you can still manually run the Cleaner. For more information, see [maintenance --filesystem \[-reclaim_space\]](#).

Syntax

```
schedule --add --day Sunday --start_time 06:00 --stop_time 22:00 --cleaner
```

-  **NOTE:** Set a corresponding stop time for every start time in each Cleaner (or Replication) schedule you create. The following example shows setting up a Cleaner schedule for the remainder of the week (Monday through Saturday).
-  **NOTE:** Do not select 00:00 for a start time or stop time endpoint for midnight when setting Cleaner or Replication schedules (instead, use either the 23:59 or 00:05 value).

Result

Successfully updated Cleaner schedule.

-  **NOTE:** To create a Replication schedule (use the DR Series system CLI **--replication** command), and the same process shown here to schedule the start and stop times for a Replication schedule. This lets you schedule start and stop times for each day in the week in which you want the Replication process to run.



schedule --delete --day <day of the week> [--cleaner] [--name <name>] [--replication]

Description

Deletes a day in an existing Cleaner or Replication schedule for a DR Series system (on a source DR). The --name option is only applicable for replication and not for the cleaner. You can use it to specify a container.

 **NOTE:** To delete days from either an existing Cleaner or Replication schedule, specify the day in the week and the schedule type.

Syntax

```
schedule --delete --day Sunday --replication --name Container1
```

Result

Successfully updated Replication schedule.

schedule --help

Description

Displays the list of schedule-related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
schedule --help
```

Result

Usage:

```
schedule --show [--cleaner]
                [--replication]
                [--name <name>]

schedule --add --day <Day of the week (Sunday|Monday...)>
                [--start_time <hh:mm>]
                [--stop_time <hh:mm>]
                [--cleaner]
                [--replication]
                [--name <name>]

schedule --delete --day <Day of the week (Sunday|Monday...)>
                [--cleaner]
                [--name <name>]
                [--replication]

schedule --help
```

schedule <command> <command-arguments>
<command> can be one of:

```
--show      Displays command specific information.
--add       Adds a schedule for replication/cleaner (use on source DR).
--delete    Deletes a replication/cleaner schedule (use on source DR).
```

For command-specific help, please type schedule --help <command>

For example:

```
schedule --help show
```

Data Integrity Checking

The DR Series system design includes an online data integrity verification feature known as Data Check, which checks for potential or unexpected data inconsistencies in the data store associated with the internal system deduplication engine. Data Check performs a series of checks for unexpected data inconsistencies as early as possible in the data ingest and backup process.

Data Check checks and verifies data both during the write process and also the data already stored on the system disks. The design purpose is to detect potential issues early enough in the data management process so that original data can be used to backup and correct any potential data inconsistencies. Data Check reports data verification issues, but it is not intended nor designed to repair these issues itself.

Any data inconsistencies that are encountered are reported as DR Series system alerts, and these filesystem errors can be repaired using the **Maintenance** mode (for more information, see [Maintenance](#)).

The Data Check feature runs continuously except for when the DR Series system enters its **Maintenance** mode (it does not run while the system is in this mode). Data Check leaves the system in an **Operational** mode when it detects an error, at which point, it sends an alert and an event.

If an alert has already been sent, but has not been cleared (for example, when repairs occur during the **Maintenance** mode), no new event is sent. Similarly, for events, one is sent for the first detected data inconsistency, and then the total number of issues detected during the scan are listed in a new event.

If Data Check is enabled, it runs in the background as a low-priority process, and changes to an idle state when the other major DR Series system operations (data ingest, replication, and cleaner) are active.

 **NOTE:** Unless otherwise noted, all later references to `datacheck` or **Data Check** in this guide are used interchangeably to represent the **Data Check** feature in the DR Series system.

About Data Check

The purpose of the Data Check feature is to perform data integrity checks to detect potential silent data inconsistencies that can affect the DR Series system disks or disk subsystems, and protect user data before there is any potential data loss.

Silent data inconsistencies can be any of the following types of disk-based data storage issues: hardware imperfections, bit rot, current spikes, disk firmware problems, and ghost writes. Data Check performs its own integral data integrity checks that detect and identify potential issues after performing the following scans:

- Priority write verify scans
- Continuous data verification scans

For more information, see [Continuous Data Verification Scans](#) and [Priority Write Verify Scans](#).

Priority Write Verify Scans

Data Check performs an early write verify scan, also known as a **namespace** scan, when files are first created or when they are modified by users. All of the modified files are flagged for priority scanning and this process is based on its timestamp—with a higher priority given to the most recently modified files. Early write verify scans are performed every five minutes when the other DR Series system operations are idle. For more information, see [About Data Check](#) and [Continuous Data Verification Scans](#).



Continuous Data Verification Scans

Data Check performs a data verification scan, also known as a **blockmap** scan, which cycles every two hours through all of the objects in the data store. Data integrity verification is done by recalculating the hash values for the underlying data, and comparing these to the stored hash values using an additional checksum process. Any unexpected data inconsistencies are reported using the DR Series system alerts process.

For more information, see [About Data Check](#) and [Priority Write Verify Scans](#).

Data Check CLI Commands

These DR Series system CLI commands allow you to perform the following Data Check-related scans and display current Data Check status. There are two sets of Data Check related DR Series system CLI commands: **system --datacheck** and **stats --datacheck**.

system --datacheck Commands

- Display the current Data Check state (enabled/disabled status for **namespace**, **blockmap**, or **all**). For more information, see [system --datacheck](#).
- Enable Data Check scans (**namespace**, **blockmap**, or **all**). For more information, see [system --datacheck \[--enable <all | namespace | blockmap>\]](#).
- Disable Data Check scans (for **namespace**, **blockmap**, or **all**). For more information, see [system --datacheck \[--disable <all | namespace | blockmap>\]](#).
- Set the percentage of available system resources to use for Data Check scans. For more information, see [system --datacheck \[--throttle <1-100>\]](#).
- Display the list of Data Check help-related options that can be used as a reference when using the CLI. For more information, see [system --help datacheck](#).

stats --datacheck Commands

- Display the variety of Data Check statistics collected by the DR4000 system. For more information, see [stats --datacheck](#).
- Reset the Data Check statistics in the DR4000 system. For more information, see [stats --reset --datacheck](#).
- Display the list of Data Check-related options that can be used as a reference when using the DR Series system CLI. For more information, see [stats --help datacheck](#).

Data Check Options

Data Check performs data integrity checks that detect potential silent data inconsistencies that can affect the system disks or disk subsystems, and protect user data. Data Check provides the following options that can be set for DR Series system data scan operations:

- Namespace (**system --datacheck --enable namespace**).
- Blockmap (**system --datacheck --enable blockmap**).
- All (**system --datacheck --enable all**); this is the default setting where both namespace and blockmap are enabled.

Data Check: Namespace Scan Option

The namespace scan option focuses on file attributes such as file size, file name, permissions, and last time modified. Data integrity verification is done using a checksum process. You can choose to enable or disable the Data Check namespace scan in the DR Series system based on the command setting you select.

Data Check: Blockmap Scan Option

The blockmap scan option identifies a specific mapping of data contained within a block, with a block being a structured form of data that the DR Series system can identify. You can choose to enable or disable the Data Check blockmap scan based on the command option you select.



Data Check: All Data Scan Option

The All scan option is one of three options that can be selected for DR Series system data scan operations. The All scan option identifies that both the namespace and blockmap options are to be included in the Data Check commands. You can choose to enable or disable Data Check scans for both namespace and blockmap in the DR Series system based on the specific command option you select.

System --Datacheck

This set of DR Series system CLI commands allow you to display the current Data Check status, enable and disable Data Check scans on the DR Series system, set the throttle percentage of system resources to use for Data Check scans, and display the system Data Check help-related options. For more information, see [System --Datacheck Command Usage](#).

System --Datacheck Command Usage

This topic introduces the **system --datacheck** command usage:

- **system --datacheck**
- **system --datacheck--enable [options]**
- **system --datacheck --disable [options]**
- **system --datacheck --throttle [options]**
- **system --help datacheck**

 NOTE: If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

system --datacheck

Description

Displays the current status of Data Check on a DR Series system.

Syntax

```
system --datacheck
```

Result

```
Data Check : Enabled - namespace,blockmap,throttle:50%
```

```
Data Check : Disabled
```

 NOTE: The first example shows that both --namespace and --blockmap scans are enabled, and the default --throttle setting (50%) is on for the DR Series system. As shown in the second example, a Data Check status of disabled indicates that both the --namespace and --blockmap scans are disabled on the DR Series system.

system --datacheck --disable

Disables one or both Data Check scan option types that can be used on a DR Series system. You can individually disable **namespace** or **blockmap** scan options, or both options using the **all** scan option (which means that both the **namespace** and **blockmap** scan types will be disabled).

Description

Disables an individual Data Check scan option type (or both scan types) when used in a DR Series system CLI command.

Syntax

```
system --datacheck [--disable <all | namespace | blockmap>]
```



Result

Data Check configuration successful: all scans currently disabled.

 **NOTE:** This example shows all Data Check scan options being disabled. To disable only the namespace or the blockmap scan, use those options respectively in the DR Series system CLI command, for example, --disable --namespace, or --disable --blockmap.

system --datacheck --enable

Enables one or both Data Check scan options that can be used on a DR Series system. The enable option can be set to all, namespace, or blockmap. You can individually enable **namespace** or **blockmap** scan options, or both options using the **all** scan option (which means that both the **namespace** and **blockmap** scan types will be enabled).

Description

Enables an individual Data Check scan option type (or both scan types) when used in a DR Series system CLI command.

Syntax

```
system --datacheck [--enable <all | namespace | blockmap>]
```

Result

Data Check configuration successful: namespace and blockmap scans currently enabled.

 **NOTE:** This example shows all Data Check scan options enabled. To enable only the namespace or only the blockmap scan, use those options respectively in the DR Series system CLI command, for example, --enable --namespace, or --enable --blockmap.

system --datacheck --throttle

Use the Data Check **--throttle** option to specify the percentage of available DR Series system resources you want to use when running Data Check scans when the other system operations (data ingest, Replication, and Cleaner processes) are idle. The range is between 1 to 100 percent (%), and the default is 50%.

Description

Enables Data Check scans to use any percentage (1–100) of available DR Series system resource that you define. In this example, 75% of the available DR Series system resources are selected.

Syntax

```
system --datacheck [--throttle <1-100>]
```

Result

Data Check configuration successful: throttle set to 75%.

system --help datacheck

Description

Displays the list of **system --datacheck** related options that can be used as a reference when using the DR Series system CLI.

Syntax

```
system --help datacheck  
--datacheck - Displays statistics for online data verification.
```

Result

Usage:

```
system --datacheck
```



```

[--enable <all|namespace|blockmap>]
[--disable <all|namespace|blockmap>]
[--throttle <1-100>]

--enable           Enables online data verification scans.
--disable          Disables online data verification scans.
--throttle        Sets the online data verification throttle percentage.

```

stats --datacheck

This set of DR Series system CLI commands allow you to display the current Data Check statistics gathered by the system, reset the Data Check statistics for the system, and display the statistic-based Data Check help-related options. For more information, see [Stats --Datacheck Command Usage](#).

stats --datacheck Command Usage

This topic introduces the **stats --datacheck** command usage:

- **stats --datacheck**
- **stats --reset --datacheck**
- **stats --help datacheck**

 **NOTE:** If you specify a command without supplying the expected value or option, you will be prompted to provide the correct value or option.

stats --datacheck

Description

Displays the current set of datacheck statistics on a DR Series system.

 **NOTE:** The Progress field in the statistics can indicate one of three values: Waiting, Running, and Idle.

- **Waiting:** Data Check is in this state because another operation is now running.
- **Running:** Data Check is in this state when running the scans.
- **Idle:** Data Check is in this state waiting for the next opportunity to run the Data Check scans.

The following example shows the status of active DR Series system operations in response to the **stats --datacheck** command on a DR Series system when Data Check is enabled.

Syntax

```
stats --datacheck
```

Result

Data Check	: Enabled -
namespace,blockmap,throttle:75%	
Progress	: Idle
Active Writes	: No
Active System Operations	: No
Total Detected Errors	: 0
Last Complete Namespace Scan	: 2012-02-02 17:48:18
Last Complete Blockmap Scan	: 2012-02-02 16:33:08
Namespace Scans Completed	: 183
Namespace Scan Entries	: 6
Namespace Scan Errors	: 0
Namespace Scan Start Time	: 2012-02-02 17:43:08
Namespace Scan Progress	: 100.00%
Blockmap Scans Completed	: 8
Blockmap Scan Entries	: 3
Blockmap Scan Errors	: 0



```
Blockmap Scan Start Time      : 2012-02-02 16:33:06
Blockmap Scan Progress        : 100.00%
```

Other Examples

This example shows the output from the **stats --datacheck** command used on a DR Series system when Data Check is disabled.

```
stats --datacheck

Online Data Verification      : Disabled
Progress                      : Disabled
Active Writes                  : No
Active System Operations       : No
Total Detected Errors         : 0
Last Complete Namespace Scan  : 2012-01-24 15:50:10
Last Complete Blockmap Scan   : 2012-01-24 15:55:59
```



Additional Linux Commands

This topic introduces additional Linux commands that have limited usage when used with the DR Series system CLI:

- **grep**
- **more**

While these Linux commands are available to the user, this topic and other topics related to these commands are not intended to be a reference source for these commands. You can consult a Linux command reference guide for more information about these commands and how they can be used.

grep

Description

Displays the supported usage of the Linux **grep** command with the DR Series system.

Syntax

```
grep --help
```

Result

```
Usage: grep [OPTION]... PATTERN [FILE] ...
Search for PATTERN in each FILE or standard input.
Example: grep -i 'hello world' menu.h main.c

Regexp selection and interpretation:
-E, --extended-regexp      PATTERN is an extended regular expression
-F, --fixed-strings        PATTERN is a set of newline-separated strings
-G, --basic-regexp         PATTERN is a basic regular expression
-P, --perl-regexp          PATTERN is a Perl regular expression
-e, --regexp=PATTERN       use PATTERN as a regular expression
-f, --file=FILE             obtain PATTERN from FILE
-i, --ignore-case          ignore case distinctions
-w, --word-regexp          force PATTERN to match only whole words
-x, --line-regexp           force PATTERN to match only whole lines
-z, --null-data             a data line ends in 0 byte, not newline

Miscellaneous:
-s, --no-messages          suppress error messages
-v, --invert-match          select non-matching lines
-V, --version                print version information and exit
--help                      display this help and exit
--mmap                      use memory-mapped input if possible

Output control:
-m, --max-count=NUM         stop after NUM matches
-b, --byte-offset            print the byte offset with output lines
-n, --line-number             print line number with output lines
--line-buffered              flush output on every line
-H, --with-filename          print the filename for each match
-h, --no-filename             suppress the prefixing filename on output
--label=LABEL                 print LABEL as filename for standard input
```



```

-o, --only-matching      show only the part of a line matching PATTERN
-q, --quiet, --silent    suppress all normal output
--binary-files=TYPE      assume that binary files are TYPE
                         TYPE is 'binary', 'text', or 'without-match'
-a, --text                equivalent to --binary-files=text
-I                       equivalent to --binary-files=without-match
-d, --directories=ACTION  how to handle directories
                         ACTION is 'read', 'recurse', or 'skip'
-D, --devices=ACTION      how to handle devices, FIFOs and sockets
                         ACTION is 'read' or 'skip'
-R, -r, --recursive       equivalent to --directories=recurse
--include=PATTERN         files that match PATTERN will be examined
--exclude=PATTERN         files that match PATTERN will be skipped.
--exclude-from=FILE       files that match PATTERN in FILE will be skipped.
-L, --files-without-match only print FILE names containing no match
-l, --files-with-matches  only print FILE names containing matches
-c, --count                only print a count of matching lines per FILE
-Z, --null                 print 0 byte after FILE name

Context control:
-B, --before-context=NUM   print NUM lines of leading context
-A, --after-context=NUM    print NUM lines of trailing context
-C, --context=NUM          print NUM lines of output context
--NUM                      same as --context=NUM
--color[=WHEN],             use markers to distinguish the matching string
--colour[=WHEN]             WHEN may be `always', `never' or `auto'.
-U, --binary                do not strip CR characters at EOL (MSDOS)
-u, --unix-byte-offsets     report offsets as if CRs were not there (MSDOS)

`egrep' means `grep -E'.  `fgrep' means `grep -F'.
With no FILE, or when FILE is -, read standard input.  If less than
two FILES given, assume -h.  Exit status is 0 if match, 1 if no match,
and 2 if trouble.

```

Report bugs to <bug-grep@gnu.org>.

more

Description

Displays the supported usage of the Linux **more** command with the DR Series system.

Syntax

`more --help`

Results

`usage: more [-dflpstu] [+linenum | +/pattern] name1 name2 ..`

